



**EXTENDED MONITORING AND ANALYSIS OF MOISTURE-
TEMPERATURE DATA**

ODOT 8881
State Job No. 14694(0)

FINAL REPORT

Submitted to
The Ohio Department of Transportation



Case Western Reserve University
Department of Civil Engineering

October, 2001

Prepared in Cooperation with the Ohio Department of Transportation and the
U.S. Department of Transportation, Federal Highway Administration

Reproduced from
best available copy.



**PROTECTED UNDER INTERNATIONAL COPYRIGHT
ALL RIGHTS RESERVED
NATIONAL TECHNICAL INFORMATION SERVICE
U.S. DEPARTMENT OF COMMERCE**

REPRODUCED BY:
U.S. Department of Commerce
National Technical Information Service
Springfield, Virginia 22161



EXTENDED MONITORING AND ANALYSIS OF MOISTURE- TEMPERATURE DATA

FHWA REPORT No. FHWA/OH-2001/10
Author: Dr. J. Ludwig Figueroa
Performing Organization: Case Western Reserve University
State Job No. 14694(0)
Date: October, 2001

Executive Summary

The performance of asphalt concrete pavements is in part affected by the seasonal variations of the resilient modulus of the AC layer and of the subgrade soil. To determine the variation of these parameters throughout Ohio, nine moisture-temperature-rainfall recording stations, previously installed during two Ohio Department of Transportation-funded projects, were monitored for an additional period of three years. These stations, located to include various climatic zones and the four most common soil types within the state, recorded air, asphalt concrete and subgrade soil temperature, rainfall and moisture content (or degree of saturation) of the subgrade soil on a two-hour basis.

Recorded data led to the development of polynomial equations to calculate the average asphalt concrete pavement temperature from the air temperature and to the division of the state into three temperature zones: Northern, Central and Southern. Monthly and seasonal average values of the resilient modulus of the asphalt concrete for each station, the three climatic zones and for all of the state were also calculated.

Recorded depths of frost penetration indicated average depths of 45 to 61 cm. within the southern zone and of 70 to 82 cm. within the northern zone. Similarly, the northern and the southern zones experience an average of 7 to 12 and 4 to 5 freeze-thaw cycles, respectively.

The degree of saturation calculated from moisture and temperature sensor readings varied from about 90% to 100% throughout the monitoring period. The late spring to early summer consistently led to a higher degree of saturation at all depths.

Finally, a method to back calculate the resilient modulus of subgrade soils at the break point from measured FWD deflections was developed. Seasonal averages of this modulus were obtained at each of six station locations where FWD testing was conducted. Seasons were ranked in terms of expected higher resilient modulus. The designated "fall" testing period (early fall) showed the highest followed by "summer", "winter" and "spring" in decreasing order. Determined monthly and seasonal variation of material properties will find immediate application as inputs in mechanistic-empirical pavement design procedures.

FOR COPIES OF THIS REPORT, CONTACT:

Ohio Department of Transportation
Office of Research and Development
(614) 728-6048
research@dot.state.oh.us

1. Report No. FHWA/OH-2001/10	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and subtitle. Extended Monitoring and Analysis of Moisture Temperature Data		5. Report Date October, 2001	
		6. Performing Organization Code	
7. Author(s) Dr. J. Ludwig Figueroa		8. Performing Organization Report No.	
		10. Work Unit No. (TRAIS)	
9. Performing Organization Name and Address Case Western Reserve University Department of Civil Engineering 10900 Euclid Avenue Cleveland, OH 44106-7201		11. Contract or Grant No. State Job No. 14694(0)	
		13. Type of Report and Period Covered Final Report	
12. Sponsoring Agency Name and Address Ohio Department of Transportation 1980 W Broad Street Columbus, OH 43223		14. Sponsoring Agency Code	
		15. Supplementary Notes	
16. Abstract <p>The performance of asphalt concrete pavements is in part affected by the seasonal variations of the resilient modulus of the AC layer and of the subgrade soil. To determine the variation of these parameters throughout Ohio, nine moisture-temperature-rainfall recording stations, previously installed during two Ohio Department of Transportation-funded projects, were monitored for an additional period of three years. These stations, located to include various climatic zones and the four most common soil types within the state, recorded air, asphalt concrete and subgrade soil temperature, rainfall and moisture content (or degree of saturation) of the subgrade soil on a two-hour basis. Recorded data led to the development of polynomial equations to calculate the average asphalt concrete pavement temperature from the air temperature and to the division of the state into three temperature zones: Northern, Central and Southern. Monthly and seasonal average values of the resilient modulus of the asphalt concrete for each station, the three climatic zones and for all of the state were also calculated. Recorded depths of frost penetration indicated average depths of 45 to 61 cm. within the southern zone and of 70 to 82 cm. within the northern zone. Similarly, the northern and the southern zones experience an average of 7 to 12 and 4 to 5 freeze-thaw cycles, respectively. The degree of saturation calculated from moisture and temperature sensor readings varied from about 90% to 100% throughout the monitoring period. The late spring to early summer consistently led to a higher degree of saturation at all depths. Finally, a method to back calculate the resilient modulus of subgrade soils (E_{ri}) at the break point from measured FWD deflections was developed. Seasonal averages of this modulus were obtained at each of six station locations where FWD testing was conducted. Seasons were ranked in terms of expected higher resilient modulus. The designated "fall" testing period (early fall) showed the highest followed by "summer", "winter" and "spring" in decreasing order. Determined monthly and seasonal variation of material properties will find immediate application as inputs in mechanistic-empirical pavement design procedures.</p>			
17. Key Words Pavement Design, Flexible Pavement Evaluation, Non-Destructive Testing, Backcalculation		18. Distribution Statement No Restrictions. This document is available to the public through the National Technical Information Service, Springfield, Virginia 22161	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 169	22. Price



**EXTENDED MONITORING AND ANALYSIS OF MOISTURE-
TEMPERATURE DATA**

ODOT 8881

State Job No. 14694(0)

FINAL REPORT

October, 2001

Submitted to

The Ohio Department of Transportation

by

J. Ludwig Figueroa

Department of Civil Engineering

CASE WESTERN RESERVE UNIVERSITY

Cleveland, Ohio 44106

Prepared in Cooperation with the Ohio Department of Transportation and the
U.S. Department of Transportation, Federal Highway Administration

The contents of this report reflect the views of the authors who are responsible for the facts and the accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the Ohio Department of Transportation or the Federal Highway Administration. This report does not constitute a standard, specification or regulation.



EXTENDED MONITORING AND ANALYSIS OF MOISTURE- TEMPERATURE DATA

Abstract

The seasonal variations in the resilient modulus of asphalt concrete (AC) pavements and the corresponding resilient modulus variations of the subgrade soil are major factors in determining the performance of new AC pavements and overlays. Unfortunately, current design procedures do not directly consider these factors. It is expected however, that with the implementation of mechanistic pavement design procedures these variations will be included, leading to a more realistic design

Moisture-temperature-rainfall data was collected for a period of three years from monitoring stations previously installed during the ODOT-funded project "Characterization of Ohio Subgrade Types" and monitored for an additional period of 2-1/2 years during the project "Monitoring and Analysis of Data Obtained from Moisture-Temperature Recording Stations." These stations record hourly, daily and seasonal variations in air temperature, rainfall, temperature within the asphalt concrete layer and moisture content (or degree of saturation) and temperature within the subgrade soil. Typically, temperature variations within the subgrade soil are minimal on a daily basis. Only the uppermost subgrade soil thermistor shows daily temperature variations although within a narrower range, following those of the bottom asphalt concrete thermistor.

The thermistors within the asphalt concrete layer exhibit large daily temperature fluctuations. Typically the AC layer exhibits a uniform temperature (no temperature gradient) twice a day, normally occurring between 8:00 and 10:00 AM and around 8:00 PM. Similarly, the maximum daytime temperature gradient within the pavement is observed between 2:00 and 4:00 PM at all seasons and the maximum overnight temperature gradient occurs around 6:00 AM. It is

to be noted that the temperature gradient is greater in the afternoon than in the early morning and that AC layer temperature variations closely follow air temperature changes.

The average AC pavement temperature was calculated in the middle of the layer at each location, and then monthly and seasonal averages were tabulated. The average pavement temperature difference between summer and winter is of the order of 30 to 35 deg. C at all sites. This range also indicates the wide variation in the elastic properties of the AC. As expected the northern sites exhibit slightly lower averages than the southern sites. Observations in temperature changes within the pavement and subgrade profiles indicate that the daytime and the nighttime averages for any sensors located at depths in excess of 30.48 cm. (1.0 ft.) from the surface (i.e. the subgrade soil sensors) are very similar. In addition, the asphalt concrete sensors show warmer temperatures than the soil sensors (on the average) during the spring and summer. However, this trend reverses during the fall and winter.

Polynomial equations were derived relating the average asphalt concrete pavement temperature to the air temperature for eight (excluding the Columbiana Co.) of the nine monitored stations. The coefficients included in these equations indicate that asphalt concrete temperature is higher in the southern part than in the northern part of the state. The regression coefficients also point to the fact that the state of Ohio may be subdivided into three general temperature zones: North, (from the North Shore to Mansfield – Mount Vernon) Central (from Mansfield – Mount Vernon to Lancaster) and South (from Lancaster to the southern state line).

As a result of temperature differences during the four seasons the resilient modulus of the asphalt concrete also changes in an inverse form to the temperature variation. It was determined that for a typical mid-season day the resilient modulus averages:

3791.7 MPa (550 ksi) in the spring (+/- 1034.1 MPa or +/- 150 ksi)

1723.5 MPa (250 ksi) in the summer (+/- 1034.1 MPa or +/- 150 ksi)

8272.8 MPa (1200 ksi) in the fall (+/- 1378.8 MPa or +/- 200 ksi)

15511.5 MPa (2250 ksi) in the winter (+/- 1551.1 MPa or +/- 225 ksi)

Recorded depths of frost penetration show, as expected, that they are greater in the northern than in the southern stations. On a normal season the average depth of frost penetration is about 45.7 to 61.0 cm. (1.5 to 2.0 ft) at the southern stations and from 70.1 to 82.3 cm. (2.3 to 2.7 ft) at the northern locations. It was also observed that when the frost penetration is high at the northern sites the number of freeze-thaw cycles is lower. This normally occurs during severe winters. The number of cycles appears to increase during milder winters. Normally, the northern sites experience an average 7 to 12 cycles as compared to between 4 and 5 in the southern sites.

A calibration equation previously developed was used to obtain monthly and seasonal averages of the degree of saturation from moisture and temperature sensor readings at each of four moisture sensor locations. The degree of saturation typically varied between about 90% and 100% throughout the monitoring period. The late spring to early summer period seems to consistently lead to slightly higher (nearing 100%) degree of saturation at all depths.

Finally a method to back calculate the resilient modulus of subgrade soils at the break point from measured FWD deflections was developed. Overall seasonal averages of the modulus were obtained at each of six station locations where FWD testing was conducted. Seasons were ranked in terms of expected higher resilient modulus. The designated "fall" testing period (early fall) showed the highest followed by "summer", "winter" and "spring" in decreasing order. This ranking is expected since the fall testing period follows the generally drier summer season and the spring testing period happens at the spring thaw and normally wetter early spring. Generally, for the most part a higher back calculated resilient modulus followed lower amounts of rainfall. Similarly lower resilient modulus back calculations were generally preceded by higher rainfall. Attempts to correlate the amount of rainfall accumulated over either one month, two or three months preceding the date of FWD testing with the back calculated resilient modulus were unsuccessful.

THIS PAGE LEFT INTENTIONALLY BLANK

Table of Contents

	page
Abstract	ii
Table of Contents	vi
List of Figures	viii
List of Tables	xii
Chapter 1 Introduction	1
Chapter 2 Review of Pertinent Background Information	5
2.1 Site Selection	5
2.2 Material Property Determination Procedures	8
2.2.1 Relationships Between Resilient Modulus of the Asphalt Concrete and Temperature	11
2.2.2 Backcalculation of the Resilient Modulus of Subgrade Soils Based on Measured FWD Deflections	14
Chapter 3 Seasonal Factors Affecting Asphalt Concrete Pavements	19
3.1 Temperature Data	19
3.1.1 Daily Asphalt Concrete Pavement and Subgrade Temperature Variations	20
3.1.2 Monthly and Seasonal Asphalt Concrete Pavement Temperature Variations	23
3.1.3 Relationships Between Air Temperature and Average Asphalt Concrete Pavement Temperature	27
3.1.4 Monthly and Seasonal Asphalt Concrete Resilient Modulus Variation	30
3.1.5 Seasonal Subgrade Temperature Variations	38
3.2 Rainfall Data	41
3.3 Degree of Saturation	42
3.3.1 Moisture Sensor Calibration Factors	42
3.3.2 Degree of Saturation Results	44
Chapter 4 Back Calculation of Resilient Modulus of Subgrade Soils from Falling Weight Deflectometer Test Results	55
4.1 Analysis Method	55
4.2 Back Calculated Resilient Modulus	57
Chapter 5 Summary and Conclusions	67
References	73

Appendix A. Average AC Temperature and Relationships Between Air Temperature and Average Asphalt Concrete Pavement Temperature	75
Appendix B. Depth of Frost Penetration and Number of Freeze-Thaw Cycles Summary	113
Appendix C. Monthly and Seasonal Rainfall and Degree of Saturation Summaries	123
Appendix D. Back Calculation of Resilient Modulus of Subgrade Soils from FWD Deflections	157

List of Figures

	page
2.1 AC Modulus vs. Temperature	13
2.2 Backcalculation Procedure to Obtain E_n	15
3.1 WOOD 2.85 Sta. Spring 1993 AC Temperature Reversal	21
3.2 WOOD 2.85 Sta. Summer 1993 AC Temperature Reversal	21
3.3 WOOD 2.85 Sta. Fall 1993 AC Temperature Reversal	22
3.4 WOOD 2.85 Sta. Winter 1993 AC Temperature Reversal	22
3.5 Average AC Monthly Temperature	24
3.6 Average Seasonal AC Temperature	24
3.7 Hourly Variation of AC Modulus – Wood 2.85 Station (Spring)	32
3.8 Hourly Variation of AC Modulus – Wood 2.85 Station (Summer)	32
3.9 Hourly Variation of AC Modulus – Wood 2.85 Station (Fall)	33
3.10 Hourly Variation of AC Modulus – Wood 2.85 Station (Winter)	33
3.11 Monthly Variation of AC Modulus	35
3.12 Seasonal AC Modulus	36
3.13 Max. Depth of Frost Penetration	39
3.14 Number of Freeze-Thaw Cycles	39
3.15 No. of F-T Cycles & Frost Depth	40
3.16 Seasonal Rainfall	41
3.17 Variation of Degree of Saturation ADAMS Co.	45
3.18 Variation of Degree of Saturation ATHENS Co.	46
3.19 Variation of Degree of Saturation COLUMBIANA Co.	46
3.20 Variation of Degree of Saturation CRAWFORD Co.	47
3.21 Variation of Degree of Saturation KNOX Co.	47
3.22 Variation of Degree of Saturation LICKING Co.	48
3.23 Variation of Degree of Saturation WOOD2 Co.	48

3.24 Variation of Degree of Saturation WOOD8 Co.	49
3.25 Seasonal Degree of Saturation-ADAMS Co.	49
3.26 Seasonal Degree of Saturation-ATHENS Co.	50
3.27 Seasonal Degree of Saturation-COLUMBIANA Co.	50
3.28 Seasonal Degree of Saturation-CRAWFORD Co.	51
3.29 Seasonal Degree of Saturation-KNOX Co .	51
3.30 Seasonal Degree of Saturation-LICKING Co.	52
3.31 Seasonal Degree of Saturation-WOOD2 Co.	52
3.32 Seasonal Degree of Saturation-WOOD8 Co.	53
4.1 Resilient Modulus Variation (Adams Co.)	60
4.2 Resilient Modulus Variation (Athens Co.)	60
4.3 Resilient Modulus Variation (Crawford Co.)	61
4.4 Resilient Modulus Variation (Knox Co.)	61
4.5 Resilient Modulus Variation (Licking Co.)	62
4.6 Resilient Modulus Variation (Wood8 Co.)	62
4.7 Resilient Modulus vs. Monthly Rainfall (Adams Co.)	63
4.8 Resilient Modulus vs. Monthly Rainfall (Athens Co.)	63
4.9 Resilient Modulus vs. Monthly Rainfall (Crawford Co.)	64
4.10 Resilient Modulus vs. Monthly Rainfall (Knox Co.)	64
4.11 Resilient Modulus vs. Monthly Rainfall (Licking Co.)	65
4.12 Resilient Modulus vs. Monthly Rainfall (Wood8 Co.)	65
A1 Air Temperature vs. Average Asphalt Concrete Temperature (Adams Co.)	104
A2 Air Temperature vs. Average Asphalt Concrete Temperature (Athens Co.)	105
A3 Air Temperature vs. Average Asphalt Concrete Temperature (Columbiana Co.)	106
A4 Air Temperature vs. Average Asphalt Concrete Temperature (Crawford Co.)	107
A5 Air Temperature vs. Average Asphalt Concrete Temperature (Knox Co.)	108
A6 Air Temperature vs. Average Asphalt Concrete Temperature (Licking Co.)	109

A7 Air Temperature vs. Average Asphalt Concrete Temperature (Lucas Co.)	110
A8 Air Temperature vs. Average Asphalt Concrete Temperature (Wood2 Co.)	111
A9 Air Temperature vs. Average Asphalt Concrete Temperature (Wood8 Co.)	112

THIS PAGE LEFT INTENTIONALLY BLANK

List of Tables

	page
2.1a Monitoring Station Locations	6
2.1b Monitoring Station Soil Classification Parameters	6
2.2a Pavement Profile and Subgrade Type Existing at Each Location	7
2.2b Sensor Depth and Nomenclature	8
2.3 Available Moisture-Temperature Weather Data	10
2.4 Equation 2.1 Regression Coefficients	12
2.5a Coefficients used in Equation 2.6 (SI Units)	18
2.5b Coefficients used in Equation 2.6 (English Units)	18
3.1 Average Monthly Asphalt Concrete Temperature (deg C)	26
3.2 Average Seasonal Asphalt Concrete Temperature	27
3.3 Average AC Temp. vs. Air Temp. Coefficients	29
3.4 Average Monthly AC Modulus ($\times 10^6$ psi)	34
3.5 Average Seasonal Asphalt Concrete Elastic Modulus	37
4.1 Average Seasonal Resilient Modulus Back Calculated from FWD Deflections	58
A1 Average Seasonal Asphalt Concrete Temperature (Adams Co.) (deg C)	76
A2 Average Seasonal Asphalt Concrete Temperature (Athens Co.) (deg C)	78
A3 Average Seasonal Asphalt Concrete Temperature (Columbiana Co.) (deg C)	79
A4 Average Seasonal Asphalt Concrete Temperature (Crawford Co.) (deg C)	80
A5 Average Seasonal Asphalt Concrete Temperature (Knox Co.) (deg C)	82
A6 Average Seasonal Asphalt Concrete Temperature (Licking Co.) (deg C)	84
A7 Average Seasonal Asphalt Concrete Temperature (Lucas Co.) (deg C)	85
A8 Average Seasonal Asphalt Concrete Temperature (Wood 2 Co.) (deg C)	86
A9 Average Seasonal Asphalt Concrete Temperature (Wood 8 Co.) (deg C)	87
A10 Average Monthly Asphalt Concrete Temperature (Adams Co.) (deg C)	89
A11 Average Monthly Asphalt Concrete Temperature (Athens Co.) (deg C)	91

A12 Average Monthly Asphalt Concrete Temperature (Columbiana Co.) (deg C)	93
A13 Average Monthly Asphalt Concrete Temperature (Crawford Co.) (deg C)	94
A14 Average Monthly Asphalt Concrete Temperature (Knox Co.) (deg C)	96
A15 Average Monthly Asphalt Concrete Temperature (Licking Co.) (deg C)	98
A16 Average Monthly Asphalt Concrete Temperature (Lucas Co.) (deg C)	100
A17 Average Monthly Asphalt Concrete Temperature (Wood 2 Co.) (deg C)	101
A18 Average Monthly Asphalt Concrete Temperature (Wood 8 Co.) (deg C)	102
B1 Frost Cycles and Frost Depth (Adams Co.)	114
B2 Frost Cycles and Frost Depth (Athens Co.)	115
B3 Frost Cycles and Frost Depth (Crawford Co.)	116
B4 Frost Cycles and Frost Depth (Knox Co.)	117
B5 Frost Cycles and Frost Depth (Licking Co.)	118
B6 Frost Cycles and Frost Depth (Lucas Co.)	119
B7 Frost Cycles and Frost Depth (Wood 2 Co.)	120
B8 Frost Cycles and Frost Depth (Wood 8 Co.)	121
C1 Seasonal Rainfall (Adams Co.) (in)	124
C2 Seasonal Rainfall (Athens Co.) (in)	125
C3 Seasonal Rainfall (Columbiana Co.) (in)	126
C4 Seasonal Rainfall (Crawford Co.) (in)	127
C5 Seasonal Rainfall (Knox Co.) (in)	128
C6 Seasonal Rainfall (Licking Co.) (in)	129
C7 Seasonal Rainfall (Lucas Co.) (in)	130
C8 Seasonal Rainfall (Wood 2 Co.) (in)	131
C9 Seasonal Rainfall (Wood 8 Co.) (in)	132
C10 Monthly Rainfall (Adams Co.)	133
C11 Monthly Rainfall (Athens Co.)	134
C12 Monthly Rainfall (Columbiana Co.)	135

C13 Monthly Rainfall (Crawford Co.)	136
C14 Monthly Rainfall (Knox Co.)	137
C15 Monthly Rainfall (Licking Co.)	138
C16 Monthly Rainfall (Lucas Co.)	139
C17 Monthly Rainfall (Wood 2 Co.)	140
C18 Monthly Rainfall (Wood 8 Co.)	141
C19 Monthly Degree of Saturation-Adams Co.	142
C20 Monthly Degree of Saturation-Athens Co.	143
C21 Monthly Degree of Saturation-Columbiana Co.	144
C22 Monthly Degree of Saturation-Crawford Co.	145
C23 Monthly Degree of Saturation-Knox Co.	146
C24 Monthly Degree of Saturation-Licking Co.	147
C25 Monthly Degree of Saturation-Wood2 Co.	148
C26 Monthly Degree of Saturation-Wood8 Co.	149
C27 Seasonal Degree of Saturation-Adams Co.	150
C28 Seasonal Degree of Saturation-Athens Co.	151
C29 Seasonal Degree of Saturation-Columbiana Co.	152
C30 Seasonal Degree of Saturation-Crawford Co.	153
C31 Seasonal Degree of Saturation-Knox Co.	154
C32 Seasonal Degree of Saturation-Licking Co.	155
C33 Seasonal Degree of Saturation-Wood2 Co.	155
C34 Seasonal Degree of Saturation-Wood8 Co.	156
D1 Data to Back Calculate Resilient Modulus at the Break Point from FWD Testing (Adams Co.)	158
D2 Data to Back Calculate Resilient Modulus at the Break Point from FWD Testing (Athens Co.)	159

D3 Data to Back Calculate Resilient Modulus at the Break Point from FWD Testing (Crawford Co.)	160
D4 Data to Back Calculate Resilient Modulus at the Break Point from FWD Testing (Knox Co.)	161
D5 Data to Back Calculate Resilient Modulus at the Break Point from FWD Testing (Licking Co.)	162
D6 Data to Back Calculate Resilient Modulus at the Break Point from FWD Testing (Wood 8 Co.)	163
D7 Back Calculated Resilient Modulus at the Break Point from FWD Testing (ksi) (Adams Co.)	164
D8 Back Calculated Resilient Modulus at the Break Point from FWD Testing (ksi) (Athens Co.)	165
D9 Back Calculated Resilient Modulus at the Break Point from FWD Testing (ksi) (Crawford Co.)	166
D10 Back Calculated Resilient Modulus at the Break Point from FWD Testing (ksi) (Knox Co.)	167
D11 Back Calculated Resilient Modulus at the Break Point from FWD Testing (ksi) (Licking Co.)	168
D12 Back Calculated Resilient Modulus at the Break Point from FWD Testing (ksi) (Wood 8 Co.)	169

Chapter 1

INTRODUCTION

Stiffness properties of materials included in a flexible pavement profile directly affect the response of these pavements when subjected to traffic loadings. It is thus important to consider the seasonal variations of the resilient modulus of the asphalt concrete and the corresponding variations in the resilient modulus of the subgrade when designing new asphalt concrete pavements or overlays.

The resilient modulus of the asphalt concrete is affected by factors such as type of asphalt mix (including aggregates and admixtures), degree of compaction, and temperature. However, out of all these factors only temperature varies with time.

Similarly, among the factors affecting the resilient modulus of fine-grained soils such as soil type (i.e. A-4, A-6, A-7, etc.), dry unit weight and moisture content (or degree of saturation), only the moisture content varies with time.

Environmental factors including temperature within the asphalt concrete and moisture within the subgrade soil are now easily monitored with field data acquisition systems developed over the past few years. A total of nine moisture-temperature-monitoring stations were installed during the ODOT-funded project "Characterization of Ohio Subgrade Types". Subsequently, monitoring of these stations continued until 1997 during the ODOT-funded project "Monitoring and Analysis of Data Obtained from Moisture-Temperature Recording Stations." Some of these stations have been collecting data since 1991 at a 2-hour interval, providing a wealth of information as to the variation of environmental factors in typical climatic zones within the State of Ohio.

Similarly, the Ohio Department of Transportation has been collecting FWD readings periodically, on 152.4 m. (500')-long sections adjacent to some of the environmental monitoring stations. This information coupled with the environmental data obtained from the stations

permits the back calculation of the resilient modulus of the subgrade soil, to obtain trends on the variation of this parameter throughout the years.

The eventual implementation of mechanistic flexible pavement design procedures in the State of Ohio requires the determination of changes in material properties for an accurate evaluation of pavement life and proper determination of required layer thicknesses.

This report includes the results of the research project "Extended Monitoring and Analysis of Moisture-Temperature Data," funded by the Ohio Department of Transportation (ODOT). In essence, this project is an extension of the two previously ODOT-funded projects "Characterization of Ohio Subgrade Types" and "Monitoring and Analysis of Data Obtained from Moisture-Temperature Recording Stations." since data has been collected for a substantially longer period of time.

The project under consideration in this report consisted of three major efforts:

The first part included the extension of the monitoring and analysis period for data obtained from the originally installed stations located throughout Ohio. At most of these stations, the temperature (to obtain the depth of frost penetration) and the degree of saturation of the subgrade soil, the temperature of the asphalt concrete surface layer, the air temperature and the amount of rainfall have been almost continuously monitored and recorded.

The second part consisted of the analysis of seasonal FWD deflection data obtained by ODOT, which coupled with the moisture and temperature readings would yield a more extensive measure of the variability in the resilient properties of both asphalt concrete surface layer and subgrade soil.

It is expected that with the analysis of data obtained in parts 1 and 2, more representative seasonal average resilient properties of both surface and subgrade layers in flexible pavements, as well as of climate-related parameters could be obtained.

The third part involved the development of guidelines regarding the use of these resilient properties in the eventual implementation of a mechanistic flexible pavement design procedure.

Following, a summary of the contents of subsequent chapters is presented.

Chapter two includes the review of pertinent background information including previously developed methods linking changes in the stiffness properties of pavement materials to also varying environmental factors. In addition, the criteria used for selecting the location of each of the monitoring stations as well as the pavement section characteristics and sensor location existing at each site are presented.

Chapter three analyzes the seasonal data collected and discusses the effects of these environment-related factors on properties of influence in the mechanistic design of asphalt concrete pavements, such as the modulus of the asphalt concrete. The influence of temperature, rainfall and frost is discussed in detail. Finally, graphs and charts showing the variation of the degree of saturation at the monitored test sites are presented.

Chapter four discusses results of back calculating the resilient modulus of subgrade soil from measured FWD deflections and the possible link of changing resilient modulus as a result of previous rainfall regimes.

Chapter five includes a summary of the overall findings and implementation recommendations, along with any conclusions drawn as a result of this research. All supporting information in the form of tables and graphs is included in the appendixes.

THIS PAGE LEFT INTENTIONALLY BLANK

Chapter 2

REVIEW OF PERTINENT BACKGROUND INFORMATION

The first section of this chapter summarizes pertinent information concerning the criteria used for site selection, pavement section characteristics and periods of available data. The second section reviews material property determination procedures used in the previous two projects and summarizes the procedure to backcalculate the resilient modulus of subgrade soils, based on measured subgrade deflections, also developed during the same projects. Both of these methods will be used in subsequent chapters to analyze the additional data obtained, as well as to develop guidelines of eventual application in flexible pavement mechanistic design procedures.

2.1 Site Selection

A total of nine moisture-temperature-monitoring stations were installed during the ODOT-funded project "Characterization of Ohio Subgrade Types," between 1991 and 1994. At the end of the winter 2000-2001, five of these stations were in operation at the locations listed in Table 2.1a. The location selection criteria included the coverage of climatic zones within the state of Ohio: northwestern, northeastern, southwestern, southeastern and central; soil type A-3, A-4, A-6 and A-7; and a flexible pavement structure. Other factors considered in the selection criteria included a four-lane flexible pavement to facilitate the closure of one lane during installation as well as non-destructive testing; pavements in good condition, sites with good drainage and away from power lines to eliminate electrical noise. Other special considerations included the proximity to a Weight In Motion (WIM) station, such as the Licking Co. site. A summary of the soil classification parameters such as grain size distribution and Atterberg Limits is contained in Table 2.1b.

Table 2.1a Monitoring Station Locations

COUNTY	CLIMATE ZONE	ROAD	MILE POST	LANE	SOIL TYPE
ADAMS	SW	SR-32	4.4	WB	A-4a(8)
ATHENS	SE	US-50	5.9	WB	A-6a(10)
COLUMBIANA *	NE	SR-11	18.2	NB	A-6a(1)
CRAWFORD	Central	US-30	5.1	EB	A-6a(8)
KNOX	Central	SR-13	16.3	NB	A-6a(10)
LICKING *	Central	I-70	117@WIM	WB	A-4a(5)
LUCAS *	NW	I-475	10.9	NB	A-3a
WOOD 2.85 **	NW	SR-795	2.85	WB	A-7-6(15)
WOOD 8.1	NW	SR-795	8.1	WB	A-7-6(13)

Note: Numbers in parenthesis () in SOIL TYPE column represent the Group Index

* Not operating at present

** Dismantled

Table 2.1b Monitoring Station Soil Classification Parameters

SITE	% PASSING SIEVE #				LL	PL	GROUP
	200	40	10	4			
ADAMS	88.6	96.9	99.2	99.7	32.2	23.1	A-4a(8)
ATHENS	79.3	96.1	96.8	98.5	34.2	20.1	A-6a(10)
COLUMBIANA	42.0	57.6	68.2	76.3	30.0	11.0	A-6a(1)
CRAWFORD	65.6	90.0	97.5	99.0	33.2	18.3	A-6a(8)
KNOX	90.1	98.9	99.6	99.7	36.0	21.9	A-6a(10)
LICKING	60.2	77.5	87.8	92.7	25.1	17.7	A-4a(5)
LUCAS	15.5	96.1	100.0	100.0	----	----	A-3a
WOOD (2.85)	90.1	97.7	99.3	99.9	46.1	22.8	A-7-6(15)
WOOD (8.1)	92.5	98.4	99.8	100.0	44.2	22.6	A-7-6(13)

The WOOD 2.85 Co. station was dismantled in the summer of 1995 because of new urban development at the site and the lack of Non-Destructive (FWD) testing data. The COLUMBIANA Co. station was extensively damaged by a vehicle crash, shortly after its installation, even though it was located at least 9.2 m (30 ft.) from the road shoulder. Replacement of the logger unit indicated that only a small number of sensors remained in operation. The scant usable data collected at this station was considered to be statistically insignificant to be able to develop meaningful relationships. The LUCAS and the LICKING Co.

stations were damaged by lightning discharges in their vicinity. Information about soil types existing at each site is given in Table 2.1a. More detail regarding the geological characteristics of these soils can be found in the report by Figueroa et al. (1994).

Table 2.2a is a summary of the pavement profile geometric characteristics along with the subgrade soil type existing at each monitoring site. Similarly Table 2.2b lists wire denomination numbers and sensor types (moisture and temperature) at each of the monitoring stations, along with the depth of every sensor measured from the pavement surface. Damaged sensors within the working stations are also identified. A rain gage (tipping bucket type) is also installed next to the data logger at each site.

Table 2.2a Pavement Profile and Subgrade Type Existing at Each Location

Site	Thickness (cm)		
	AC Layer	Gravel Layer	Subgrade Type
Adams	39.6 (15.6")	12.7 (5.0")	A-4a(8)
Athens	29.2 (11.5")	15.2 (6.0")	A-6a(10)
Columbiana	29.5 (11.6")	15.0 (5.9")	A-6a(1)
Crawford	29.5 (11.6")	24.1 (9.5")	A-6a(8)
Knox	33.3 (13.1")	20.3 (8.0")	A-6a(10)
Licking	34.8 (13.7")	10.2 (4.0")*	A-4a(5)
Lucas	28.7 (11.3")	55.9 (22.0")	A-3a
Wood (2.85)	26.7 (10.5")	15.2 (6.0")	A-7-6(15)
Wood (8.1)	30.5 (12.0")	15.2 (6.0")	A-7-6(13)

* Plus 45.7 cm (18") of lime stabilized soil

Available asphalt concrete pavement, soil temperature and weather-related data to be analyzed in this report include data from the monitoring stations for the periods listed in Table 2.3.

2.2 Material Property Determination Procedures

Following is a summary of relationships and procedures developed during the project "Characterization of Ohio Subgrade Types" of fundamental importance in determining the variation of flexible pavement material properties throughout the year.

Table 2.2b Sensor Depth and Nomenclature

Adams			Athens			Columbiana		
Wire#	Depth (cm)	Type	Wire#	Depth (cm)	Type	Wire#	Depth (cm)	Type
15	AIR	T	15	AIR	T	15	AIR	T
14	6.4 (0'-2.5")	T*	14	5.1 (0'-2")	T*X	14	5.1 (0'-2")	T*X
13	12.7 (0'-5")	T*X	13	10.2 (0'-4")	T*	13	10.2 (0'-4")	T*X
12	19.0 (0'-7.5")	T*	12	15.2 (0'-6")	T*X	12	15.2 (0'-6")	T*X
11	25.4 (0'-10")	T*X	11	20.3 (0'-8")	T*X	11	20.3 (0'-8")	T*X
10	31.7 (1'-0.5")	T*	10	25.4 (0'-10")	T*	10	25.4 (0'-10")	T*X
4	45.7 (1'-6")	MX	4	45.7 (1'-6")	MX	4	45.7 (1'-6")	M
9	60.9 (2'-0")	TX	9	60.9 (2'-0")	TX	9	60.9 (2'-0")	TX
3	76.2 (2'-6")	M	3	76.2 (2'-6")	MX	3	76.2 (2'-6")	M
8	91.4 (3'-0")	T	8	91.4 (3'-0")	T	8	91.4 (3'-0")	TX
2	106.7 (3'-6")	MX	2	106.7 (3'-6")	M	2	106.7 (3'-6")	M
7	121.9 (4'-0")	TX	7	121.9 (4'-0")	TX	7	121.9 (4'-0")	T
1	137.1 (4'-6")	M	1	137.1 (4'-6")	MX	1	137.1 (4'-6")	M
6	152.4 (5')	T	6	152.4 (5')	TX	6	152.4 (5')	T
Crawford			Knox			Licking		
Wire#	Depth (cm)	Type	Wire#	Depth (cm)	Type	Wire#	Depth (cm)	Type
15	AIR	T	14	AIR	T	14	AIR	T
14	5.1 (0'-2")	T*X	13	5.1 (0'-2")	T*	13	5.1 (0'-2")	T*X
13	10.2 (0'-4")	T*	12	10.2 (0'-4")	T*	12	10.2 (0'-4")	T*
12	15.2 (0'-6")	T*X	11	20.3 (0'-8")	T*X	11	20.3 (0'-8")	T*X
11	20.3 (0'-8")	T*	10	29.2 (0'-11.5")	T*X	10	25.4 (0'-10")	T*
10	25.4 (0'-10")	T*X	9	45.7 (1'-6")	TX	9	30.5 (1'-0")	TX
4	45.7 (1'-6")	MX	4	60.9 (2'-0")	MX	4	45.7 (1'-6")	MX
9	60.9 (2'-0")	T	8	76.2 (2'-6")	TX	8	60.9 (2'-0")	TX
3	76.2 (2'-6")	MX	3	91.4 (3'-0")	MX	3	76.2 (2'-6")	MX
8	91.4 (3'-0")	TX	7	106.7 (3'-6")	TX	7	91.4 (3'-0")	T
2	106.7 (3'-6")	MX	2	121.9 (4'-0")	MX	2	106.7 (3'-6")	MX
7	121.9 (4'-0")	T	6	137.1 (4'-6")	T	6	121.9 (4'-0")	TX
1	137.1 (4'-6")	MX	1	152.4 (5')	MX	1	137.1 (4'-6")	MX
6	152.4 (5')	T					152.4 (5')	

Table 2.2b Sensor Depth and Nomenclature (cont.)

Lucas			Wood(2.85)			Wood(8.1)		
Wire#	Depth (cm)	Type	Wire#	Depth (cm)	Type	Wire#	Depth (cm)	Type
15	AIR	T	14	AIR	T	15	AIR	T
14	5.1 (0'-2")	T*X	13	5.1 (0'-2")	T*	14	5.1 (0'-2")	T*X
13	10.2 (0'-4")	T*	12	10.2 (0'-4")	T*	13	10.2 (0'-4")	T*
12	15.2 (0'-6")	T*X	11	15.2 (0'-6")	T*	12	15.2 (0'-6")	T*X
11	20.3 (0'-8")	T*X	10	20.3 (0'-8")	T*X	11	20.3 (0'-8")	T*X
10	25.4 (0'-10")	T*	4	45.7 (1'-6")	M	10	25.4 (0'-10")	T*
4	45.7 (1'-6")	MX	9	60.9 (2'-0")	T	4	45.7 (1'-6")	M
9	60.9 (2'-0")	T	3	76.2 (2'-6")	M	9	60.9 (2'-0")	T
3	76.2 (2'-6")	MX	8	91.4 (3'-0")	T	3	76.2 (2'-6")	M
8	91.4 (3'-0")	TX	2	106.7 (3'-6")	M	8	91.4 (3'-0")	TX
2	106.7 (3'-6")	MX	7	121.9 (4'-0")	T	2	106.7 (3'-6")	M
7	121.9 (4'-0")	T	1	137.1 (4'-6")	M	7	121.9 (4'-0")	T
1	137.1 (4'-6")	MX	6	152.4 (5')	T	1	137.1 (4'-6")	M
6	152.4 (5')	TX				6	152.4 (5')	T

Sensor Types

"T" = Temperature Probe

"*" = Sensor in Asphalt Concrete

"M" = Moisture Sensor

"X" = Damaged Sensor (disconnected) – April 2001

Table 2.3 Available Moisture-Temperature-Weather Data

Site	From	To	From	To	From	To	From	To	From	To
Adams	3/1/94	7/6/94	6/14/95	5/4/96	10/10/96	12/31/99	4/4/00	4/19/01		
Athens	12/21/91	1/12/94	5/12/94	7/4/96	12/21/96	2/22/97	7/24/97	8/24/99	4/4/00	4/19/01
Columbiana	11/3/94	6/20/95	7/7/95	3/14/96						
Crawford	6/3/92	8/20/96	10/10/96	12/31/99	4/4/00	4/18/01				
Knox	12/20/91	6/4/92	6/10/92	8/15/95	3/21/96	12/31/99	4/5/00	4/19/01		
Licking	12/5/91	6/13/97	7/24/97	7/21/98	8/3/98	4/19/99				
Lucas	6/2/92	8/11/92	8/15/92	10/16/92	12/29/92	12/18/96				
Wood(2.85)	6/2/92	6/13/95								
Wood(8.1)	6/2/92	8/18/92	8/20/92	10/21/92	12/29/92	1/11/94	5/12/94	12/31/99	4/4/00	4/18/01

2.2.1 Relationships Between Resilient Modulus of the Asphalt Concrete and Temperature

The resilient modulus of the asphalt concrete is one of the parameters required in the determination of the resilient modulus of subgrade soils by the backcalculation procedure explained in the following section. The asphalt concrete modulus is known to be independent of the applied stresses (as opposed to that of subgrade soils) but dependent upon the asphalt concrete temperature. Figueroa et al., 1994 conducted a complete testing program to develop a relationship between the resilient modulus of the asphalt concrete and its temperature. The Indirect Tension for Resilient Modulus for Bituminous Mixtures test method (ASTM D 4123-82) was followed in testing 4" diameter asphalt concrete cores, obtained from the center of the truck lane during the installation of each monitoring station listed in Tables 2.1 and 2.2. A parabolic equation yields the best fit to the test data for typical Ohio mixtures. Equation 2.1 defines the curves of best fit with the coefficients listed in Table 2.4 (in both SI and English units) for each type of asphalt concrete (ODOT items 404 and 402) found at the monitored sections, in conjunction with the curve-fit coefficient of determination, R^2 . Figure 2.1 is a graphical representation of the regression equation trend lines for both types of mixes.

$$E_r = a_c + a_1P + a_2P^2 \quad (2.1)$$

where:

E_r = Resilient modulus MPa in SI units or (psi x 10⁶ in English units)

a_0, a_1, a_2 = Regression constants listed in Table 2.4:

Columns 2 & 3 for SI units

Columns 4 & 5 for English units

P = Asphalt concrete temperature: Deg. C in SI units or (Deg F in English units)

Table 2.4 Equation 2.1 Regression Coefficients

1	2	3	4	5
Coefficient	SI Units		English Units	
	AC Type		AC Type	
	404	402	404	402
a_0	12659	12118	3.5405	3.1164
a_1	-562.10	-473.59	-0.0611	-0.0487
a_2	5.8344	3.9292	2.57×10^{-4}	1.73×10^{-4}
R^2	0.8548	0.6403	0.8547	0.6403

The test is conducted using a repeated indirect tensile test set-up under controlled temperature and controlled loading conditions with a typical load application time of 0.1 seconds and a rest period of 1.9 seconds, with an applied load nearing 444.8 N (100 lbs). The load is applied to the 4" disks along the diameter through a narrow curved loading strip, while the load, the vertical and horizontal deformations are recorded to calculate the Poisson's ratio and the resilient modulus by the following equations.

$$\nu = \frac{3.59 \Delta H}{\Delta V} \quad (2.2)$$

$$E_r = \frac{P(\nu + 0.27)}{t \Delta H} \quad (2.3)$$

Where:

E_r = Resilient modulus of elasticity (psi)

P = Applied repeated load (lb)

ν = Resilient Poisson's ratio

t = Specimen thickness (in)

ΔH = Total recoverable horizontal deformation (in)

ΔV = Recoverable vertical deformation (in)




Figure 2.1 AC Modulus vs. Temperature

To consider the influence of temperature on the resilient modulus, each asphalt concrete disk was tested at temperatures of: 4.5, 15.5 and 26.5 degrees Celsius (40, 60, and 80 degrees Fahrenheit). A few additional tests were conducted at temperatures of -1.1 and 17.8° C (30 and 64° F). The samples, as well as the testing machine, were kept in a controlled-temperature room and brought to the specified test temperature. The temperature was maintained constant until all of the specimens reached the necessary equilibrium temperature and the tests were completed.

In turn, the average asphalt concrete temperature can be related to the air temperature by developing relationships of the form given in Equation 2.4, from data obtained at each monitoring location, as will be shown in the following chapters. Thus, it is feasible to assess the resilient modulus of the AC from air temperature data, which is normally obtained during FWD testing.

$$P = C_1 + C_2 A + C_3 A^2 \quad (2.4)$$

where

C1, C2, and C3 = Regression constants updated in the following chapters for each station location.
 P = Average AC temperature (Deg C).
 A = Air temperature (Deg C).

2.2.2 Backcalculation of the Resilient Modulus of Subgrade Soils Based on Measured FWD Deflections

It is well known that pavement performance is affected among other factors by the characteristics of the subgrade. The seasonal variation of the resilient modulus of the subgrade soil is one of the major factors in determining design parameters for new asphalt concrete pavements and overlays. The flexible pavement analysis program (ILLIPAVE) was validated during the “Characterization of Ohio Subgrade Types” project (Figuroa et al., 1994) as an effective tool to calculate deflections. This program was also used to develop nomographs to back calculate the resilient modulus of the subgrade based on measured Falling Weight Deflectometer (FWD) deflections for a given soil type. Figure 2.2 depicts the fundamentals of this developed method and can be explained as follows:

The air temperature is measured during FWD tests. This temperature is entered into Equation 2.4 and the corresponding average asphalt concrete pavement temperature is obtained. The AC pavement temperature is then entered into Equation 2.1 (with coefficients defined in Table 2.4) or Figure 2.1 in order to obtain the AC modulus. The AC modulus is entered into a nomograph (developed for a given soil type) along with the AC thickness, the gravel base thickness, and the maximum FWD deflection to obtain the resilient modulus of the subgrade soil at the break point E_{ri} . The slopes of the lines before and after the break point on a plot representing the variation of the resilient modulus vs. the deviator stress were found to be approximately constant and independent of the degree of saturation by Figuroa et al., 1994




Figure 2.2 Back Calculation Procedure to Obtain E_{ri}

Alternatively, regression equations (presented below) were developed relating all of the previously mentioned parameters to measured maximum FWD pavement surface deflections. The basis of the nomographs as well as the regression equations can be explained as follows:

Typical flexible pavement structures are composed of a top asphalt concrete layer, a granular base course and a bottom subgrade layer. The development of nomographs to back calculate the resilient modulus of the subgrade for a given soil type, included the consideration of

the influence of the applied load, the asphalt concrete thickness, the thickness of the gravel base course, the asphalt concrete resilient modulus and the resilient modulus of the subgrade soil.

Observing the deflections measured by FWD testing, the applied loads are typically around 40.03, 53.38 and 66.72 kN (9000, 12000 and 15000 lbs). Thus, these magnitudes were selected to calculate the contact pressure for a given type of soil. Thickness values of 10.2, 20.3 and 30.5 cm. (4, 8, and 12 in.) were chosen for both the asphalt concrete layer and the gravel base course, representing typical layer thickness ranges found in Ohio pavements. Data recorded by the moisture-temperature-rainfall monitoring stations shows that the seasonal air temperature usually varies between -1.11 and 26.7°C (30 and 80°F). Thus, temperatures of -1.11 , 10.0 and 26.7°C (30 , 50 and 80°F) were adopted as representative of average temperatures in the winter, spring/fall, and summer respectively. These values are then entered into Equation 2.4 to obtain the corresponding asphalt concrete pavement temperature. Finally, the calculated pavement temperature is used as input to Equation 2.1 or Figure 2.1 to obtain the average asphalt concrete resilient modulus during the corresponding season.

Generalized relationships were obtained by conducting a regression analysis between the deflection as the dependent variable and the thickness of the asphalt concrete, the gravel base thickness, the resilient modulus of the asphalt concrete and the resilient modulus of the subgrade soil. Based on the higher Coefficient of Determination R^2 , the logarithmic relationship provides the best fit, expressed by:

$$\log(d) = a_0 + a_1 t_{ac} + a_2 t_{base} + a_3 E_{ac} + a_4 E_{ri} \quad (2.5)$$

Considering units in the SI or English systems of measurement, these variables are:

- d = Deflection at the center of load application (cm or in)
- t_{ac} = Thickness of the asphalt concrete (cm or in)
- t_{base} = Gravel base thickness (cm or in)
- E_{ac} = Resilient modulus of the asphalt concrete (MPa or ksi)
- E_{ri} = Resilient modulus of the subgrade soil at the break point (MPa or ksi)
- a_0, a_1, a_2, a_3, a_4 = Regression constants

Thus the resilient modulus of the subgrade soil is back calculated by:

$$E_{ri} = [\log(d) - a_0 - a_1 t_{ac} - a_2 t_{base} - a_3 E_{ac}] / a_4 \quad (2.6)$$

Tables 2.5a and 2.5b summarize the coefficients (in SI and English units, respectively) for the three types of soil A-4, A-6 and A-7, along with the corresponding Coefficient of Determination R^2 , to be used in conjunction with Equation 2.6 to back calculate the resilient modulus of the subgrade soil at the break point.

In summary, knowing both the thickness of the asphalt concrete layer and the gravel base course, the resilient modulus of the asphalt concrete from air temperature records in combination with Equations 2.4 and 2.1 and maximum measured surface deflections by the Falling Weight Deflectometer, the resilient modulus of the subgrade soil can be backcalculated following the procedure shown in Figure 2.2.

At a certain location, the thicknesses of both the asphalt concrete layer and the gravel base course are known from construction records. Thus, the total deflection is dependent upon the variations of the resilient modulus of the subgrade soil E_{ri} and the asphalt concrete modulus E_{ac} . Comparing the influence of E_{ac} with respect to E_{ri} in affecting the total deflection, it is found that the total deflection is very sensitive to the variation of E_{ri} . This influence is evident in the relative values of the coefficients a_4 and a_3 , whereby a_4 is approximately two orders of magnitude higher than a_3 , although E_{ac} and E_{ri} do not differ by as much as two orders of magnitude at a given time during the year. As a result of this observation, it can be concluded that the subgrade soil significantly contributes to the total deflection of typical flexible pavements.

Table 2.5a. Coefficients used in Equation 2.6 (SI units)

Soil Type	P (N)	a ₀	a ₁	a ₂	a ₃	a ₄	R ²
A-4	40032	-0.67328	-0.01775	-3.99543E-04	-4.62929E-05	-2.90883E-03	0.92032
	53376	-0.55789	-0.01746	-4.97508E-04	-4.58201E-05	-2.92112E-03	0.91975
	66720	-0.46776	-0.01726	-5.77815E-04	-4.54227E-05	-2.92710E-03	0.91896
A-6	40032	-0.67834	-0.01761	-5.62748E-04	-4.55944E-05	-3.23827E-03	0.91943
	53376	-0.56192	-0.01731	-6.61429E-04	-4.50786E-05	-3.28619E-03	0.91859
	66720	-0.47122	-0.01711	-7.38004E-04	-4.47405E-05	-3.29810E-03	0.91778
A-7	40032	-0.61095	-0.01719	-9.14484E-04	-4.39790E-05	-4.48548E-03	0.92234
	53376	-0.49853	-0.01674	-1.15048E-03	-4.38220E-05	-4.40564E-03	0.92347
	66720	-0.40663	-0.01670	-1.08492E-03	-4.30709E-05	-4.48473E-03	0.92195
$\log(d)=a_0 + a_1 t_{ac} + a_2 t_{base} + a_3 E_{ac} + a_4 E_{ri}$ t_{ac} and t_{base} = given in cm. E_{ac} and E_{ri} = given in MPa R^2 = Coefficient of Determination							

Table 2.5b. Coefficients used in Equation 2.6 (English units)

Soil Type	P (lb)	a ₀	a ₁	a ₂	a ₃	a ₄	R ²
A-4	9000	-1.07811	-0.04509	-1.01484 E-3	-3.19143 E-4	-2.00535 E-2	0.92032
	12000	-0.96273	-0.04434	-1.26367 E-3	-3.15884 E-4	-2.01382 E-2	0.91975
	15000	-0.87260	-0.04384	-1.46765 E-3	-3.13144 E-4	-2.01794 E-2	0.91896
A-6	9000	-1.08317	-0.04474	-1.42938 E-3	-3.14328 E-4	-2.23246 E-2	0.91943
	12000	-0.96675	-0.04396	-1.68003 E-3	-3.10772 E-4	-2.26550 E-2	0.91859
	15000	-0.87606	-0.04346	-1.87453 E-3	-3.08441 E-4	-2.27371 E-2	0.91778
A-7	9000	-1.01578	-0.04365	-2.32279 E-3	-3.03191 E-4	-3.09229 E-2	0.92234
	12000	-0.90336	-0.04251	-2.92221 E-3	-3.02109 E-4	-3.03725 E-2	0.92347
	15000	-0.81146	-0.04242	-2.75569 E-3	-2.96931 E-4	-3.09177 E-2	0.92195
$\log(d)=a_0 + a_1 t_{ac} + a_2 t_{base} + a_3 E_{ac} + a_4 E_{ri}$ t_{ac} and t_{base} = given in inches E_{ac} and E_{ri} = given in ksi R^2 = Coefficient of Determination							

Chapter 3

SEASONAL FACTORS AFFECTING ASPHALT CONCRETE PAVEMENTS

This chapter presents the updated seasonal data collected at the moisture-temperature monitoring stations with emphasis on the effects of seasonal factors on the engineering properties of materials included in a flexible pavement profile. Of particular interest is the discussion of temperature variations (daily, monthly and seasonal) within the asphalt concrete and the development of relationships linking the average AC temperature (and consequently the modulus) to the measured air temperature. Summary tables and graphs are included in this chapter showing the amount of rainfall, depth of frost penetration, number of freeze-thaw cycles and the variation of the degree of saturation with depth at the different monitoring stations.

3.1 Temperature Data

Temperature is one of the most important parameters affecting the performance of asphalt concrete pavements and in particular during the warmer months. As previously shown in Figure 2.1, the modulus of the asphalt concrete decreases with an increase in temperature. However it is only when the AC temperature rises beyond 10-15.6°C (50-60°F) that there is a substantial decrease in the surface layer stiffness. Any applied traffic loads during this period will significantly affect the stress on the subgrade soil, increasing the likelihood of distress development.

Asphalt concrete pavement, soil and air temperature data to be analyzed in the following sections includes data from eight of the nine monitoring stations for the periods listed in Table 2.3. As previously indicated, scant data was only collected at the Columbiana Co. station since initially this unit was damaged by lightning and soon after it was repaired, a vehicle crash

damaged it beyond repair. Thus, development of meaningful relationships was not possible at this site.

3.1.1. Daily Asphalt Concrete Pavement and Subgrade Temperature

Variations

Typically, temperature variations within the subgrade soil are minimal on a daily basis. Only the uppermost subgrade soil thermistor shows daily temperature variations, although within a narrower range, following those of the lowest asphalt concrete thermistor.

The thermistors within the asphalt concrete layer do exhibit large daily temperature fluctuations. Figures 3.1 to 3.4 show typical surface layer temperature variations for a typical three-day period at mid-spring, mid-summer, mid-fall and mid-winter. Wood Co. 2.85 station surface layer thermistor and air temperature readings obtained in 1993-1994 are shown in these figures. Sensors W13, W12, W11 and W10 are located at 5.08, 10.16, 15.24 and 20.32 cm. (2, 4, 6 and 8 in.) below the surface of the 26.7 cm. (10.5 in)-thick AC surface layer.

Figure 3.1 WOOD 2.85 Sta. SPRING 1993 AC TEMPERATURE REVERSAL




Figure 3.2 WOOD 2.85 Sta. SUMMER 1993 AC TEMPERATURE REVERSAL




Figure 3.3 WOOD 2.85 Sta. FALL 1993 AC TEMPERATURE REVERSAL





Figure 3.4 WOOD 2.85 Sta. WINTER 1993-1994 AC TEMPERATURE REVERSAL



Normally and depending on the air temperature variations and weather fronts, as seen in these figures the AC layer experiences a uniform temperature (no temperature gradient) twice a day, primarily during the days that solar radiation influences the asphalt concrete temperature. These points occur between 8:00 and 10:00 AM and around 8:00 PM. After the morning period of no temperature gradient, thermistors closer to the surface show faster warming as compared to those near the bottom of the surface layer. An opposite trend occurs after the evening period of no temperature gradient. This information is important in selecting the optimal times for FWD testing (between 8:00-10:00 AM) since the surface layer exhibits a uniform stiffness throughout its thickness. Similarly, the maximum daytime temperature gradient within the pavement is observed between 2:00 and 4:00 PM at all seasons and the maximum overnight temperature gradient occurs around 6:00 AM. It is to be noted that the temperature gradient is greater in the afternoon than in the early morning and that AC layer temperature variations closely follow air temperature changes.

3.1.2. Monthly and Seasonal Asphalt Concrete Pavement Temperature Variations

The daytime and nighttime seasonal temperature averages were computed from the temperature sensor readings. This information is presented in two different formats.

Temperature data from the Logger data files was separated into daytime and nighttime values. All data points lying between 7:00 AM and 7:00 PM were defined as daytime temperatures. The remaining points were considered nighttime temperatures. For each of the station locations the average AC pavement temperature was calculated in the middle of the layer and both the monthly and seasonal averages of these temperatures were calculated. Tables 3.1 and 3.2 contain the daytime, nighttime and combined (total: day and night) monthly and seasonal AC pavement temperatures.

Graphs of the monthly and seasonal average AC pavement temperatures are shown in Figures 3.5 and 3.6. It is to be noted that the average pavement temperature difference between summer and winter is on the order of 30 to 35 deg. C at all sites. This temperature range

Figure 3.5 Average AC Monthly Temperature





Figure 3.6 Average Seasonal AC Temperature



obviously indicate the wide variation in the elastic properties of the AC as it will be shown later in this chapter. As expected the northern sites exhibit slightly lower averages than the southern sites. These average temperatures are later used to calculate the corresponding AC modulus average values.

Seasonal and monthly averages of the AC temperature are tabulated in Appendix A including all collected data, at all sections. The seasonal averages are contained in Tables A1 to A9, whereas the monthly averages are listed in Tables A10 to A18. All data points collected have been examined for accuracy, deleting values from damaged sensors to obtain these averages.

Figuroa et al. (1994) indicated from observations in temperature changes within the pavement and subgrade profiles that the daytime and the nighttime averages for any sensors located at depths in excess of 30.5 cm. (1.0 ft.) (i.e. the soil sensors) are virtually identical. In addition, the asphalt concrete sensors are warmer than the soil sensors (on the average) during the spring and summer seasons. Furthermore, in the fall and winter seasons the soil sensors are warmer than the asphalt concrete sensors.

Table 3.1 AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (deg C)

COUNTY	TIME	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
ADAMS	day	2.66	5.86	9.77	17.75	24.96	30.75	33.47	31.94	26.90	19.44	10.12	4.88
	night	2.46	5.43	9.01	16.69	23.69	29.55	32.25	30.84	25.92	18.57	9.60	4.65
	total	2.56	5.65	9.39	17.22	24.33	30.15	32.86	31.39	26.41	19.01	9.86	4.76
ATHENS	day	2.19	3.73	8.39	17.13	24.83	31.01	33.96	31.94	26.33	18.02	9.27	3.50
	night	1.88	3.16	7.39	15.64	23.04	29.05	32.13	30.35	24.79	16.79	8.56	3.12
	total	2.03	3.44	7.88	16.39	23.98	30.03	33.04	31.14	25.57	17.40	8.91	3.31
CRAWFORD	day	-0.57	1.35	5.98	14.83	22.28	28.25	30.99	28.88	23.65	15.92	7.82	2.64
	night	-0.66	1.04	5.09	13.54	20.62	26.66	29.46	27.66	22.56	15.01	7.32	2.43
	total	-0.62	1.19	5.54	14.19	21.45	27.47	30.23	28.26	23.10	15.46	7.57	2.54
KNOX	day	-0.07	2.17	6.68	13.38	20.48	27.07	30.98	29.13	23.56	15.07	7.26	2.11
	night	-0.19	1.92	6.05	12.47	19.26	26.08	29.95	28.24	22.72	14.31	6.80	1.65
	total	-0.13	2.05	6.37	12.92	19.87	26.58	30.46	28.69	23.14	14.69	7.03	1.99
LICKING	day	1.62	3.22	7.55	14.84	20.92	26.57	29.18	28.36	23.55	16.19	8.68	4.36
	night	1.62	3.10	7.13	14.20	19.95	25.84	28.51	27.78	23.07	15.91	8.48	4.28
	total	1.62	3.16	7.35	14.52	20.44	26.20	28.85	28.07	23.31	16.05	8.58	4.32
LUCAS	day	-0.74	-0.31	5.46	12.65	20.13	26.15	28.56	27.74	22.31	14.75	7.79	2.45
	night	-0.97	-0.59	5.00	12.35	19.72	25.53	27.82	27.13	21.86	14.58	7.59	2.30
	total	-0.86	-0.45	5.31	12.49	19.92	25.83	28.19	27.41	22.09	14.66	7.69	2.37
WOOD2	day	-1.31	-0.85	5.38	13.27	22.28	27.46	30.53	28.52	23.69	15.45	7.97	2.61
	night	-1.32	-1.01	4.71	12.21	20.77	26.75	29.94	27.94	23.30	15.09	7.76	2.55
	total	-1.31	-0.93	5.04	12.74	21.52	27.10	30.24	28.23	23.50	15.27	7.87	2.58
WOOD8	day	-1.65	-0.21	4.31	12.16	19.90	26.23	29.58	27.67	22.65	14.84	6.22	0.65
	night	-1.66	-0.27	4.04	11.69	19.30	25.86	29.30	27.45	22.52	14.69	6.15	0.62
	total	-1.65	-0.24	4.17	11.92	19.60	26.04	29.44	27.56	22.59	14.76	6.18	0.64

Table 3.2 AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE
(deg C)

LOCATION		SPRING	SUMMER	FALL	WINTER
ADAMS	day	22.68	31.72	14.16	4.80
	night	21.52	30.60	13.50	4.45
	total	22.10	31.16	13.83	4.62
ATHENS	day	22.08	31.76	12.82	3.65
	night	20.40	30.12	11.93	3.13
	total	21.24	30.94	12.50	3.39
CRAWFORD	day	19.68	28.86	11.05	1.28
	night	18.17	27.58	10.42	0.97
	total	18.92	28.23	10.74	1.13
KNOX	day	18.03	28.97	10.46	1.73
	night	16.98	27.99	9.90	1.46
	total	17.25	28.48	10.18	1.59
LICKING	day	18.45	27.74	11.85	3.25
	night	17.65	27.14	11.64	3.14
	total	18.05	27.44	11.75	3.20
LUCAS	day	17.43	27.12	10.66	0.63
	night	17.07	26.46	10.49	0.41
	total	17.24	26.79	10.57	0.52
WOOD 2	day	18.69	28.42	10.93	0.20
	night	17.49	27.88	10.69	0.03
	total	18.09	28.15	10.81	0.11
WOOD 8	day	17.18	27.66	9.70	-0.16
	night	16.69	27.43	9.61	-0.23
	Total	16.94	27.55	9.66	-0.20

3.1.3. Relationships Between Air Temperature and Average Asphalt Concrete Pavement Temperature

Equations were derived relating the average asphalt concrete pavement temperature to the air temperature for eight (excluding the Columbiana Co.) of the nine monitored stations. These station sites were selected among other considerations, in order to show the change in asphalt concrete temperature corresponding to a change in latitude for a given air temperature.

Figures A1 to A9 show the average AC temperature as a function of air temperature for all stations. These figures include all of the available field data (both the daytime and the nighttime values), up to March, 2001. Statistical regression analyses were conducted on the combined daytime and nighttime values to develop regression equations between the average AC temperature and the air temperature. Such equations would be useful in inferring the average AC modulus based on air temperature readings, as it will be shown later. After viewing the graphs of asphalt concrete temperature vs. air temperature, a polynomial relationship following the general form of Equation 2.4, reproduced below, yielded the best fit for the field data.

$$P = C1 + C2 A + C3 A^2 \quad (2.4)$$

where

C1, C2, and C3 =	Regression constants updated in the following chapters for each station location.
P =	Average AC temperature (Deg C).
A =	Air temperature (Deg C).

The values of C1, C2, and C3 for the combined daytime and nighttime data are included in Table 3.3 for the eight analyzed station locations. In addition, the coefficient of determination R^2 , indicating the highly significant relationship ($R^2 > 0.83$ in all cases) between the two parameters in every instance is included for each equation.

The monitoring station locations in order of increasing latitude are Adams, Athens, Licking, Knox, Crawford and Wood (8.1), Lucas and Wood(2.85) Co. sites. It is instructive to note that the coefficient C1 (intercept at zero air temperature) for the most part, tends to decrease with increasing latitude. This indicates that asphalt concrete temperature will be higher in the southern part than in the northern part of the state. Similarly, the coefficient C3 tends to be higher in the southern part than in the northern part of the state. This can be related to the declination of the sun during the colder seasons leading to more direct sunlight in the southern than in the northern counties of the state.

Table 3.3 Average AC Temp. vs. Air Temp. Coefficients

Site	No. of Points	C1	C2	C3	R ²
Adams	23732	6.0758	0.8880	0.0044	0.8325
Athens	37420	4.8031	0.9233	0.0062	0.8508
Columbiana*					
Crawford	39753	4.7594	0.9110	0.0055	0.8446
Knox	41551	4.4847	0.8917	0.0067	0.8317
Licking	36986	5.2147	0.8447	0.0037	0.8616
Lucas	21408	5.1270	0.9145	0.0014	0.8776
Wood(2.85)	16502	4.0461	0.9483	0.0051	0.8793
Wood(8.1)	37504	3.5786	0.9605	0.0024	0.8554
NORTH	75414	4.1409	0.9423	0.0027	0.8640
CENTRAL	118290	4.8118	0.8860	0.0052	0.8418
SOUTH	61152	5.2834	0.9113	0.0055	0.8431
ALL SITES	254856	4.7055	0.9107	0.0045	0.8475

* Not enough data to develop

ALL SITES: Adams, Athens, Crawford, Knox, Licking, Lucas, Wood(2.85) and Wood(8.1)

NORTH: Lucas, Wood(2.85) and Wood(8.1)

CENTRAL: Crawford, Knox, Licking

SOUTH: Adams, Athens

Examination of the regression equation coefficients shown in Table 3.3 indicates that the state of Ohio may be subdivided into three general temperature zones: North, (from the North Shore to Mansfield – Mount Vernon) Central (from Mansfield – Mount Vernon to Lancaster) and South (from Lancaster to the southern state line). This division will be useful in assessing the

average AC modulus on a seasonal or monthly basis for any future implementation of mechanistic pavement design procedures. Individual regression equations for each climatic zone as well as for all of Ohio were also determined and are included in Table 3.3. It is worth noting that the overall equation approaches the equation determined for the central zone of the state

3.1.4. Monthly and Seasonal Asphalt Concrete Resilient Modulus Variation

As a result of temperature differences during the four seasons the resilient modulus of the asphalt concrete is also expected to vary, in view of the direct dependency of the elastic modulus of the AC on temperature. To examine the temperature susceptibility (modulus variation) of the asphalt concrete, the same 3-day sequence used to illustrate the daily variation of temperature during a given season was selected in this section. Referring back to Figures 3.1 to 3.4 where typical surface layer temperature variations for a three-day period at mid-spring, mid-summer, mid-fall and mid-winter at the Wood Co. 2.85 station, the elastic modulus was calculated from the values of temperature measured at thermistors W12, W11 and W10, with the aid of Equation 2.1 along with the coefficients for mixture 404 contained in Table 2.4. As expected, the elastic modulus also displays the typical sinusoidal day-night variation also observed in the temperature changes within the pavement surface layer (when weather fronts do not come through during the three day sequence).

Figures 3.7 to 3.10 depict the resilient modulus variation for the three-day sequence during the spring, summer, fall and winter. The times of the day of equal stiffness are also evident as indicated in the temperature-related discussion. These figures have been plotted with the same vertical scale to facilitate the comparison of relative modulus values with respect to the season. For a typical mid-season day the resilient modulus averages:

3791.7 MPa (550 ksi) in the spring (+/- 1034.1 MPa or +/- 150 ksi)

1723.5 MPa (250 ksi) in the summer (+/- 1034.1 MPa or +/- 150 ksi)

8272.8 MPa (1200 ksi) in the fall (+/- 1378.8 MPa or +/- 200 ksi)

15511.5 MPa (2250 ksi) in the winter (+/- 1551.1 MPa or +/- 225 ksi)

The larger modulus range in the colder seasons can be explained as a result of the steeper variation of the resilient modulus at colder than at warmer temperatures as indicated in Figure 2.1. These typical modulus values also indicate that the contribution of the subgrade soil in supporting traffic loads is more important during the warmer months because of the lower stiffness of the surface layer during this time of the year. Unfortunately, this fact is also coupled with the lower stiffness of the subgrade soil itself during and after the rainy spring and early summer as is typical in Ohio. Consequently the two combined effects make the spring-summer the critical time of the year considering environmental effects.

It should be mentioned that a desirable asphalt concrete mixture must have a narrower modulus range such that it is not too brittle in the winter (low temperature cracking) and not too soft in the summer (rutting). Additives to asphalt cement may minimize this range and consequently improve the performance of the asphalt concrete.

Tables 3.4 and 3.5 include monthly and seasonal daytime, nighttime and total averages of the resilient modulus of the asphalt concrete for eight of the nine monitored stations. Once again these averages were determined from corresponding average AC temperatures as summarized in Tables 3.1 and 3.2, in combination with Equation 2.1. It is evident, that the three temperature zones proposed in the previous section are reaffirmed in regards to the relative values of the modulus of the AC. Specifically, the southern zone is represented by the Adams and Athens Co. stations; the central zone by the Licking, Knox and Crawford Co. stations and the northern zone by the Lucas and two Wood Co. stations. Expected ranges of the resilient modulus are easily selected from this table. A graphical representation of the monthly and seasonal averages of the resilient modulus of the asphalt concrete is included in Figures 3.11 and 3.12 respectively.

Figure 3.7 HOURLY VARIATION OF AC MODULUS - WOOD 2.85 STATION (SPRING)




Figure 3.8 HOURLY VARIATION OF AC MODULUS - WOOD 2.85 STATION (SUMMER)




Figure 3.9 HOURLY VARIATION OF AC MODULUS - WOOD 2.85 STATION (FALL)




Figure 3.10 HOURLY VARIATION OF AC MODULUS - WOOD 2.85 STATION (WINTER)




Table 3.4 AVERAGE MONTHLY AC MODULUS (MPa)

COUNTY	TIME	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
ADAMS	day	11313.1	9693.0	7879.8	4715.5	2488.7	1130.6	627.4	903.1	1992.4	4143.3	7721.3	10175.5
	night	11416.5	9899.8	8217.6	5094.7	2840.3	1378.8	841.1	1109.9	2240.6	4432.8	7948.8	10292.7
	total	11361.3	9796.4	8045.3	4901.6	2661.1	1254.7	730.8	1006.5	2109.6	4288.1	7838.5	10237.6
ATHENS	day	11554.3	10754.6	8500.3	4936.1	2523.2	1082.4	544.6	903.1	2130.2	4625.9	8100.5	10871.8
	night	11726.7	11051.1	8962.2	5480.7	3019.6	1489.1	861.8	1213.3	2537.0	5060.2	8424.5	11071.8
	total	11637.1	10906.3	8734.7	5205.0	2757.6	1282.3	703.2	1054.8	2323.3	4839.6	8259.0	10968.4
CRAWFORD	day	13064.1	12009.3	9637.8	5784.1	3247.1	1668.3	1082.4	1530.5	2847.2	5377.3	8762.3	11319.9
	night	13112.4	12174.8	10072.1	6294.2	3757.2	2047.5	1399.5	1806.2	3164.3	5722.0	8996.7	11430.3
	total	13084.8	12092.1	9851.5	6039.1	3495.3	1854.5	1240.9	1668.3	3005.8	5549.7	8879.5	11375.1
KNOX	day	12781.5	11568.1	9300.0	6356.3	3805.5	1951.0	1089.3	1475.3	2874.8	5694.4	9024.2	11595.7
	night	12850.4	11699.1	9596.4	6728.5	4198.4	2192.3	1296.1	1675.2	3116.1	5990.9	9244.9	11843.9
	total	12815.9	11630.2	9451.7	6542.4	3998.5	2068.2	1192.7	1571.8	2992.0	5839.2	9134.6	11664.6
LICKING	day	11864.6	11016.6	8886.4	5784.1	3660.7	2075.1	1461.5	1647.7	2874.8	5273.9	8369.3	10437.5
	night	11857.7	11078.7	9086.3	6032.3	3970.9	2261.2	1613.2	1778.7	3012.7	5377.3	8458.9	10478.9
	total	11864.6	11051.1	8982.9	5908.2	3819.3	2164.7	1537.4	1709.7	2943.7	5329.1	8410.7	10458.2
LUCAS	day	13160.6	12912.5	9892.9	6652.7	3915.8	2178.5	1599.4	1785.5	3240.2	5818.5	8776.1	11416.5
	night	13284.7	13071.0	10113.5	6776.8	4046.8	2337.1	1771.8	1937.2	3371.2	5887.5	8872.6	11499.2
	total	13222.7	12995.2	9961.8	6721.7	3984.7	2261.2	1682.1	1868.3	3302.2	5853.0	8824.3	11457.8
WOOD2	day	13477.8	13215.8	9927.4	6397.6	3247.1	1854.5	1178.9	1606.3	2833.4	5549.7	8693.3	11333.7
	night	13484.7	13312.3	10258.3	6832.0	3709.0	2026.8	1296.1	1744.2	2950.6	5687.6	8789.9	11368.2
	total	13484.7	13264.1	10092.8	6618.2	3474.6	1944.1	1234.0	1675.2	2895.5	5618.6	8741.6	11354.4
WOOD8	day	13670.8	12864.2	10465.1	6852.6	3991.6	2157.8	1371.9	1806.2	3136.8	5784.1	9520.6	12388.5
	night	13677.7	12898.7	10603.0	7052.6	4184.7	2254.3	1434.0	1861.4	3178.1	5846.1	9555.1	12402.3
	total	13677.7	12878.0	10534.0	6949.2	4088.1	2206.1	1406.4	1833.8	3157.5	5811.6	9534.4	12395.4
ALL	day	12610.8	11754.3	9311.2	5934.9	3360.0	1762.3	1119.4	1457.2	2741.2	5283.4	8620.9	11192.4
	night	12676.3	11898.2	9613.7	6286.5	3715.9	1998.4	1314.2	1640.8	2946.3	5500.6	8786.4	11298.4
	total	12643.6	11826.7	9456.8	6110.7	3534.9	1879.5	1215.9	1548.6	2841.2	5391.1	8702.8	11238.9
NORTH	day	13436.4	12997.5	10095.1	6634.3	3718.2	2063.6	1383.4	1732.7	3070.1	5717.4	8996.7	11712.9
	night	13482.4	13094.0	10324.9	6887.1	3980.1	2206.1	1500.6	1847.6	3166.6	5807.0	9072.5	11756.6
	total	13461.7	13045.7	10196.2	6763.0	3849.2	2137.1	1440.8	1792.4	3118.4	5761.1	9033.4	11735.9
CENTRAL	day	12570.1	11531.4	9274.7	5974.8	3571.1	1898.1	1211.0	1551.2	2865.6	5448.6	8718.6	11117.7
	night	12606.8	11650.9	9585.0	6351.7	3975.5	2167.0	1436.3	1753.4	3097.7	5696.7	8900.2	11251.0
	total	12588.4	11591.1	9428.7	6163.2	3771.0	2029.1	1323.6	1650.0	2980.5	5572.7	8808.2	11166.0
SOUTH	day	11433.7	10223.8	8190.1	4825.8	2506.0	1106.5	586.0	903.1	2061.3	4384.6	7910.9	10523.7
	night	11571.6	10475.4	8689.9	5287.7	2930.0	1434.0	851.4	1161.6	2388.8	4746.5	8186.6	10682.3
	total	11499.2	10351.3	8390.0	5053.3	2709.3	1268.5	717.0	1030.7	2216.4	4563.8	8048.7	10603.0

Table 3.5 AVERAGE SEASONAL ASPHALT CONCRETE ELASTIC MODULUS
(MPa)

LOCATION		SPRING	SUMMER	FALL	WINTER
ADAMS	day	3129.9	944.5	6046.0	10216.9
	night	3481.5	1165.1	6308.0	10396.2
	total	3302.2	1047.9	6177.0	10306.5
ATHENS	day	3309.1	937.6	6583.8	10796.0
	night	3826.2	1282.3	6949.2	11064.9
	total	3564.2	1096.1	6714.8	10933.9
CRAWFORD	day	4060.6	1530.5	7321.4	12043.8
	night	4570.7	1826.9	7590.3	12209.3
	total	4315.6	1675.2	7459.3	12126.5
KNOX	day	4619.0	1509.8	7576.5	11802.5
	night	4991.3	1730.4	7817.8	11947.3
	total	4894.7	1620.1	7700.6	11878.4
LICKING	day	4474.2	1792.4	6983.6	11002.8
	night	4750.0	1930.3	7066.4	11058.0
	total	4612.1	1861.4	7025.0	11030.4
LUCAS	day	4825.8	1937.2	7486.9	12402.3
	night	4956.8	2102.7	7562.7	12512.6
	total	4894.7	2019.9	7528.2	12457.5
WOOD 2	day	4391.5	1633.9	7376.6	12636.7
	Night	4812.0	1758.0	7480.0	12726.3
	total	4598.3	1695.9	7424.8	13367.5
WOOD 8	day	4915.4	1806.2	7907.4	12829.7
	night	5094.7	1861.4	7948.8	12871.1
	Total	5005.0	1833.8	7928.1	12850.4
ALL	day	4215.7	1511.5	7160.3	11716.4
	night	4560.4	1707.1	7340.4	11848.2
	Total	4398.4	1606.3	7244.7	11868.9
NORTH	day	4710.9	1792.4	7590.3	12622.9
	night	4954.5	1907.3	7663.8	12703.3
	Total	4832.7	1849.9	7627.1	12891.8
CENTRAL	day	4384.6	1610.9	7293.9	11616.4
	night	4770.6	1829.2	7491.5	11738.2
	Total	4607.5	1718.9	7395.0	11678.4
SOUTH	day	3219.5	941.0	6314.9	10506.5
	night	3653.8	1223.7	6628.6	10730.5
	Total	3433.2	1072.0	6445.9	10620.2

3.1.5 Seasonal Subgrade Temperature Variations

The most important information obtained from the seasonal variation of subgrade temperature refers to the depth of frost penetration. This information is helpful when determining roadside drainage ditch depths as well as granular base thickness for asphalt concrete pavements when the subgrade soil is frost susceptible.

Two computer programs were written to scan the collected data files containing the temperature at a given time of the day measured by the active temperature sensors to determine the maximum depth of frost penetration and the number of freeze-thaw cycles. In the first program, for a given reporting time, the temperature values are examined in order of decreasing sensor depth. Once the first sub-freezing temperature value is found, the depth of frost penetration is obtained by linearly interpolating between the depth of this temperature sensor, its corresponding temperature, the depth of the temperature sensor immediately below the first frozen temperature sensor, and its temperature. This program then generates a file containing the time of the year in decimals of months and the depth of frost penetration in feet. The second program takes the data file generated by the first scanning program and determines the number of freeze-thaw cycles and the depth of frost penetration. A frost cycle is defined as a period when the frost line drops below the bottom of the asphalt concrete pavement and then recedes back into the pavement surface layer. Figure 3.13 depicts the maximum depth of frost penetration, while Figure 3.14 shows the number of freeze-thaw cycles. A combined presentation of the number of freeze-thaw cycles and depth of frost penetration (in English units) for the winters between 1991-1992 to 2000-2001 is included in Figure 3.15 for the available data at eight of the nine monitoring stations. It is to be noted from this figure that when the frost penetration is high at the northern sites the number of freeze-thaw cycles is lower. This normally occurs during harsh winters. The number of cycles appears to increase during milder winters. Normally, the northern sites experience an average 7 to 12 cycles as compared to between 4 and 5 in the southern sites.

Figure 3.13 MAX. DEPTH OF FROST PENETRATION






Figure 3.14 NUMBER OF FREEZE-THAW CYCLES



As expected the depth of frost penetration is greater in the northern than in the southern stations. The maximum depth of frost penetration measured to date approached 121.9 cm. (4.0') at the Wood 2 station during the 1993-1994 winter, which happened to be a severe winter. On a normal season the average depth of frost penetration is about 45.7 to 61.0 cm. (1.5 to 2.0') at the southern stations and from 70.1 to 82.3 cm. (2.3 to 2.7') at the northern locations.

Summary tables and average values are included in Appendix B (Tables B1 to B8) showing the depth of frost penetration and the number of freeze-thaw cycles during each monitored winter for each of the seven monitoring stations. This data is complete including the monitoring periods listed in Table 2.3.

Figure 3.15 No. OF F-T CYCLES & FROST DEPTH



The most critical condition occurs when frost penetrates the entire surface layer and enters the gravel base and the subgrade soil. It is to be indicated that the definition of a frost cycle, previously given, does not take into consideration its "severity". For example, the long,

3.3 Degree of Saturation

In order to determine the degree of saturation from the voltage readings generated by the gypsum block-type moisture sensors the calibration developed by Figueroa et al. (1994) during the project "Characterization of Ohio Subgrade Types" was adopted as explained below.

3.3.1 Moisture Sensor Calibration Factors

Typically the gypsum block sensors provide a voltage output of approximately 0.0 volts when completely dry and of 4.0 volts when saturated (submerged). Incidentally, output voltages in excess of 4.0 have been observed (up to about 4.3 V) in the data retrieved at one of the Logger sites. It is possible that the moisture sensors are picking up localized spurious electrical currents. Another explanation involves the temperature sensors. Each moisture sensor has a temperature probe located six inches above it and six inches below. These temperature probes operate on a 5VDC current. The moisture sensors, on the other hand, use a 4VAC power source. In extremely wet soil there might be some current leakage ("cross talk") from the temperature probes to the moisture sensors.

Since the output voltages of the moisture sensors are being recorded at all sites, the calibration equation suggested by Armstrong, et al. (1985) had to be modified (see Figueroa et al. 1994, for more details). The sensor resistance contained in this equation was replaced by sensor output voltage and soil moisture tension was replaced by the degree of soil saturation. In addition, the degree of saturation is approximately inversely proportional to the soil moisture tension, as shown by Walsh et al. (1993). The developed combined equation are presented next.

Using the nomenclature

C, D, E, F, G, and H = Regression constants

V = Sensor output voltage (V)

T = Sensor temperature (Deg C)

Sr = Degree of saturation of the soil (%)

During the sensor calibration, it was observed that for a given degree of saturation, its output voltage varied linearly with temperature. Thus the equation:

$$V = A + BT \quad (3.1)$$

Could be followed to link voltage output to temperature. The slope and vertical intercept of the straight line represented by this equation was found to be a function of the degree of saturation of the soil. Coefficients A and B best related to the degree of saturation using a second order polynomial fit as shown below.

$$A = C + DSr + ESr^2 \quad (3.2)$$

$$B = F + GSr + HSr^2 \quad (3.3)$$

Since the sensor output voltage and the sensor temperature are known, Equation 3.1 needed to be solved in conjunction with Equations. 3.2 and 3.3 for the degree of saturation (S). As a result, Equation 3.4 was obtained.

$$(E+HT)Sr^2 + (D+GT)Sr + (C+FT-V) = 0 \quad (3.4)$$

The positive root of this simple quadratic equation is then solved for S, leading to Equation 3.5

$$Sr = \frac{-(D+GT) + \sqrt{(D+GT)^2 - 4(E+HT)(C+FT-V)}}{2(E+HT)} \quad (3.5)$$

with regression constants:

$$C = 2.14103$$

$$D = -0.04139$$

$$E = 5.973315 \times 10^{-4}$$

$$F = -0.03814$$

$$G = 2.312154 \times 10^{-3}$$

$$H = -1.92560 \times 10^{-5}$$

and Coefficient of Determination $R^2 = .94$

This equation is valid for fine-grained soils with temperatures between 0 and 30 degrees Celsius and corresponding moisture sensor output voltages between 1.5 and 4.0 volts. In practice, the temperature at the moisture sensor depth is determined by interpolation of the temperature measured by the thermistors located above and below the moisture sensor, since the thermistors and moisture sensors are normally offset every six inches.

3.3.2 Degree of Saturation Results

Whenever possible, the degree of saturation was determined at each location at four sensor depths designated by sensors W1, W2, W3 and W4, which measure voltages corresponding to Sr. The location of each sensor is specified in Table 2.2b with W1 being the deepest and in sequential order W2, W3 and finally W4 being the closest to the surface. The degree of saturation corresponding to these sensors has been labeled Sr1, Sr2, Sr3 and Sr4 respectively.

Monthly averages of the degree of saturation are included in Figures 3.17 to 3.24 for eight of the nine stations, with the numerical detail contained in Tables C19 to C26. Each figure and table shows the values for each of the working moisture sensors identified above. Seasonal values have been included in Figures 3.25 to 3.32 and in Tables C27 to C34, where the “*” following the specific season indicates incomplete data.

Examination of these figures and tables indicates that the degree of saturation varies between about 90% and 100% throughout the monitoring period. It is also observed that the degree of saturation “appears” to consistently decrease in the winter months. This may not actually be an actual decrease in Sr but a peculiarity of the sensor, in particular when the frost line reaches the sensor depth. Minor variations in Sr (between 96 and 100%) are observed throughout the year, which may be associated to previous rainfall regime affecting this zone. The late spring to early summer period seems to consistently lead to slightly higher (nearing 100%) degree of saturation at all depths. The delay in the increase with respect to the higher rainfall may be attributed to the low permeability of the subgrade soil and the time it takes for moisture to migrate from the shoulder to the center of the lane. In late summer and fall the flow will be

reversed from the center of the lane to the shoulder, also leading to somewhat lower degree of saturation prior to the beginning of the winter.

Figure 3.17 Variation of Degree of Saturation ADAMS Co.




Figure 3.18 Variation of Degree of Saturation ATHENS Co.




Figure 3.19 Variation of Degree of Saturation COLUMBIANA Co.




Figure 3.20 Variation of Degree of Saturation CRAWFORD Co.




Figure 3.21 Variation of Degree of Saturation KNOX Co.




Figure 3.22 Variation of Degree of Saturation LICKING Co.




Figure 3.23 Variation of Degree of Saturation WOOD2 Co.




Figure 3.24 Variation of Degree of Saturation WOOD8 Co.




Figure 3.25 Seasonal Degree of Saturation-ADAMS Co.




Figure 3.26 Seasonal Degree of Saturation-ATHENS Co.




Figure 3.27 Seasonal Degree of Saturation-COLUMBIANA Co.




Figure 3.28 Seasonal Degree of Saturation-Cawford Co.




Figure 3.29 Seasonal Degree of Saturation-KNOX Co.




Figure 3.30 Seasonal Degree of Saturation-LICKING Co.




Figure 3.31 Seasonal Degree of Saturation-WOOD2 Co.





Figure 3.32 Seasonal Degree of Saturation-WOOD8 Co.



THIS PAGE LEFT INTENTIONALLY BLANK

Chapter 4

BACK CALCULATION OF RESILIENT MODULUS OF SUBGRADE SOILS FROM FALLING WEIGHT DEFLECTOMETER TEST RESULTS

An alternate procedure to evaluate the influence of seasonal factors on the material properties of flexible pavements is with the use of non-destructive testing techniques. Proper characterization of the response of a flexible pavement subjected to repeated, dynamic loads and its seasonal variations are essential in the development of mechanistic-based pavement design procedures. Findings from a previous study by Thompson et al. (1976) indicated that the seasonal resilient behavior of the asphalt concrete and the fine-grained soil significantly influence the performance of a flexible pavement.

Recently the Falling Weight Deflectometer (FWD) has gained popularity in the evaluation of pavement layer mechanical properties. As part of this research project, the Ohio Department of Transportation has been conducting FWD testing at six of the station locations, with a frequency of 3 to 4 times per year, in an effort to evaluate material property variation on a seasonal basis. Details of the method developed in this project to back calculate the resilient modulus of subgrade soils at the break point from measured FWD deflections were introduced in Section 2.2.2 of this report and will be expanded next, followed by actual computations.

4.1 Analysis Method

Falling Weight Deflectometer (FWD) tests at three different load levels were performed three to four times a year (once every season, when possible) at six of the station locations. FWD testing was conducted along a 152.4 m. (500 ft.) long section at a spacing of 15.2 m. (50 ft.) A reference point at mid-length within the test section was selected to coincide with the seasonal instrumentation installed in the middle of the travel lane.

FWD Loads are applied to the asphalt concrete surface via a rubber coated steel loading plate, with a radius of 15 cm. (5.9 in.) and the corresponding pavement deflections are measured

and recorded at seven radial distances including 0.0, 20.3, 30.5, 45.7, 61.0, 91.4 and 152.4 cm. (0.0, 8.0, 12.0, 18.0, 24.0, 36.0 and 60.0 in.) from the center of the loading plate.

As previously indicated, the flexible pavement analysis program (ILLIPAVE) was used to develop nomographs to back calculate the resilient modulus at the break point of the subgrade based on measured maximum Falling Weight Deflectometer (FWD) deflections for a given soil type, during the “Characterization of Ohio Subgrade Types” project (Figuroa et al., 1994). The resilient modulus at the break point was selected as the representative parameter to define both the bilinear stress-dependent model introduced by Thompson et al. (1976), as well as the stiffness characteristics of fine-grained soils.

The back calculation procedure has been previously shown in Figure 2.2. A FORTRAN computer program to follow this procedure was written for each of the six test sites, with the following detail:

- Since FWD testing is conducted at three load levels between approximately 40.03 and 53.38 kN (9000 and 12000 lbs), linear interpolation is used to calculate the deflection at exactly 53.38 kN (12000 lbs) of load. This load was selected, since nomographs were developed previously to determine the maximum FWD deflection according to Equation 2.5, with the coefficients contained in Table 2.5, for this selected magnitude of load. These coefficients indicate the relative influence of E_{ac} with respect to E_{ri} in affecting the total deflection, leading to the conclusion that the total deflection is very sensitive to the variation of E_{ri} . This influence is evident in the values of the coefficients a_4 and a_3 , whereby a_4 is approximately two orders of magnitude higher than a_3 , although E_{ac} and E_{ri} do not differ by as much as two orders of magnitude at a given time during the year.
- The air temperature is in most instances measured during FWD tests. Alternatively, when the FWD does not provide the air temperature, it is interpolated from logger air temperature readings obtained at the same time the FWD testing was conducted.
- The air temperature is entered into Equation 2.4 using the coefficients for the specific site and the corresponding average asphalt concrete pavement temperature is obtained.

- The AC pavement temperature is then entered into Equation 2.1 (with coefficients defined in Table 2.4) to obtain the AC modulus at the time of FWD testing.
- The AC modulus is entered into Equation 2.6 with the coefficients corresponding to the soil type existing at the site, along with pavement section characteristics such as the AC thickness, the gravel base thickness, and the maximum FWD deflection (interpolated at 53.38 kN (12000 lbs) of FWD load) to obtain the resilient modulus of the subgrade soil at the break point E_{ri} .
- The process is repeated for each of the eleven locations along the test section and the program calculates an average resilient modulus for the complete section, as well as for the reference point (where the logger instrumentation is located)

Data to back calculate the resilient modulus at the break point, including date, time and temperature of seasonal FWD testing is included in Tables D1 to D6 for each of the six tested and analyzed locations. These tables also specify whether the air temperature was measured by the FWD or by the data logger. Testing periods have been designated by the four seasons. However, these designations for the most part correspond to the following times of the year:

SPRING:	Late winter – early spring
SUMMER:	Early summer
FALL	Late Summer - early fall
WINTER	Late fall

4.2 Back Calculated Resilient Modulus

Summaries of back-calculated resilient modulus by the procedure outlined above are included in Tables D7 to D12 for the testing detail contained in Tables D1 to D6. Tables D7 to D12 include the average value along the section, corresponding to eleven FWD test locations as well as E_{ri} at the reference point where the seasonal instrumentation is located. Overall seasonal averages of both moduli were also calculated and are included in Table 4.1. This table also

Table 4.1 Average Seasonal Resilient Modulus Back Calculated from FWD Deflections

(MPa)

STATION	Res. Mod. Eri	SPRING	SUMMER	FALL	WINTER
ADAMS	Av. Along Sect.	33.9	19.1	42.1	19.0
	% From Max.	80.70	45.46	100.00	45.16
	@ Ref. Pt.	50.6	40.1	53.7	56.6
ATHENS	Av. Along Sect.	144.8	153.2	155.5	143.0
	% From Max.	93.15	98.50	100.00	91.93
	@ Ref. Pt.	162.8	162.0	163.7	157.9
CRAWFORD	Av. Along Sect.	31.6	36.0	28.1	44.5
	% From Max.	70.95	80.84	63.17	100.00
	@ Ref. Pt.	31.6	42.3	33.6	54.0
KNOX	Av. Along Sect.	41.9	76.7	76.6	82.0
	% From Max.	51.11	93.49	93.32	100.00
	@ Ref. Pt.	30.3	49.7	51.7	65.8
LICKING	Av. Along Sect.	220.7	242.5	252.5	233.3
	% From Max.	87.40	96.03	100.00	92.40
	@ Ref. Pt.	164.3	186.8	196.5	188.1
WOOD8	Av. Along Sect.	63.7	67.9	82.2	56.2
	% From Max.	87.40	82.58	100.00	68.34
	@ Ref. Pt.	67.9	67.1	88.7	60.9

contains the percentage of the average seasonal modulus along the section with respect to the maximum value observed at any given season during the year. For example, considering the Adams county section, the maximum average modulus of 42.1 MPa (6.10 ksi) is observed in the

designated fall testing period, whereas the spring testing period yields $E_{ci} = 33.9$ MPa, (4.92 ksi) which is 80.70% of 42.1 MPa (6.1 ksi). These percentages are useful in ranking the seasons of higher to lower modulus. By assigning a ranking of 4 to the season with the highest modulus and of 1 to the season with the lowest modulus (obviously ranks of 3 and 2 to the intermediate seasons) at each station location, a total point ranking is obtained by adding the points for individual seasons. In order of higher point ranking and consequently of expected higher resilient modulus the designated “fall” testing period is the highest followed by “summer”, “winter” and “spring” in decreasing order. This ranking is expected since the fall testing period follows the generally drier summer season and the spring testing period happens at the spring thaw and normally wetter early spring. The high resilient modulus averages obtained at the Licking Co. station can be explained by the presence of the 45.7 cm (18 in) – thick lime stabilized layer existing beneath the gravel base.

The back calculated average resilient modulus (at the break point) along the test section and at the reference point have been included in dual axis plots with the amount of seasonal rainfall in Figures 4.1 to 4.6, for individual instrumented test sections, in an effort to determine if any relationship exists between amount of rainfall and subgrade modulus. More detailed similar plots containing the monthly rainfall and the average resilient modulus along the section were also drawn for each test section and are included in Figures 4.7 to 4.12.

The observation of the two sets of figures indicates that for the most part a higher back calculated resilient modulus follows generally lower amounts of rainfall. Similarly lower resilient modulus back calculations are generally preceded by higher rainfall. However, no correlation between the amount of rainfall accumulated during either one, two or three months preceding the date of FWD testing with the back calculated resilient modulus was found.

Figure 4.1 Resilient Modulus Variation (Adams)




Figure 4.2 Resilient Modulus Variation (Athens)




Figure 4.3 Resilient Modulus Variation (Crawford)




Figure 4.4 Resilient Modulus Variation (Knox)




Figure 4.5 Resilient Modulus Variation (Licking)




Figure 4.6 Resilient Modulus Variation (Wood8)




Figure 4.7 Resilient Modulus vs. Monthly Rainfall (Adams Co.)




Figure 4.8 Resilient Modulus vs. Monthly Rainfall (Athens Co.)




Figure 4.9 Resilient Modulus vs. Monthly Rainfall (Crawford Co.)




Figure 4.10 Resilient Modulus vs. Rainfall (Knox Co.)




Figure 4.11 Resilient Modulus vs. Monthly Rainfall (Licking Co.)





Figure 4.12 Resilient Modulus vs. Rainfall (Wood 8)



THIS PAGE LEFT INTENTIONALLY BLANK

Chapter 5

SUMMARY AND CONCLUSIONS

Nine moisture-temperature-rainfall recording stations previously installed during the project "Characterization of Ohio Subgrade Types" (Figuroa et al. 1994) and monitored for an additional time period of 2-1/2 years during the project "Monitoring and Analysis of Data Obtained from Moisture-Temperature Recording Stations," were monitored during this project for an additional period of three years. These stations were located in Adams, Athens, Columbiana, Crawford, Licking, Lucas and Wood (two stations) county. The station locations were selected to include the variation in climate within the state of Ohio and the four most commonly occurring soil types (A-3, A-4, A-6, and A-7). The Columbiana Co. station was destroyed by a vehicle crash and one of the Wood Co. stations had to be dismantled because of new urban development in its vicinity. These stations recorded hourly, daily and seasonal variations in air temperature, rainfall, temperature within the asphalt concrete layer and moisture content (or degree of saturation) and temperature within the subgrade soil.

The temperature sensors recorded air, asphalt concrete pavement and subgrade soil temperatures. Typically, temperature variations within the subgrade soil are minimal on a daily basis. Only the uppermost subgrade soil thermistor shows daily temperature variations, although within a narrower range, following those of the lowest asphalt concrete thermistor.

The thermistors within the asphalt concrete layer exhibit large daily temperature fluctuations. Typically the AC layer exhibits a uniform temperature (no temperature gradient) twice a day, normally occurring between 8:00 and 10:00 AM and around 8:00 PM. After the morning period of no temperature gradient, thermistors closer to the surface show faster warming as compared to those near the bottom of the surface layer. An opposite trend occurs after the evening period of no temperature gradient. This information is important in selecting the optimal times for FWD testing (between 8:00-10:00 AM) since the surface layer exhibits a uniform stiffness throughout its thickness. Similarly, the maximum daytime temperature gradient

within the pavement is observed between 2:00 and 4:00 PM at all seasons and the maximum overnight temperature gradient occurs around 6:00 AM. It is to be noted that the temperature gradient is greater in the afternoon than in the early morning and that AC layer temperature variations closely follow air temperature changes.

The average AC pavement temperature was calculated in the middle of the layer at each location, then monthly and seasonal averages were tabulated. The average pavement temperature difference between summer and winter is of the order of 30 to 35 deg. C at all sites. This range also indicates the wide variation in the elastic properties of the AC. As expected the northern sites exhibit slightly lower averages than the southern sites. The average monthly and seasonal asphalt concrete temperatures are summarized in Tables 3.1 and 3.2 respectively for each tested site.

Figuroa et al. (1994) indicated from observations in temperature changes within the pavement and subgrade profiles that the daytime and the nighttime averages for any sensors located at depths in excess of 30.48 cm. (1.0 ft.) (i.e. the subgrade soil sensors) are very similar. In addition, the asphalt concrete sensors show warmer temperatures than the subgrade soil sensors (on the average) during the spring and summer. However, this trend reverses during the fall and winter.

Polynomial equations were derived relating the average asphalt concrete pavement temperature to the air temperature for eight (excluding the Columbiana Co.) of the nine monitored stations. The coefficients included in these equations indicate that asphalt concrete temperature is higher in the southern part than in the northern part of the state. The regression coefficients also point to the fact that the state of Ohio may be subdivided into three general temperature zones: North, (from the North Shore to Mansfield – Mount Vernon) Central (from Mansfield – Mount Vernon to Lancaster) and South (from Lancaster to the southern state line). This division is useful in assessing the average AC modulus on a seasonal or monthly basis for any future implementation of mechanistic pavement design procedures. Separate regression coefficients have been provided for each of the three zones as well as for all of them together.

Table 3.3 includes the coefficients applicable to the polynomial equation of the form of Equation 2.4 for the eight specific sites, all sites grouped together as well as the northern, central and southern zones of the state. It is then possible to determine the average asphalt concrete temperature from measured air temperature which is normally obtained during FWD testing.

As a result of temperature differences during the four seasons the resilient modulus of the asphalt concrete also changes in an inverse form to the temperature variation. It was determined that for a typical mid-season day the resilient modulus averages:

3791.7 MPa (550 ksi) in the spring (+/- 1034.1 MPa or +/- 150 ksi)

1723.5 MPa (250 ksi) in the summer (+/- 1034.1 MPa or +/- 150 ksi)

8272.8 MPa (1200 ksi) in the fall (+/- 1378.8 MPa or +/- 200 ksi)

15511.5 MPa (2250 ksi) in the winter (+/- 1551.1 MPa or +/- 225 ksi)

These typical modulus values also indicate that the contribution of the subgrade soil in supporting traffic loads is more important during the warmer months because of the lower stiffness of the surface layer during this time of the year. Unfortunately, this fact is also coupled with the lower stiffness of the subgrade soil itself during and after the rainy spring and early summer as is typical in Ohio. Consequently the two combined effects make the spring-summer the critical time of the year considering environmental effects. Typical monthly and seasonal average values of the resilient modulus of the asphalt concrete for each station, for the three suggested climatic zones and for all of the state have been calculated from the collected data. Average monthly and seasonal asphalt concrete modulus values are listed in Tables 3.4 and 3.5 respectively. These tables contain specific values for each location, all combined stations, the northern, central and southern zones of the state, of direct application as inputs to a mechanistic pavement design procedures.

Recorded depths of frost penetration show, as expected, that they are greater in the northern than in the southern stations. The maximum depth of frost penetration measured to date approached 121.9 cm. (4.0 ft.) at the Wood 2 station during the 1993-1994 winter, which happened to be a severe winter. On a normal season the average depth of frost penetration is

about 45 to 61 cm. (1.5 to 2.0 ft) at the southern stations and from 70 to 82 cm. (2.3 to 2.7 ft) at the northern locations. It was also observed that when the frost penetration is high at the northern sites the number of freeze-thaw cycles is lower. This normally occurs during a severe winter. The number of cycles appears to increase during milder winters. Normally, the northern sites experience an average 7 to 12 cycles as compared to between 4 and 5 in the southern sites. Detailed curves of depth of frost penetration and number of freeze-thaw cycles are included in section 3.1.5 and in Appendix B

Collected precipitation was summarized on a monthly and seasonal basis to determine if a correlation existed between the amount of precipitation and the degree of saturation of the subgrade soil, as well as the value of the back calculated resilient modulus from Falling Weight Deflectometer-measured deflections.

A calibration equation previously developed was used to obtain monthly and seasonal averages of the degree of saturation from moisture and temperature sensor readings at each of four moisture sensor locations. The degree of saturation typically varied between about 90% and 100% throughout the monitoring period. It was also observed that the degree of saturation “appears” to consistently decrease in the winter months. This may not actually be an actual decrease in S_r but a peculiarity of the sensor, in particular when the frost line reaches the sensor depth. Minor variations in S_r (between 96 and 100%) are observed throughout the year which may be associated to previous rainfall regime affecting this zone. The late spring to early summer period seems to consistently lead to slightly higher (nearing 100%) degree of saturation at all depths. The delay in the increase with respect to the higher rainfall may be attributed to the low permeability of the subgrade soil and the time it takes for moisture to migrate from the shoulder to the center of the lane. In late summer and fall the flow will be reversed from the center of the lane to the shoulder, also leading to somewhat lower degree of saturation prior to the beginning of the winter.

Finally a method to back calculate the resilient modulus of subgrade soils (E_{ri}) at the break point from measured FWD deflections was developed. The method, explained in Section

2.2.2. requires the input of the maximum FWD deflection, the resilient modulus of the asphalt concrete (alternatively determined from air temperature readings in combination with Equations 2.4 and 2.1) and the thickness of the asphalt concrete and the base layers. Eri is back calculated through equation 2.6 using the coefficients listed in Tables 2.5a and 2.5b depending on the soil type (A-4, A-6 or A-7) and the applied FWD load. If the exact FWD load is not found in these tables, interpolation is required.

Overall seasonal averages of Eri were obtained at each of six station locations where FWD testing was conducted. Seasons were ranked in terms of expected higher resilient modulus. The designated “fall” testing period (early fall) showed the highest followed by “summer”, “winter” and “spring” in decreasing order. This ranking is expected since the fall testing period follows the generally drier summer season and the spring testing period happens at the spring thaw and normally wetter early spring, also reflected in a higher degree of saturation, as described above.

Generally, for the most part a higher back-calculated resilient modulus followed lower amounts of rainfall. Similarly lower resilient modulus back calculations were generally preceded by higher rainfall.

Attempts to correlate the amount of rainfall accumulated over either one month, two or three months preceding the date of FWD testing with the back calculated resilient modulus were unsuccessful.

THIS PAGE LEFT INTENTIONALLY BLANK

References

- Armstrong, C.F., Ligon, J.T., and Thomsom, S.J. "Calibration of Watermark Model 200 Soil Moisture Sensor," American Soc. of Agricultural Engineers Paper no. 85-2077, St. Joseph, Michigan, 1985.
- Figuroa, J.L., Angyal, E and Su, X. "Characterization of Ohio Subgrade Types," Final Report No. FHWA/OH-94/006 Submitted to the Ohio Department of Transportation, Department of Civil Engineering, Case Western Reserve University, Cleveland, OH, June, 1994.
- Thompson, M.R. and Robnett, Q.L., "Final Report, Resilient Properties of Subgrade Soils," Civil Engineering Studies Transportation Engineering Series no. 14, Illinois Cooperative Highway and Transportation Series no. 160, 1976.
- Walsh, K. D., Houston, W. N., and Houston, S. L., "Evaluation of In-Place Wetting Using Soil Suction Measurements," Journal of Geotechnical Engineering, vol. 119, no. 5, pp. 862-873, 1993.

THIS PAGE LEFT INTENTIONALLY BLANK

Appendix A

**AVERAGE AC TEMPERATURE AND RELATIONSHIPS BETWEEN
AIR TEMPERATURE AND AVERAGE ASPHALT CONCRETE
PAVEMENT TEMPERATURE**

Table A1. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Adams Co.)
(deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1991	day				
	night				
	total				
1992	day				
	night				
	total				
1993	day				-*
	night				-*
	total				-*
1994	day	22.37	-*	-	-
	night	21.37	-*	-	-
	total	21.87	-*	-	-
1995	day	-*	32.78	12.53	2.90
	night	-*	31.93	11.97	2.64
	total	-*	32.35	12.25	2.77
1996	day	-*	-	-*	5.40
	night	-*	-	-*	4.98
	total	-*	-	-*	5.19
1997	day	19.90	31.24	13.63	6.80
	night	18.68	30.03	12.93	6.48
	total	19.29	30.64	13.28	6.64

* Incomplete Data

- Data not available

Table A1. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Adams Co.)
 Cont. (deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1998	day	22.45	32.52	15.65	5.12
	night	21.36	31.32	14.94	4.74
	total	21.90	31.92	15.30	4.93
1999	day	23.91	32.87	16.46	-
	night	22.52	31.47	15.66	-
	total	23.21	32.17	16.06	-
2000	day	24.77	29.17	12.53	3.76
	night	23.65	28.23	11.98	3.39
	total	24.21	28.70	12.25	3.57

* Incomplete Data
 - Data not available

Table A2. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Athens Co.)
(deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1991	day				5.72
	night				4.32
	total				5.02
1992	day	21.59	30.28	13.10	4.14
	night	18.73	28.91	12.27	3.66
	total	20.16	29.59	12.69	3.90
1993	day	22.22	33.46	12.86	*
	night	20.13	31.23	11.77	*
	total	21.18	32.34	12.32	*
1994	day	*	31.43	14.77	4.58
	night	*	29.05	13.39	3.70
	total	*	30.24	14.98	4.14
1995	day	22.34	33.92	12.24	1.97
	night	20.27	31.98	11.25	1.72
	total	21.30	32.95	11.75	1.84
1996	day	20.08	-*	-	-*
	night	18.58	-*	-	-*
	total	19.33	-*	-	-*
1997	day	-*	30.14*	12.78	6.23
	night	-*	28.45*	11.86	5.89
	total	-*	29.29*	12.32	6.06

* Incomplete Data

- Data not available

Table A2. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Athens Co.)
Cont. (deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1998	day	23.19	32.92	14.74	3.79
	night	21.66	31.39	14.10	3.73
	total	22.43	32.16	14.42	3.76
1999	day	22.76	34.26*	-	-
	night	21.84	33.02*	-	-
	total	22.30	33.64*	-	-
2000	day	22.37	27.65	9.27	-0.85
	night	21.56	26.90	8.84	-1.13
	total	21.96	27.27	9.05	-0.99

* Incomplete Data

- Data not available

Table A3. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE
(Columbiana Co.) (deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1993	day				
	night				
	total				
1994	day			6.48*	0.42
	night			4.22*	-2.03
	total			5.34*	-0.80
1995	day	13.85	23.62*	6.92	-3.47*
	night	9.45	19.12*	4.74	-4.40*
	total	11.69	21.37*	5.83	-3.94*

* Incomplete Data

- Data not available

Table A4. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Crawford Co.)
(deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1991	day				
	night				
	total				
1992	day	*	26.81	10.22	1.95
	night	*	26.78	10.14	2.06
	total	*	26.80	10.18	2.01
1993	day	18.68	30.75	10.61	-0.81
	night	17.61	28.85	9.81	-1.45
	total	18.15	29.80	10.21	-1.13
1994	day	20.01	29.33	13.32	2.55
	night	17.88	27.37	12.27	1.78
	total	18.95	28.35	12.80	2.17
1995	day	18.42	30.29	9.47	-1.40
	night	16.62	28.54	8.70	-1.60
	total	17.52	29.41	9.08	-1.50
1996	day	15.92	-*	-*	5.46
	night	14.41	-*	-*	4.97
	total	15.16	-*	-*	5.22
1997	day	20.90	30.52	12.69	6.97
	night	18.98	29.17	12.04	6.59
	total	19.94	29.84	12.36	6.78

* Incomplete Data

- Data not available

Table A4. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Crawford Co.)
 Cont. (deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1998	day	23.40	30.48	12.72	-0.08
	night	21.81	29.19	12.01	-0.29
	total	22.61	29.84	12.36	-0.19
1999	day	20.47	28.80	11.18	-
	night	19.23	27.84	10.59	-
	total	19.85	28.32	10.89	-
2000	day	19.64	23.90	8.20	-4.42
	night	18.86	22.92	7.82	-4.30
	total	19.25	23.45	8.01	-4.36

* Incomplete Data

- Data not available

Table A5. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Knox Co.)
(deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1991	day			_*	3.50
	night			_*	2.84
	total			_*	3.17
1992	day	18.49	27.62	10.91	2.47
	night	16.66	27.69	10.80	2.35
	total	17.58	27.65	10.85	2.41
1993	day	19.04	30.59	11.37	-0.02
	night	18.60	30.24	11.16	-0.05
	total	18.82	30.42	11.27	-0.05
1994	day	19.54	28.67	13.30	2.70
	night	18.93	28.23	12.97	2.70
	total	19.24	28.45	13.14	2.70
1995	day	18.11	_*	-	-
	night	17.60	_*	-	-
	total	17.85	_*	-	-
1996	day	18.31	32.12	12.04	2.96
	night	17.97	31.83	11.82	2.97
	total	18.14	31.97	11.93	2.96
1997	day	15.60	28.64	8.86	4.12
	night	15.08	28.39	8.63	4.01
	total	15.34	28.51	8.74	4.06

* Incomplete Data

- Data not available

Table A5. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Knox Co.)
 Cont. (deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1998	day	18.56	30.35	11.01	0.08
	night	18.09	28.03	9.79	-0.67
	total	18.33	29.19	10.40	-0.29
1999	day	17.21	28.35	9.12	-
	night	14.65	25.99	7.76	-
	total	15.63	27.17	8.44	-
2000	day	17.43	25.39	7.04	-1.94
	night	15.28	23.55	6.28	-2.47
	total	16.35	24.47	6.66	-2.21

* Incomplete Data

- Data not available

Table A6. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Licking Co.)
(deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1991	day			-*	4.42
	night			-*	4.21
	total			-*	4.32
1992	day	18.03	25.73	11.18	2.92
	night	17.33	26.26	11.40	3.05
	total	17.68	25.99	11.29	2.98
1993	day	18.74	29.01	11.73	0.57
	night	17.85	28.15	11.42	0.35
	total	18.30	28.58	11.58	0.46
1994	day	19.35	27.30	13.81	3.70
	night	18.46	26.35	13.37	3.50
	total	18.91	26.82	13.59	3.60
1995	day	18.63	28.89	10.80	1.46
	night	17.85	28.27	10.63	1.48
	total	18.24	28.58	10.71	1.47
1996	day	17.60	28.27	10.99	3.78
	night	16.91	27.60	10.76	3.63
	total	17.26	27.94	10.87	3.71
1997	day	16.66	26.17	11.48	5.34
	night	15.88	25.48	11.18	5.24
	total	16.27	25.83	11.33	5.29

* Incomplete Data

- Data not available

Table A6. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Licking Co.)
Cont. (deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1998	day	20.16	28.80*	12.99	3.80
	night	19.29	27.84*	12.75	3.69
	total	19.72	28.32*	12.87	3.74
1999	day	-*			
	night	-*			
	total	-*			

Table A7. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Lucas Co.)
(deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1992	day		25.70	-*	1.45
	night		24.85	-*	1.16
	total		25.28	-*	1.31
1993	day	17.33	27.70	10.42	-1.06
	night	17.07	27.35	10.24	-1.36
	total	17.20	27.52	10.33	-1.21
1994	day	18.79	26.77	12.32	2.29
	night	18.71	26.64	12.27	2.04
	total	18.75	26.70	12.29	2.16
1995	day	16.70	28.44	9.54	-0.18
	night	16.63	27.97	9.28	-0.18
	total	16.66	28.20	9.41	-0.18
1996	day	16.90	27.01	10.37	-
	night	15.89	25.49	10.17	-
	total	16.39	26.25	10.27	-

* Incomplete Data

- Data not available

Table A8. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Wood 2 Co.)
(deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1991	day				
	night				
	total				
1992	day	-*	26.15	9.90	0.91
	night	-*	26.03	9.78	0.70
	total	-*	26.09	9.84	0.81
1993	day	18.68	29.78	9.69	-2.40
	night	16.81	27.88	8.89	-2.91
	total	17.74	28.83	9.29	-2.66
1994	day	20.06	29.33	13.19	2.08
	night	18.11	29.72	13.39	2.29
	total	19.08	29.53	13.29	2.19
1995	day	17.34			
	night	17.54			
	total	17.44			

* Incomplete Data

- Data not available

Table A9. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Wood 8 Co.)
(deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1991	day				
	night				
	total				
1992	day	-*	25.60	-*	0.05
	night	-*	25.92	-*	-0.03
	total	-*	25.76	-*	0.01
1993	day	17.20	28.99	10.18	-*
	night	16.00	27.84	10.04	-*
	total	16.60	28.41	10.11	-*
1994	day	-*	29.09	13.01	1.89
	night	-*	28.71	12.79	1.72
	total	-*	28.90	12.90	1.81
1995	day	17.94	30.53	9.50	-0.88
	night	17.39	30.32	9.41	-0.88
	total	17.66	30.42	9.46	-0.88
1996	day	16.00	28.81	8.92	-0.23
	night	15.60	28.53	8.79	-0.33
	total	15.80	28.67	8.86	-0.28
1997	day	15.20	26.58	8.76	1.84
	night	14.73	26.54	8.75	1.84
	total	14.97	26.56	8.76	1.84

* Incomplete Data

- Data not available

Table A9. AVERAGE SEASONAL ASPHALT CONCRETE TEMPERATURE (Wood 8 Co.)
 Cont. (deg C)

YEAR		SPRING	SUMMER	FALL	WINTER
1998	day	18.67	28.09	11.23	-0.76
	night	18.43	28.01	11.20	-0.82
	total	18.55	28.05	11.22	-0.79
1999	day	18.01	27.25	9.40	-
	night	17.55	27.02	9.28	-
	total	17.78	27.14	9.34	-
2000	day	17.36	24.03	6.63	-3.03
	night	17.10	24.00	6.60	-3.12
	total	17.23	24.01	6.61	-3.08

* Incomplete Data

- Data not available

Table A10. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Adams Co.)
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1991												
1992												
1993												
1994												
1995												
1996												
1997												

* Incomplete Data

- Data not available

Table A10. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Adams Co.) Cont.
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
	6.12	7.26	10.70	18.27	26.16	29.28	32.87	33.11	29.71	19.36	11.39	7.50
1998	5.86	6.88	9.99	17.26	24.99	28.20	31.71	31.81	28.55	18.47	10.76	7.27
	5.99	7.07	10.34	17.76	25.58	28.74	32.29	32.46	29.13	18.92	11.07	7.38
	3.34	6.91	9.12	19.05	27.21	31.81	35.66	32.50	28.07	19.79	14.80	7.42
1999	3.12	6.43	8.19	17.91	25.60	30.33	34.10	31.21	26.84	18.78	14.14	7.03
	3.23	6.67	8.66	18.48	26.41	31.06	34.88	31.86	27.46	19.29	14.47	7.22
	-	-	-	18.02	26.69	30.83	30.64	29.29	24.13	19.34	9.51	0.56
2000	-	-	-	16.99	25.50	29.69	29.62	28.34	23.38	18.53	9.04	0.52
	-	-	-	17.50	26.09	30.26	30.13	28.82	23.76	18.93	9.28	0.54
	0.76	6.10	9.24									
2001	0.47	5.68	8.49									
	0.62	5.89	8.87									

* Incomplete Data

- Data not available

Table A11. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Athens Co.)
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1991												3.70*
												2.73*
												3.22*
1992												
1993												
1994												
1995												
1996												
1997												

* Incomplete Data

- Data not available

Table A11. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Athens Co.) Cont.
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
	5.65	6.56	10.58	18.57	27.13	29.96	33.65	33.63	29.81	18.85	10.01	5.87
1998	5.43	6.15	9.86	17.17	25.47	28.47	31.97	32.04	28.37	17.93	9.61	5.86
	5.54	6.35	10.18	17.87	26.30	29.21	32.81	32.83	29.09	18.39	9.81	5.86
	2.38	5.10	7.96	17.88	25.59	32.12	35.84	32.49*	-	-	-	-
1999	2.39	5.04	7.44	17.27	24.44	30.98	34.60	31.27*	-	-	-	-
	2.39	5.07	7.70	17.58	25.02	31.55	35.22	31.88*	-	-	-	-
	-	-	-	15.43	24.37	28.91	28.91	27.54	22.50	16.21	5.96	-2.69
2000	-	-	-	14.80	23.66	27.90	28.07	27.02	21.61	15.60	5.62	-2.70
	-	-	-	15.11	24.01	28.40	28.49	27.28	22.06	15.90	5.79	-2.69
	-3.15	1.07	3.29									
2001	-3.40	0.81	2.74									
	-3.28	0.94	3.01									

* Incomplete Data

- Data not available

Table A12. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Columbiana Co.)
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1991	day											
	night											
	total											
1992	day											
	night											
	total											
1993	day											
	night											
	total											
1994	day											
	night										8.68*	3.13
	total										6.28*	0.85
1995	day										7.48*	1.99
	night	-1.57	-2.94	6.28	8.97	16.45	24.91*	25.37	18.14	13.82	2.58	-2.95
	total	-2.81	-5.28	2.42	5.42	11.84	20.50*	20.75	13.78	10.60	1.46	-4.24
1996	day	-2.19	-4.11	4.35	7.19	14.15	22.70*	23.06	15.96	12.21	2.02	-3.63
	night	-4.16	-2.30									
	total	-4.65	-3.21									
1997	day	-4.40	-2.76									
	night											
	total											

* Incomplete Data

- Data not available

Table A13. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Crawford Co.)
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
	day											
1991	night											
	total											
	day		-	-	-	26.44	28.12	27.29	23.21	14.21	7.51	2.68
1992	night		-	-	-	26.23	28.02	27.39	23.07	14.12	7.44	2.73
	total		-	-	-	26.34	28.07	27.34	23.13	14.16	7.48	2.70
	day	2.22	1.17	4.21	12.85	23.29	32.88	32.07	23.36	15.60	7.11	2.17
1993	night	2.37	1.39	4.02	12.21	22.24	30.76	30.11	22.03	14.36	6.58	1.76
	total	2.30	1.28	4.12	12.53	22.77	31.82	31.09	22.70	14.98	6.85	1.96
	day	-3.60	-0.97	6.17	15.28	21.27	32.16	28.76	25.53	17.97	10.82	4.45
1994	night	-4.01	-1.49	4.75	13.55	18.87	29.89	26.99	23.66	16.43	9.97	3.98
	total	-3.80	-1.23	5.46	14.41	20.07	31.03	27.87	24.60	17.20	10.40	4.21
	day	0.80	-0.15	8.86	12.97	21.01	31.60	31.76	23.79	16.16	4.95	-1.26
1995	night	0.51	-0.87	7.33	11.39	18.87	29.48	30.18	22.32	15.17	4.45	-1.55
	total	0.65	-0.51	8.09	12.18	19.94	30.54	30.97	23.05	15.66	4.70	-1.40
	day	-3.05	-1.03	3.46	11.06	18.74	30.26	30.59*	-	16.46*	7.64	5.55
1996	night	-2.99	-1.24	2.43	9.79	17.06	28.34	28.60*	-	15.64*	6.99	5.22
	total	-3.02	-1.14	2.95	10.42	17.90	29.30	29.58*	-	16.05*	7.31	5.38
	day	1.84	5.92	11.95	18.13	21.46	32.76	28.91	26.14	18.87	7.57	4.99
1997	night	1.61	5.33	11.02	16.19	19.41	31.25	27.78	25.00	17.87	7.17	4.80
	total	1.73	5.63	11.48	17.16	20.44	32.01	28.34	25.57	18.37	7.37	4.90

* Incomplete Data

- Data not available

Table A13 AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Crawford Co.) Cont.
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
	6.00	7.95	10.63	19.45	27.92	29.04	32.44	30.40	25.54	16.20	9.10	4.36
1998	5.75	7.42	9.71	18.04	26.12	27.47	31.04	29.25	24.47	15.30	8.42	4.15
	5.87	7.69	10.17	18.75	27.02	28.25	31.74	29.83	25.01	15.75	8.76	4.25
	-2.79	1.61	4.43	15.23	23.39	30.51	32.92	26.72	22.71	14.36	9.49	2.71
1999	-2.89	1.38	3.73	14.11	22.01	29.30	31.57	26.06	21.91	13.53	9.01	2.53
	-2.84	1.49	4.08	14.67	22.70	29.91	32.24	26.39	22.31	13.94	9.25	2.62
	-	-	-	13.70	21.17	25.48	25.79	23.38	18.88	13.41	6.16	-1.86
2000	-	-	-	13.06	20.41	24.12	24.83	22.54	18.04	12.68	5.87	-1.74
	-	-	-	13.38	20.79	24.96	25.31	22.96	18.46	13.04	6.02	-1.80
	-5.99	-3.71	-1.90									
2001	-5.63	-3.62	-2.26									
	-5.81	-3.67	-2.01									

* Incomplete Data

- Data not available

Table A14. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Knox Co.)
(deg C)

YEAR		JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1991	day												2.65*
	night												2.09*
	total												2.37*
1992	day	1.11	3.48	7.14	14.55	22.78	26.62	29.13	28.00	23.92	15.14	8.10	3.21
	night	0.73	2.75	6.00	12.73	20.28	26.23	29.15	28.12	23.94	15.05	8.06	2.99
	total	0.92	3.12	6.57	13.64	21.53	26.44	29.14	28.06	23.93	15.10	8.08	3.10
1993	day	2.70	1.71	5.25	13.45	23.01	27.38	32.51	31.75	23.92	15.74	8.36	3.04
	night	2.59	1.59	5.09	13.14	22.55	26.77	32.04	31.51	23.56	15.46	8.14	3.06
	total	2.64	1.65	5.17	13.29	22.78	27.08	32.27	31.63	23.74	15.60	8.25	3.05
1994	day	-2.66	-0.10	6.47	15.05	20.62	29.11	31.19	28.53	24.52	17.41	11.02	5.09
	night	-2.69	-0.08	6.13	14.76	19.91	28.39	30.56	28.13	24.08	16.92	10.72	5.00
	total	-2.67	-0.09	6.30	14.90	20.26	28.75	30.88	28.33	24.30	17.16	10.87	5.04
1995	day	0.98	-0.15	8.93	13.36	20.00	27.93	31.39	-*	-*	-*	-*	-*
	night	1.08	-0.07	8.65	12.96	19.33	27.41	30.91	-*	-*	-*	-*	-*
	total	1.03	-0.11	8.79	13.16	19.66	27.67	31.15	-*	-*	-*	-*	-*
1996	day	-	-	-*	13.90	20.78	30.06	34.14	32.74	24.43	17.53	7.90	5.02
	night	-	-	-*	13.65	20.41	29.69	33.85	32.35	24.30	17.24	7.70	4.90
	total	-	-	-*	13.77	20.59	29.88	34.00	32.55	24.37	17.38	7.80	4.96
1997	day	0.33	2.94	7.33	12.86	16.03	25.98	31.67	27.22	22.32	14.28	4.91	1.14
	night	0.59	2.84	7.12	12.46	15.20	25.64	31.30	27.05	22.17	13.94	4.64	1.13
	total	0.46	2.89	7.22	12.66	15.61	25.81	31.48	27.14	22.24	14.11	4.78	1.13

* Incomplete Data

- Data not available

Table A14. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Knox Co.) Cont.
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
	2.37	6.05	8.14	14.31	22.70	25.26	31.72	30.92	25.66	14.24	6.62	3.73
1998	2.38	5.87	7.72	13.83	22.14	24.27	29.39	28.54	23.68	12.65	5.53	3.27
	2.37	5.96	7.93	14.07	22.42	24.77	30.56	29.73	24.67	13.44	6.08	3.50
	-1.48	1.29	3.50	12.55	19.59	26.51	30.83	27.87	23.31	12.57	7.20	-0.17
1999	-1.93	0.54	1.66	10.16	16.96	23.76	28.05	25.87	21.26	10.78	6.04	-0.70
	-1.70	0.91	2.58	11.35	18.28	25.14	29.44	26.87	22.29	11.67	6.62	-0.44
	-	-	-	10.43	18.78	24.81	26.24	26.03	20.42	13.68	3.95	-4.68
2000	-	-	-	8.55	16.57	22.60	24.26	24.33	18.74	12.42	3.55	-6.93
	-	-	-	9.48	17.67	23.71	25.25	25.18	19.58	13.05	3.75	-4.79
	-3.90											
2001	-4.30											
	-4.10											

* Incomplete Data

- Data not available

Table A15. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Licking Co.)
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
												4.49
1991												4.18
												4.34
	2.02	4.56	7.86	14.50	21.00	24.65	27.04	25.68	22.92	15.28	8.96	3.55
1992	1.92	4.31	7.48	13.67	19.88	24.79	27.49	26.34	23.39	15.62	9.12	3.58
	1.97	4.43	7.67	14.09	20.44	24.72	27.27	26.01	23.16	15.45	9.04	3.57
	3.30	1.88	5.64	13.69	22.30	26.46	30.83	29.67	23.18	15.60	9.15	3.42
1993	3.51	2.07	5.26	12.99	21.30	25.45	29.80	28.86	22.62	15.20	8.81	3.31
	3.40	1.97	5.45	13.34	21.80	25.91	30.31	29.26	22.90	15.40	8.98	3.37
	-2.54	1.32	6.89	15.47	20.29	28.10	29.39	27.27	23.56	17.42	12.05	6.23
1994	-2.72	1.17	6.35	14.82	19.20	27.14	28.33	26.34	22.75	16.79	11.67	6.04
	-2.63	1.24	6.62	15.15	19.74	27.62	28.86	26.80	23.16	17.10	11.86	6.14
	1.61	1.07	10.01	14.41	20.46	27.36	30.02	30.47	23.05	17.12	6.52	1.20
1995	1.60	0.92	9.53	13.73	19.53	26.51	29.22	29.92	22.60	16.85	6.44	1.23
	1.60	1.00	9.77	14.07	20.00	26.94	29.62	30.19	22.83	16.98	6.48	1.22
	0.01	1.68	6.12	13.77	19.95	26.82	29.29	29.02	22.90	16.25	6.30	5.04
1996	0.14	1.68	5.87	13.24	19.24	25.90	28.65	28.31	22.42	15.93	6.13	4.89
	0.08	1.68	6.00	13.50	19.60	26.35	28.97	28.66	22.65	16.09	6.21	4.96
	0.59	4.16	9.07	14.00	18.58	-*	-	26.45	22.95	17.15	7.49	4.10
1997	0.74	3.87	8.67	13.27	17.66	-*	-	25.82	22.36	16.69	7.22	4.07
	0.66	4.01	8.87	13.64	18.12	-*	-	26.14	22.65	16.92	7.36	4.08

* Incomplete Data

- Data not available

Table A16 AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Lucas Co.)
(deg C)

YEAR		JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
	day												
1991	night												
	total												
	day					25.29	26.80	26.10	22.55			-	-*
1992	night					24.17	26.03	25.53	21.80			-	-*
	total					24.74	26.41	25.67	22.18			-	-*
	day	1.62	0.51	3.81	12.42	21.39	24.88	28.74	20.92	14.47	7.66	7.66	2.52
1993	night	1.36	0.11	2.92	12.20	21.13	24.54	28.36	20.79	14.28	7.40	7.40	2.40
	total	1.49	0.31	3.70	12.31	21.26	24.71	28.55	20.85	14.37	7.53	7.53	2.46
	day	-3.82	-1.05	5.55	14.41	20.35	27.77	25.73	23.50	16.24	10.29	10.29	4.50
1994	night	-4.09	-1.56	5.44	14.22	20.36	27.77	25.60	23.48	16.19	10.17	10.17	4.38
	total	-3.95	-1.31	5.50	14.32	20.35	27.71	25.66	23.49	16.22	10.23	10.23	4.43
	day	0.86	-0.05	7.38	11.18	19.44	26.52	29.74	22.07	16.05	5.55	5.55	0.34
1995	night	0.61	-0.30	7.16	11.18	19.19	26.30	29.18	21.59	15.76	5.37	5.37	0.12
	total	0.73	-0.17	7.27	11.13	19.31	26.41	29.46	21.83	15.90	5.46	5.46	0.23
	day	-1.63	-0.65	5.08	12.59	19.32	26.30	26.99	22.50	12.22	7.66	7.66	
1996	night	-1.74	-0.60	4.48	11.78	18.21	24.89	25.27	21.65	12.07	7.41	7.41	
	total	-1.69	-0.62	4.78	12.18	18.76	25.59	26.13	22.08	12.14	7.54	7.54	
	day	-	-	-	-	-	-	-	-	-	-	-	-
1997	night	-	-	-	-	-	-	-	-	-	-	-	-
	total	-	-	-	-	-	-	-	-	-	-	-	-

* Incomplete Data

- Data not available

Table A17. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Wood 2 Co.)
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1991												
	day											
	night											
	total											
	day		-			25.90	27.12	26.60	22.92	13.92	7.11	2.34
1992			-			25.90	27.06	26.46	22.66	13.82	6.91	2.38
	night		-			25.90	27.09	26.53	22.79	13.87	7.01	2.36
	total											
	day	1.10	0.20	3.52	13.21	23.40	32.49	30.98	22.05	14.54	6.28	1.24
1993		0.97	0.03	2.62	11.49	21.17	30.31	29.03	20.73	13.34	5.70	0.90
	night	1.03	0.11	3.07	12.35	22.28	31.40	30.01	21.39	13.94	5.99	1.06
	total											
	day	-5.50	-2.46	4.59	14.14	22.17	31.99	27.98	26.11	17.90	10.52	4.25
1994		-5.58	-3.01	3.22	12.52	19.76	32.46	28.33	26.51	18.11	10.68	4.36
	night	-5.54	-2.74	3.90	13.33	20.97	32.22	28.16	26.31	18.01	10.60	4.31
	total											
	day	0.48	-0.29	8.04	12.46	21.27						
1995		0.65	-0.06	8.29	12.62	21.37						
	night	0.57	-0.17	8.16	12.54	21.32						
	total											
	day											
1996												
	night											
	total											
	day											
1997												
	night											
	total											

* Incomplete Data

- Data not available

Table A18. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Wood 8 Co.)
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1991	day											
	night											
	total											
	day					25.43	26.64	26.12	22.19	22.19	-	22.19
1992	night					25.86	26.95	26.44	22.41	22.41	-	22.41
	total					25.65	26.80	26.28	22.30	22.30	-	22.30
	day	0.38	-0.91	2.21	11.91	25.34	31.45	30.52	21.82	14.98	6.86	17.91
1993	night	0.41	-0.94	1.69	10.79	24.11	30.04	29.32	21.29	14.78	6.77	17.71
	total	0.40	-0.93	1.95	11.35	24.72	30.74	29.92	21.56	14.88	6.81	17.75
	day	-*	-	-	-	26.25	31.71	27.88	25.90	17.61	10.39	4.26
1994	night	-*	-	-	-	25.78	31.33	27.56	25.50	17.23	10.24	4.17
	total	-*	-	-	-	26.02	31.52	27.72	25.70	17.42	10.31	4.21
	day	0.48	-0.76	7.65	11.84	28.61	31.87	32.04	23.97	16.35	5.04	-0.47
1995	night	0.41	-0.92	7.29	11.33	28.17	31.57	31.86	23.88	16.26	4.97	-0.50
	total	0.45	-0.84	7.47	11.58	28.39	31.72	31.95	23.93	16.30	5.01	-0.48
	day	-2.10	-1.35	3.80	11.49	26.74	29.98	29.64	22.89	14.91	4.22	0.81
1996	night	-2.04	-1.34	3.50	11.18	26.41	29.68	29.33	22.72	14.78	4.08	0.69
	total	-2.07	-1.34	3.65	11.33	26.57	29.83	29.49	22.80	14.84	4.15	0.75
	day	-2.55	-0.26	4.92	12.08	25.80	29.00	25.17	21.60	14.78	4.17	0.84
1997	night	-2.58	-0.42	4.74	11.60	25.34	29.05	25.16	21.58	14.68	4.18	0.90
	total	-2.56	-0.34	4.83	11.84	25.57	29.02	25.16	21.59	14.73	4.17	0.87

* Incomplete Data

- Data not available

Table A18. AVERAGE MONTHLY ASPHALT CONCRETE TEMPERATURE (Wood 8 Co.) Cont.
(deg C)

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
	0.89	2.44	5.77	13.77	22.91	26.50	29.71	27.61	24.18	14.74	7.29	3.14
1998	0.85	2.45	5.66	13.55	22.72	26.33	29.53	27.53	24.21	14.69	7.14	3.21
	0.87	2.44	5.72	13.66	22.82	26.41	29.62	27.57	24.20	14.71	7.21	3.18
	-3.75	1.26	3.71	12.95	20.92	27.59	30.62	25.82	21.93	12.52	7.52	0.28
1999	-3.82	1.24	3.54	12.55	20.34	27.16	30.29	25.68	21.75	12.29	7.52	0.24
	-3.79	1.25	3.62	12.75	20.63	27.37	30.45	25.75	21.86	12.41	7.52	0.26
	-	-	-	11.11	18.99	23.82	25.27	24.19	19.38	12.85	4.28	-5.45
2000	-	-	-	10.82	18.68	23.56	25.26	24.17	19.33	12.77	4.27	-5.46
	-	-	-	10.96	18.84	23.69	25.27	24.18	19.36	12.81	4.27	-5.46
	-4.88	-1.90	2.08									
2001	-4.87	-1.99	1.83									
	-4.87	-1.94	1.95									

* Incomplete Data

- Data not available

ADAMS Co.

$$P = 6.0758 + 0.8880 A + 0.0044 A^2$$




Figure A1 AIR TEMPERATURE vs. AVERAGE ASPHALT CONCRETE TEMPERATURE (Adams Co.)

ATHENS Co.




Figure A2 AIR TEMPERATURE vs. AVERAGE ASPHALT CONCRETE TEMPERATURE (Athens Co.)

COLUMBIANA Co.




Figure A3 AIR TEMPERATURE vs. AVERAGE ASPHALT CONCRETE TEMPERATURE (Columbiana Co.)

CRAWFORD Co.




Figure A4 AIR TEMPERATURE vs. AVERAGE ASPHALT CONCRETE TEMPERATURE (Crawford Co.)

KNOX Co.




Figure A5 AIR TEMPERATURE vs. AVERAGE ASPHALT CONCRETE TEMPERATURE (Knox Co.)

LICKING Co.

$$P = 5.2147 + 0.8447 A + 0.0037 A^2$$




Figure A6 AIR TEMPERATURE vs. AVERAGE ASPHALT CONCRETE TEMPERATURE (Licking Co.)

LUCAS Co.

$$P = 5.1270 + 0.9145 A + 0.0014 A^2$$




Figure A7 AIR TEMPERATURE vs. AVERAGE ASPHALT CONCRETE TEMPERATURE (Lucas Co.)

WOOD2 Co.

$$P = 4.0461 + 0.9483 A + 0.0051 A^2$$




Figure A8 AIR TEMPERATURE vs. AVERAGE ASPHALT CONCRETE TEMPERATURE (Wood2 Co.)

WOOD 8 Co.

$$P = 3.5786 + 0.9605 A + 0.0024 A^2$$




Figure A9 AIR TEMPERATURE vs. AVERAGE ASPHALT CONCRETE TEMPERATURE (Wood8 Co.)

Appendix B

DEPTH OF FROST PENETRATION AND NUMBER OF FREEZE-THAW
CYCLES SUMMARY

Table B1. Frost Cycles and Frost Depth (Adams Co.)

SEASON	No. OF FROST CYCLES	MAX. FROST DEPTH(cm)
1991-1992		
1992-1993		
1993-1994	_*	_*
1994-1995	_*	_*
1995-1996	4	-67.06 (-2.20')
1996-1997	3	-61.26 (-2.01')
1997-1998	0	In AC
1998-1999	3	-44.5 (-1.46')
1999-2000	-	-
2000-2001	9	-48.46 (-1.59')
AVERAGE	4	-50.29 (-1.65')

* Incomplete Data

- Data not available

Table B2. Frost Cycles and Frost Depth (Athens Co.)

SEASON	No. OF FROST CYCLES	MAX. FROST DEPTH(cm)
1991-1992	5	-40.54 (-1.33')
1992-1993	2	-33.22 (-1.09')
1993-1994	6*	-46.33* (-1.52')
1994-1995	8	-55.17 (-1.81')
1995-1996	4	-66.75 (-2.19')
1996-1997	-*	In AC
1997-1998	0	In AC
1998-1999	5	-61.87 (-2.03')
1999-2000	-	-
2000-2001	*	*
AVERAGE	4	-45.41 (-1.49')

* Incomplete Data

- Data not available

Table B3. Frost Cycles and Frost Depth (Crawford Co.)

SEASON	No. OF FROST CYCLES	MAX. FROST DEPTH(cm)
1991-1992		
1992-1993	9	-46.33 (-1.52')
1993-1994	4	-95.71 (-3.14')
1994-1995	15	-73.76 (-2.42')
1995-1996	14	-85.04 (-2.79')
1996-1997	5	-70.41 (-2.31')
1997-1998	0	0
1998-1999	10	-100.28 (-3.29')
1999-2000	-	-
2000-2001	7	-92.96 (-3.05')
AVERAGE	6	-70.71 (-2.32')

* Incomplete Data

- Data not available

Table B4. Frost Cycles and Frost Depth (Knox Co.)

SEASON	No. OF FROST CYCLES	MAX. FROST DEPTH(cm)
1991-1992	3	-58.83 (-1.93')
1992-1993	7	-43.59 (-1.43')
1993-1994	11	-103.94 (-3.41')
1994-1995	3	-96.01 (-3.15')
1995-1996	-*	-*
1996-1997	2	-98.15 (-3.22')
1997-1998	0	In AC
1998-1999	13	-105.77 (-3.47')
1999-2000	-	-
2000-2001	17	-56.39 (-1.85')
AVERAGE	7	-74.07 (-2.43')

* Incomplete Data

- Data not available

Table B5. Frost Cycles and Frost Depth (Licking Co.)

SEASON	No. OF FROST CYCLES	MAX. FROST DEPTH(cm)
1991-1992	5	-58.52 (-1.92')
1992-1993	5	-58.83 (-1.93')
1993-1994	9	-84.43 (-2.77')
1994-1995	5	-71.63 (-2.35')
1995-1996	13	-77.42 (-2.54')
1996-1997	5	-71.93 (-2.36')
1997-1998	0	In AC
1998-1999	6	-71.02 (-2.33')
1999-2000	-	-
2000-2001	-	-
AVERAGE	6	-65.53 (-2.15')

* Incomplete Data

- Data not available

Table B6. Frost Cycles and Frost Depth (Lucas Co.)

SEASON	No. OF FROST CYCLES	MAX. FROST DEPTH(cm)
1991-1992		
1992-1993	17	-57.61 (-1.89')
1993-1994	2	-113.08 (-3.71')
1994-1995	15	-65.23 (-2.14')
1995-1996	14	-89.00 (-2.92')
1996-1997	-	-
1997-1998		
1998-1999		
1999-2000		
2000-2001		
AVERAGE	12	-81.08 (-2.66')

* Incomplete Data

- Data not available

Table B7. Frost Cycles and Frost Depth (Wood 2 Co.)

SEASON	No. OF FROST CYCLES	MAX. FROST DEPTH(cm)
1991-1992		
1992-1993	34	-54.86 (-1.80')
1993-1994	7	120.09 (-3.94')
1994-1995	13	-52.12 (-1.71')
1995-1996		
1996-1997		
AVERAGE	18	-75.59 (-2.48')

* Incomplete Data

- Data not available

Table B8. Frost Cycles and Frost Depth (Wood 8 Co.)

SEASON	No. OF FROST CYCLES	MAX. FROST DEPTH(cm)
1991-1992		
1992-1993	18	-66.14 (-2.17')
1993-1994	2	-74.37* (-2.44')
1994-1995	7	-92.35 (-3.03')
1995-1996	5	-79.86 (-2.62')
1996-1997	3	-75.29 (-2.47')
1997-1998	1	-39.93 (-1.31')
1998-1999	5	-76.50 (-2.51')
1999-2000	-	-
2000-2001	*	*
AVERAGE	6	-71.93 (-2.36')

* Incomplete Data

- Data not available

THIS PAGE LEFT INTENTIONALLY BLANK

Appendix C

**MONTHLY AND SEASONAL RAINFALL AND DEGREE OF SATURATION
SUMMARIES**

Table C1 SEASONAL RAINFALL (Adams Co.)
(cm)

YEAR	SPRING	SUMMER	FALL	WINTER
1991				
1992				
1993				
1994	29.08	4.88*	-	-
1995	1.35*	15.75	16.56	25.91
1996	43.66	13.06	18.72	34.54
1997	17.60	16.84	14.07	17.09
1998	33.43	4.47	17.32	22.05
1999	10.74	15.27	0.81*	-
2000	3.10*	3.96*	16.31	22.86
2001				

* Incomplete Data

- Data not available

Table C2 SEASONAL RAINFALL (Athens Co.)
(cm)

YEAR	SPRING	SUMMER	FALL	WINTER
1991				18.26
1992	30.81	29.08	21.29	23.06
1993	24.87	16.59	25.60	5.92*
1994	7.29*	38.13	17.91	23.39
1995	31.32	32.21	24.92	29.18
1996	46.56	-	-	35.76
1997	25.65	26.59	12.57	27.23
1998	33.68	7.26	17.55	29.85
1999	14.73	22.68*	-	-
2000	17.45*	16.89	19.76	15.24
2001				

* Incomplete Data

- Data not available

Table C3 SEASONAL RAINFALL (Columbiana Co.)
(cm)

YEAR	SPRING	SUMMER	FALL	WINTER
1991				
1992				
1993				
1994			14.48*	11.51
1995	29.92	3.00*		
1996				
1997				

* Incomplete Data

- Data not available

Table C4 SEASONAL RAINFALL (Crawford Co.)
(cm)

YEAR	SPRING	SUMMER	FALL	WINTER
1991				
1992	8.51*	41.17	25.22	22.45
1993	26.37	11.73	34.16	10.29
1994	23.55	20.14	20.19	19.23
1995	25.81	31.01	24.43	19.05
1996	40.49	17.22*	25.32*	5.36
1997	31.24	30.99	11.25	21.89
1998	31.95	38.07	10.95	17.35
1999	21.34	17.65	17.22	*
2000	32.54*	28.58	21.13	11.13
2001				

* Incomplete Data

- Data not available

Table C5 SEASONAL RAINFALL (Knox Co.)
(cm)

YEAR	SPRING	SUMMER	FALL	WINTER
1991				15.21
1992	21.28*	45.80	23.90	20.12
1993	24.54	23.67	21.67	14.00
1994	26.75	25.96	17.27	14.83
1995	32.28	26.03*	-	-
1996	42.62	19.46	20.09	22.23
1997	32.77	15.75	13.03	19.30
1998	30.63	2.57	15.95	21.29
1999	19.05	8.94	16.05	*
2000	30.91*	15.85	23.93	7.47
2001				

* Incomplete Data

- Data not available

Table C6 SEASONAL RAINFALL (Licking Co.)
(cm)

YEAR	SPRING	SUMMER	FALL	WINTER
1991			2.31*	16.10
1992	14.66	-*	17.93	22.61
1993	28.58	11.51	17.93	10.59
1994	20.70	23.67	12.04	18.97
1995	27.66	18.69	22.02	27.46
1996	50.55	25.27	-	10.16
1997	22.58*	37.26*	14.71	18.69
1998	35.94	18.64*	14.81*	*
1999	*			
2000				
2001				

* Incomplete Data

- Data not available

Table C7 SEASONAL RAINFALL (Lucas Co.)
(cm)

YEAR	SPRING	SUMMER	FALL	WINTER
1991				
1992	3.99*	28.80*	13.34*	19.30
1993	20.98	18.11	7.85	9.17
1994	4.72	17.75	16.71	10.77
1995	22.50	19.53	14.05	-
1996	-	-	28.80	-
1997	15.95	24.49	-	
1998				
1999				
2000				
2001				

* Incomplete Data

- Data not available

Table C8 SEASONAL RAINFALL (Wood 2 Co.)
(cm)

YEAR	SPRING	SUMMER	FALL	WINTER
1991				
1992	4.27*	36.50	24.08	21.82
1993	26.37	12.09	17.19*	-
1994	-	-	15.62	11.30
1995	19.51			
1996				
1997				

* Incomplete Data

- Data not available

Table C9 SEASONAL RAINFALL (Wood 8 Co.)
(cm)

YEAR	SPRING	SUMMER	FALL	WINTER
1991				
1992	3.53*	38.15	3.91*	18.57
1993	23.72	16.46	5.31*	-
1994	1.83*	20.19	15.54	11.99
1995	22.63	22.58	12.22	7.87
1996	*	*	23.90	22.58
1997	25.12	1.85*	-	-
1998	2.79*	19.00	6.96	15.80
1999	13.94	6.20*	14.94	*
2000	27.81*	26.01	15.37	9.91
2001				

* Incomplete Data

- Data not available

Table C10 MONTHLY RAINFALL (Adams Co.)
(cm)

YEAR	JAN.	FEB.	MAR.	APR.	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1991												
1992												
1993												
1994			3.81*	17.20	5.46	6.71	0.79*	-	-	-	-	-
1995	-	-	-	-	-	2.26*	3.28	8.86	2.77	6.15	5.11	5.69
1996	12.42	6.81	8.84	12.60	27.53	1.12	10.16	2.69	0.05	3.84	9.47	7.29
1997	6.53	4.70	25.04	2.77	10.74	4.37	3.51	7.72	1.63	3.43	7.09	3.94
1998	7.24	4.39	4.95	17.22	6.35	9.27	0.43	0.58	5.69	7.24	4.70	5.97
1999	7.92	6.93	4.11	6.02	2.69	3.18	4.95	8.86	0.23*	0.15*	-	0.66*
2000	-	-	-	0.53*	0.81	4.65	1.07	0.0*	0.0*	0.89*	6.58	8.84
2001	14.83	5.33	11.00									

* Incomplete Data

- Data not available

Table C11 MONTHLY RAINFALL (Athens Co.)
(cm)

YEAR	JAN.	FEB.	MAR.	APR.	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1991												
1992	3.40	4.55	10.85	7.34	11.71	8.92	19.25	6.43	5.99	3.73	8.79	6.27
1993	8.20	5.94	12.01	7.62	8.03	9.70	4.52	2.95	12.75	9.78	9.80	4.55
1994	5.38*	-	-	-	3.43*	9.78	16.13	13.61	3.45	4.11	5.82	7.19
1995	12.40	5.92	5.66	6.35	20.04	12.98	7.49	10.69	5.84	11.02	6.43	7.21
1996	11.18	7.14	12.85	10.80	17.53	19.30	-	-	-	-	-	-
1997	7.29	5.31	24.61	3.86	12.83	5.79	6.30	15.65	3.58	3.53	7.26	3.78
1998	10.06	10.08	6.60	17.35	10.72	4.24	0.69	4.14	4.45	6.43	6.10	4.80
1999	12.78	8.10	6.99	5.64	6.07	3.89	17.63	4.19*	-	-	-	-
2000	-	-	-	6.02	6.96	6.50	4.19	5.99	9.45	3.33	3.71	8.05
2001	5.18	3.35	9.45									

* Incomplete Data

- Data not available

Table C12 MONTHLY RAINFALL (Columbiana Co.)
(cm)

YEAR	JAN.	FEB.	MAR.	APR.	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1991												
1992												
1993												
1994									-	-	7.98	6.58
1995	4.62	3.56	3.94	7.67	15.67	5.64	2.82*	.18*	0.00*			
1996												

* Incomplete Data

- Data not available

Table C13 MONTHLY RAINFALL (Crawford Co.)
(cm)

YEAR	JAN.	FEB.	MAR.	APR.	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1991												
1992						10.41*	23.19	10.64	7.01	5.66	15.62	3.81
1993	11.10	4.27	8.71	11.84	4.78	7.70	5.03	2.39	8.56	8.81	14.78	5.33
1994	6.35	1.70	4.52	12.37	5.00	11.15	0.86	7.21	6.65	1.47	9.27	8.15
1995	8.79	4.50	6.12	13.89	8.28	10.82	11.79	8.66	2.92	12.29	9.83	2.03
1996	8.36	5.72	7.82	15.06	12.55	12.27	13.11	1.85*	-	4.78*	14.25	7.98
1997	2.97	0.58	2.36	4.32	18.57	10.67	11.53	8.18	7.11	2.41	5.11	6.10
1998	5.56	8.33	7.29	12.07	8.18	28.17	9.55	9.40	1.80	5.72	3.15	3.99
1999	4.78	5.84	3.71	12.01	5.46	5.33	12.01	3.23	1.73	2.67	5.69	8.61
2000	-	-	-	6.76	16.69	12.32	9.04	7.47	14.83	4.72	4.52	5.89
2001	3.25	4.75	3.28									

* Incomplete Data

- Data not available

Table C14 MONTHLY RAINFALL (Knox Co.)
(cm)

YEAR	JAN.	FEB.	MAR.	APR.	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1991												1.60*
1992	3.84	2.79	9.55	6.20	8.94	5.51*	24.51	14.83	11.53	3.56	11.63	2.74
1993	10.03	2.39	9.96	10.06	5.18	12.80	12.55	1.42	6.17	4.24	8.66	5.49
1994	7.59	3.30	5.51	10.95	5.13	14.68	8.71	9.83	3.20	1.83	7.29	6.17
1995	9.86	1.85	3.35	8.74	14.35	16.59	11.58	6.60*	-	-	-	-
1996	-	-	2.13*	15.34	16.31	9.86	7.47	4.52	7.14	4.11	7.14	10.44
1997	5.44	4.83	11.07	3.78	20.90	7.34	12.12	2.84	0.15	3.68	6.10	5.46
1998	6.73	5.94	6.35	11.23	10.36	7.65	0.48	0.74	0.89	10.01	4.39	5.59
1999	7.44	5.64	4.06	11.25	6.38	1.83	7.62	0.89	0.03	3.28	6.20	6.81
2000	-	-	-	8.99	16.87	6.07	4.65	7.19	9.53	5.79	5.16	6.48
2001	1.80	3.12	2.54									

* Incomplete Data
- Data not available

Table C15 MONTHLY RAINFALL (Licking Co.)
(cm)

YEAR	JAN.	FEB.	MAR.	APR.	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1991												4.78*
1992	3.94	2.13	10.52	8.10	1.83	2.34	-*	8.86	5.56	4.06	9.65	4.37
1993	8.92	3.86	12.12	10.85	7.32	11.28	5.26	1.22	0.05	2.01	10.72	5.21
1994	5.23	1.57	6.43	12.57	4.11	9.12	13.00	2.90	0.08	1.14	6.45	4.47
1995	10.85	3.76	4.57	8.69	12.17	9.27	5.97	7.67	2.79	11.68	6.60	3.66
1996	10.49	7.26	11.84	17.73	18.26	12.57	14.76	2.77	11.40	4.52	-	2.97*
1997	4.14	2.77	2.67	4.14	12.47	3.58*	10.24*	22.76	4.37	3.99	7.75	4.95
1998	5.26	7.09	5.99	13.94	11.07	16.94	5.67*	3.20*	9.04	7.54	-	-
1999	-	-	-	-	-	-	-	-	-	-	-	-
2000	-	-	-	-	-	-	-	-	-	-	-	-
2001												

* Incomplete Data

- Data not available

Table C16 MONTHLY RAINFALL (Lucas Co.)
(cm)

YEAR	JAN.	FEB.	MAR.	APR.	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1991												
1992						4.14*	18.54	4.04	11.13	8.26*	-	3.78
1993	8.26	1.45	9.98	7.80	2.49	8.99	3.86	4.39	7.70	0.53	4.45	2.57
1994	3.99	1.32	5.28	0.03*	0.08*	8.84	6.53	5.31	2.39	0.18	7.39	7.75
1995	6.12	0.56	3.86	9.58	6.86	12.75	5.97	4.09	3.18	11.61	1.57	-
1996	-	-	-	-	-	-	-	-	6.55	12.45	8.15	5.08
1997	-	-	1.50	3.28	11.15	2.29	5.13	7.77	9.58	-	-	-
1998												
1999												
2000												
2001												

* Incomplete Data

- Data not available

Table C17 MONTHLY RAINFALL (Wood 2 Co.)
(cm)

YEAR	JAN.	FEB.	MAR.	APR.	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1991												
1992						4.57	20.29	7.26	13.84	5.08	11.58	9.88
1993	6.73	0.91	9.55	10.49	4.27	10.21	5.61	3.48	1.88	4.50	-	12.17*
1994	-	-	-	-	-	-	-	-	0.86	2.34	7.75	4.95
1995	5.66	3.23	3.20	9.93	8.23	0.28*						
1996												

* Incomplete Data

- Data not available

Table C18 MONTHLY RAINFALL (Wood & Co.)
(cm)

YEAR	JAN.	FEB.	MAR.	APR.	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1991												
1992						3.81	19.53	6.60	16.48	5.18*	-	7.24*
1993	7.59	1.52	5.13	9.58	3.89	9.68	5.33	1.70	11.18	0.15	1.04	0.03*
1994	-	-	-	-	0.66*	8.36	2.72	10.21	0.89	2.95	5.99	6.05
1995	5.28	3.33	3.66	10.77	8.23	13.94	5.64	5.00	1.65	4.37	7.01	0.79
1996	5.28	2.01	-	-	-	-	6.10	-	-	4.09	7.06	7.01
1997	5.33	9.86	7.80	3.33	13.67	8.20*	-	-	-	-	-	-
1998	-	-	-	-	-	5.56	7.24	7.04	1.63	3.73	2.74	3.58
1999	7.67	3.76	2.57	8.59	5.36	-	-	4.57	4.80	4.60	3.58	3.53
2000	-	-	-	7.95	12.47	10.44	12.07	5.77	8.38	3.40	2.62	6.10
2001	2.41	5.44	2.06									

* Incomplete Data
Data not available

Table C19 Monthly Degree of Saturation-Adams Co.

Month	Sr1	Sr2	Sr3	Sr4	Month	Sr1	Sr2	Sr3	Sr4
Jun-95	99.97		98.90	100.00	May-98	100.00		97.14	
Jul-95	99.77		97.08	100.00	Jun-98	100.00		96.21	
Aug-95	98.30		95.78	99.55	Jul-98	100.00		96.71	
Sep-95	98.41		97.51	100.00	Aug-98	99.95		96.34	
Oct-95	98.47		98.64	99.94	Sep-98	99.55		95.43	
Nov-95	99.46		98.88	100.00	Oct-98	99.80		97.00	
Dec-95	98.82		98.85	99.36	Nov-98	99.97		99.57	
Jan-96	98.87		98.89	99.60	Dec-98	100.00		100.00	
Feb-96	98.28		98.15	98.67	Jan-99	99.56		99.43	
Mar-96	98.13		98.17	98.80	Feb-99	99.72		99.99	
Apr-96	99.38		99.76	99.86	Mar-99	99.20		99.85	
May-96	98.81		99.50	99.98	Apr-99	99.45		99.95	
Jun-96					May-99	99.79		100.00	
Jul-96					Jun-99	99.94		99.80	
Aug-96					Jul-99	99.84		99.45	
Sep-96					Aug-99	99.87		99.83	
Oct-96	99.78		99.41	97.32	Sep-99	99.91			
Nov-96	99.37		98.83	97.05	Oct-99	99.96			
Dec-96	99.28		98.51	96.92	Nov-99	99.99			
Jan-97	98.79		97.78	94.46	Dec-99	99.89			
Feb-97	97.99		97.60	96.27	Jan-00				
Mar-97	98.42		97.61	95.89	Feb-00				
Apr-97	99.51		98.25	96.70	Mar-00				
May-97	99.00		97.53	92.06	Apr-00	98.94			
Jun-97	98.57		97.37		May-00	99.12			
Jul-97	99.79		97.08	77.08	Jun-00	99.00			
Aug-97	99.80		96.62	81.22	Jul-00	97.62			
Sep-97	100.00		97.97	87.38	Aug-00	98.60			
Oct-97	100.00		98.36	89.76	Sep-00	98.16			
Nov-97	100.00		97.80	91.52	Oct-00	98.53			
Dec-97	100.00		96.35	92.25	Nov-00	99.76			
Jan-98	99.99		96.01	91.88	Dec-00	99.32			
Feb-98	100.00		95.99	92.09	Jan-01	97.88			
Mar-98	100.00		96.85	91.89	Feb-01	97.45			
Apr-98	100.00		96.83		Mar-01	96.61			

Table C20 Monthly Degree of Saturation-Athens Co.

Month	Sr1	Sr2	Sr3	Sr4	Month	Sr1	Sr2	Sr3	Sr4
Dec-91	97.79	98.55	98.84	98.95	Aug-96				
Jan-92	98.58	99.00	99.44	99.50	Sep-96				
Feb-92	98.56	99.00	99.39	99.58	Oct-96				
Mar-92	98.42	98.83	99.11	99.40	Nov-96				
Apr-92	98.61	98.98	99.25	99.48	Dec-96	99.07	99.71	98.63	
May-92	98.76	99.19	99.63	99.69	Jan-97	96.54	99.80	95.73	
Jun-92	99.31	99.19	98.81	98.19	Feb-97	94.98	99.85	95.18	
Jul-92	99.45	99.16	98.75	96.97	Mar-97				
Aug-92	99.75	99.60	99.91	99.25	Apr-97				
Sep-92	98.33	97.75	100.00	99.52	May-97				
Oct-92	98.80	98.39	100.00	99.99	Jun-97				
Nov-92	99.71	99.38	100.00	99.96	Jul-97		96.45		
Dec-92	99.10	98.78	100.00	99.22	Aug-97		97.34		
Jan-93	98.72	98.35	99.81	98.56	Sep-97		97.56		
Feb-93	98.88	98.51	99.94	98.41	Oct-97		97.99		
Mar-93	99.53	99.14	100.00	99.11	Nov-97		97.92		
Apr-93	99.36	98.85	100.00	99.45	Dec-97		97.43		
May-93	98.58	97.85	100.00	99.99	Jan-98		98.82		
Jun-93	97.26	96.27	99.80	99.61	Feb-98		98.83		
Jul-93	96.54	95.49	99.84	99.50	Mar-98		98.63		
Aug-93	96.23	95.17	99.99	99.80	Apr-98		97.86		
Sep-93	96.96	96.19	100.00	100.00	May-98		97.66		
Oct-93	97.89	97.46	100.00	99.99	Jun-98		98.31		
Nov-93	98.42	98.17	100.00	99.95	Jul-98		97.76		
Dec-93	98.74	98.54	99.93	99.46	Aug-98		97.62		
Jan-94	99.07	98.97	99.73	99.26	Sep-98		97.90		
Feb-94					Oct-98		99.01		
Mar-94					Nov-98		97.72		
Apr-94					Dec-98		97.89		
May-94	97.76	97.25	98.69		Jan-99		96.58		
Jun-94	97.69	97.12	98.99		Feb-99		98.28		
Jul-94	97.93	97.09	99.56		Mar-99		98.13		
Aug-94	98.00	97.12	99.96		Apr-99		93.83		
Sep-94	98.06	97.31	99.99		May-99		92.30		
Oct-94	99.13	98.46	100.00		Jun-99		92.09		
Nov-94	100.00	99.94	100.00		Jul-99		93.31		
Dec-94	99.82	99.67	100.00		Aug-99		92.79		
Jan-95	99.99	99.97	99.99		Sep-99				
Feb-95	99.98	99.95	99.40		Oct-99				
Mar-95	99.94	99.97	100.00		Nov-99				
Apr-95	99.35	99.88	100.00		Dec-99				
May-95	98.52	99.94	100.00		Jan-00				
Jun-95	98.34	99.99	100.00		Feb-00				
Jul-95	98.33	99.99	100.00		Mar-00				
Aug-95	99.62	99.58	100.00		Apr-00		93.47		
Sep-95	99.21	98.83	100.00		May-00		96.48		
Oct-95	100.00	99.92	100.00		Jun-00		97.67		
Nov-95	100.00	100.00	100.00		Jul-00		96.30		
Dec-95	99.74	99.25	98.29		Aug-00		96.57		
Jan-96	98.98	99.30	94.63		Sep-00		96.62		
Feb-96	99.42	99.32	96.06		Oct-00		98.31		
Mar-96	98.99	99.34	96.94		Nov-00		98.28		
Apr-96	100.00	99.99	99.69		Dec-00		96.37		
May-96	100.00	99.92	100.00		Jan-01		95.34		
Jun-96	100.00	100.00	100.00		Feb-01		98.90		
Jul-96	100.00	100.00	100.00		Mar-01		99.58		

Table C21 Monthly Degree of Saturation-Columbiana Co.

Month	Sr1	Sr2	Sr3	Sr4
Nov-94	100.00	99.98	99.10	98.93
Dec-94	99.28	99.18	97.65	97.36
Jan-95	97.59	96.27	96.83	96.85
Feb-95	96.43	95.96	94.83	91.10
Mar-95	98.50	98.37	99.18	99.26
Apr-95	99.92	99.84	99.93	99.97
May-95	99.87	99.40	99.83	99.95
Jun-95	99.96	98.90	99.97	100.00
Jul-95	100.00	99.03	99.85	100.00
Aug-95	100.00	99.30	99.86	100.00
Sep-95	99.97	99.29	99.64	99.99
Oct-95	99.94	99.46	99.76	99.99
Nov-95	99.61	99.00	97.60	98.32
Dec-95	97.97	96.84	94.79	95.96
Jan-96	95.17	95.25	91.08	94.15
Feb-96	93.58	93.24	90.78	93.03

Table C22 Monthly Degree of Saturation-Crawford Co.

Month	Sr1	Sr2	Sr3	Sr4	Month	Sr1	Sr2	Sr3	Sr4
Jun-92	98.21	97.47	99.76	94.72	Jul-96	100.00	100.00	100.00	100.00
Jul-92	98.49	98.24	99.90	95.09	Aug-96	100.00	100.00	100.00	100.00
Aug-92	98.84	98.49	99.79	95.91	Sep-96				
Sep-92	99.17	98.84	99.86	97.29	Oct-96	99.98	100.00	100.00	99.99
Oct-92	99.30	98.99	99.99	98.71	Nov-96	99.87	99.94	99.73	99.91
Nov-92	99.38	99.05	99.99	99.21	Dec-96	99.25	99.59	99.19	99.60
Dec-92	99.45	99.21	99.99	99.35	Jan-97	99.17	99.51	98.82	96.50
Jan-93	98.75	98.51	99.38	98.82	Feb-97	97.93	99.19	97.62	98.48
Feb-93	99.04	98.66	99.65	98.43	Mar-97	98.73	99.87	99.54	99.74
Mar-93	97.89	97.24	98.36	97.70	Apr-97	99.50	99.99	100.00	100.00
Apr-93	98.78	98.18	99.43	99.06	May-97	99.90	99.97	99.99	100.00
May-93	99.36	99.00	99.77	98.34	Jun-97	99.97	99.99	99.99	100.00
Jun-93	99.35	99.33	99.75	97.57	Jul-97	99.99	100.00	100.00	100.00
Jul-93	99.36	99.73	99.85	97.09	Aug-97	100.00	100.00	100.00	100.00
Aug-93	99.29	99.72	99.80	96.26	Sep-97	100.00	100.00	100.00	100.00
Sep-93	99.17	99.46	99.71	96.06	Oct-97	100.00	100.00	100.00	100.00
Oct-93	98.72	99.27	99.64	96.76	Nov-97	99.85	99.89	99.93	99.92
Nov-93	98.55	99.19	99.66	97.66	Dec-97	99.69	99.90	99.57	99.92
Dec-93	98.19	98.85	99.35	97.34	Jan-98	99.00	99.62	98.99	99.60
Jan-94	98.52	98.68	92.75	88.98	Feb-98	99.40	99.76	99.72	99.93
Feb-94	96.25	96.22	84.45	89.14	Mar-98	99.73	99.90	99.98	99.99
Mar-94	97.35	98.09	98.45	96.88	Apr-98	100.00	100.00	100.00	100.00
Apr-94	97.64	98.47	98.85	97.26	May-98	100.00	100.00	100.00	100.00
May-94	97.89	98.83	98.85	96.99	Jun-98	99.97	100.00	100.00	100.00
Jun-94	98.51	99.47	97.81	97.33	Jul-98	99.80	100.00	100.00	100.00
Jul-94	99.37	99.98	97.62	97.94	Aug-98	99.82	100.00	100.00	100.00
Aug-94	99.99	100.00	99.07	99.55	Sep-98	99.81	100.00	100.00	100.00
Sep-94	100.00	100.00	99.60	99.78	Oct-98	99.84	100.00	100.00	100.00
Oct-94	99.98	100.00	99.82	99.82	Nov-98	99.80	99.99	100.00	100.00
Nov-94	99.93	99.99	99.93	99.93	Dec-98	99.86	99.95	100.00	100.00
Dec-94	99.70	99.97	99.68	99.60	Jan-99	99.28	99.22	98.13	95.05
Jan-95	99.19	99.81	99.06	98.58	Feb-99	98.73	99.95	99.97	99.97
Feb-95	98.53	99.42	97.83	92.99	Mar-99	98.21	99.54	99.31	99.57
Mar-95	99.04	99.88	98.95	98.76	Apr-99	98.18	99.99	100.00	100.00
Apr-95	99.73	99.94	99.64	99.24	May-99	98.82	100.00	100.00	100.00
May-95	99.98	100.00	99.95	99.85	Jun-99	99.22	100.00	100.00	100.00
Jun-95	100.00	100.00	100.00	99.99	Jul-99	99.44	99.87	100.00	100.00
Jul-95	100.00	100.00	100.00	99.96	Aug-99	99.48	99.70	100.00	99.99
Aug-95	100.00	100.00	100.00	99.80	Sep-99	99.45	99.82	100.00	100.00
Sep-95	100.00	100.00	100.00	99.82	Oct-99	99.64	99.88	100.00	100.00
Oct-95	99.97	100.00	99.99	99.90	Nov-99	99.92	99.85	100.00	100.00
Nov-95	99.90	100.00	100.00	99.97	Dec-99	99.93	99.74	100.00	99.97
Dec-95	98.75	99.32	98.60	97.77	Jan-00				
Jan-96	97.45	98.93	94.98	95.03	Feb-00				
Feb-96	96.53	99.02	93.85	95.88	Mar-00				
Mar-96	97.90	99.73	95.96	97.79	Apr-00	98.26	99.95	99.96	99.96
Apr-96	99.82	100.00	98.64	99.77	May-00	98.25	99.92	100.00	100.00
May-96	99.95	100.00	99.87	99.99	Jun-00	98.52	99.66	100.00	100.00
Jun-96	100.00	100.00	100.00	100.00	Jul-00	98.35	99.52	100.00	100.00

Table C23 Monthly Degree of Saturation-Knox Co.

Month	Sr1	Sr2	Sr3	Sr4	Month	Sr1	Sr2	Sr3	Sr4
Dec-91	100.00	100.00	100.00	100.00	Jun-94	98.37	99.10	100.00	99.88
Jan-92	100.00	100.00	100.00	100.00	Jul-94	97.54	99.88	100.00	99.91
Feb-92	100.00	100.00	100.00	100.00	Aug-94	98.78	100.00	100.00	99.93
Mar-92	100.00	100.00	100.00	100.00	Sep-94	99.32	100.00	100.00	100.00
Apr-92	100.00	100.00	100.00	100.00	Oct-94	99.44	99.87	100.00	100.00
May-92	100.00	100.00	98.93	100.00	Nov-94	98.92	99.74	100.00	100.00
Jun-92	100.00	100.00	100.00	100.00	Dec-94	99.05	99.74	100.00	100.00
Jul-92	99.35	99.39	99.83	99.80	Jan-95	99.40	99.37	99.77	99.59
Aug-92	99.37	99.34	99.87	99.80	Feb-95	98.99	99.27	99.51	95.00
Sep-92	99.99	99.98	100.00	99.89	Mar-95	98.21	99.10	100.00	100.00
Oct-92	100.00	100.00	100.00	99.83	Apr-95	97.77	98.93	100.00	100.00
Nov-92	100.00	100.00	100.00	99.77	May-95	97.85	98.90	100.00	100.00
Dec-92	100.00	100.00	100.00	99.84	Jun-95	97.30	98.23	98.59	99.71
Jan-93	99.99	99.99	100.00	99.87	Jul-95	98.88	99.19	99.11	99.82
Feb-93	99.98	99.98	100.00	99.82	Aug-95	99.33	99.92	99.78	99.96
Mar-93	99.95	99.91	99.98	99.82	Sep-95				
Apr-93	100.00	99.98	100.00	100.00	Oct-95				
May-93	100.00	100.00	100.00	100.00	Nov-95				
Jun-93	100.00	100.00	100.00	99.85	Dec-95				
Jul-93	100.00	99.97	99.77	99.28	Jan-96				
Aug-93	100.00	100.00	99.94	99.57	Feb-96				
Sep-93	100.00	99.93	99.95	99.99	Mar-96	97.68	98.09	100.00	99.32
Oct-93	100.00	99.59	99.96	100.00	Apr-96	97.71	98.59	100.00	99.39
Nov-93	100.00	99.97	100.00	100.00	May-96	97.73	98.64	100.00	98.58
Dec-93	99.99	99.97	99.98	99.89	Jun-96	98.19	98.59	100.00	97.92
Jan-94	99.76	99.44	98.61	91.64	Jul-96	99.43	99.87	100.00	99.52
Feb-94	98.74	98.50	99.55	97.88	Aug-96	99.88	99.99	100.00	99.12
Mar-94	98.41	98.11	99.91	99.89	Sep-96	99.95	100.00	100.00	99.31
Apr-94	99.60	99.56	100.00	100.00	Oct-96	99.95	99.99	100.00	98.75
May-94	99.68	99.99	100.00	99.98	Nov-96	99.68	99.96	100.00	98.71

Table C24 Monthly Degree of Saturation-Licking Co.

Month	Sr1	Sr2	Sr3	Sr4	Month	Sr1	Sr2	Sr3	Sr4
Dec-91	98.58	100.00	100.00	100.00	Sep-94	100.00	100.00	100.00	100.00
Jan-92	99.61	100.00	100.00	99.33	Oct-94	100.00	100.00	100.00	100.00
Feb-92	100.00	100.00	100.00	100.00	Nov-94	100.00	100.00	100.00	100.00
Mar-92	99.99	100.00	100.00	100.00	Dec-94	99.97	100.00	100.00	99.96
Apr-92	100.00	100.00	100.00	100.00	Jan-95	99.11	99.76	99.25	98.73
May-92	100.00	100.00	100.00	100.00	Feb-95	99.27	99.82	98.46	96.49
Jun-92	100.00	99.99	100.00	100.00	Mar-95	99.95	99.98	99.57	95.86
Jul-92	100.00	99.98	100.00	100.00	Apr-95	99.99	100.00	99.87	95.87
Aug-92	100.00	100.00	100.00	100.00	May-95	99.98	100.00	98.86	94.44
Sep-92	100.00	100.00	100.00	100.00	Jun-95	99.99	100.00	99.49	97.82
Oct-92	100.00	100.00	100.00	100.00	Jul-95	99.95	100.00	100.00	100.00
Nov-92	100.00	100.00	100.00	100.00	Aug-95	99.97	100.00	100.00	100.00
Dec-92	99.97	99.97	99.97	99.97	Sep-95	99.99	100.00	100.00	100.00
Jan-93	99.99	100.00	100.00	99.99	Oct-95	99.98	100.00	100.00	100.00
Feb-93	98.96	99.16	99.00	98.58	Nov-95	99.99	100.00	100.00	97.40
Mar-93	99.03	99.18	99.31	99.14	Dec-95	99.47	99.66	99.22	96.20
Apr-93	99.92	99.97	99.98	99.97	Jan-96	99.70	99.80	99.50	96.76
May-93	100.00	100.00	100.00	100.00	Feb-96	99.47	99.67	99.32	96.75
Jun-93	100.00	100.00	100.00	100.00	Mar-96	99.95	99.98	99.94	96.65
Jul-93	100.00	99.99	100.00	100.00	Apr-96	99.97	99.99	99.97	95.17
Aug-93	100.00	100.00	100.00	100.00	May-96	100.00	100.00	100.00	93.96
Sep-93	99.98	99.90	100.00	100.00	Jun-96	100.00	100.00	100.00	93.24
Oct-93	99.94	99.95	100.00	100.00	Jul-96	100.00	100.00	100.00	92.53
Nov-93	99.99	100.00	100.00	100.00	Aug-96	100.00	100.00	100.00	94.90
Dec-93	99.59	99.72	99.90	99.66	Sep-96	100.00	100.00	100.00	98.24
Jan-94	98.30	98.61	97.93	97.45	Oct-96	100.00	100.00	100.00	96.73
Feb-94	98.72	98.97	98.04	96.32	Nov-96	100.00	100.00	100.00	97.11
Mar-94	99.97	99.97	99.83	98.01	Dec-96	99.98	99.96	99.94	97.80
Apr-94	99.99	99.99	99.97	98.16	Jan-97	99.94	99.94	99.13	97.13
May-94	100.00	100.00	100.00	100.00	Feb-97	99.79	99.80	98.60	96.56
Jun-94	100.00	100.00	100.00	100.00	Mar-97	99.74	99.75	99.01	96.94
Jul-94	100.00	100.00	100.00	100.00	Apr-97	99.98	99.98	99.33	97.27
Aug-94	100.00	100.00	100.00	100.00	May-97	99.99	99.99	99.96	99.46

Table C25 Monthly Degree of Saturation-Wood2 Co.

Month	Sr1	Sr2	Sr3	Sr4
Jun-92	99.54	99.35	99.72	99.51
Jul-92	99.54	99.38	99.48	99.12
Aug-92	100.00	100.00	100.00	100.00
Sep-92	100.00	100.00	100.00	100.00
Oct-92	100.00	100.00	100.00	100.00
Nov-92	100.00	100.00	100.00	100.00
Dec-92	100.00	100.00	99.66	99.67
Jan-93	100.00	100.00	98.39	98.64
Feb-93	99.87	99.88	97.48	98.23
Mar-93	99.37	99.07	98.84	98.09
Apr-93	99.47	99.24	99.75	100.00
May-93	100.00	99.99	99.70	100.00
Jun-93	100.00	100.00	99.91	100.00
Jul-93	100.00	99.96	99.66	100.00
Aug-93	100.00	99.79	97.88	100.00
Sep-93	99.74	99.51	99.56	99.53
Oct-93	99.88	99.73	99.98	99.96
Nov-93	99.89	99.77	99.99	99.91
Dec-93	99.98	99.88	99.96	99.88
Jan-94	99.77	98.60	94.92	81.43
Feb-94	99.52	95.72	91.56	83.32
Mar-94	99.80	99.53	94.32	98.77
Apr-94	99.69	99.14	97.51	100.00
May-94	99.77	99.33	98.47	100.00
Jun-94	99.57	99.28	96.77	100.00
Jul-94	99.28	98.92	96.74	100.00
Aug-94	99.49	99.38	99.08	100.00
Sep-94	99.58	99.45	100.00	100.00
Oct-94	99.85	99.73	99.96	100.00
Nov-94	99.99	99.93	99.99	100.00
Dec-94	99.90	99.80	100.00	100.00
Jan-95	99.85	99.81	100.00	99.85
Feb-95	99.86	99.91	99.92	99.15
Mar-95	99.44	99.48	100.00	100.00
Apr-95	98.71	98.09	99.96	100.00
May-95	97.17	96.90	99.85	98.22

Table C26 Monthly Degree of Saturation-Wood8 Co.

Month	Sr1	Sr2	Sr3	Sr4	Month	Sr1	Sr2	Sr3	Sr4
Jun-92	92.77	93.81	86.69	92.24	Nov-96	100.00	100.00	100.00	100.00
Jul-92	91.34	92.42	88.42	91.48	Dec-96	100.00	100.00	100.00	100.00
Aug-92	88.49	90.46	87.18	89.97	Jan-97	99.38	99.32	99.62	95.26
Sep-92	92.52	94.37	91.45	93.60	Feb-97	98.62	98.58	99.59	97.75
Oct-92	93.88	96.20	93.57	95.25	Mar-97	99.85	99.92	100.00	99.97
Nov-92					Apr-97	99.99	99.99	100.00	99.99
Dec-92	98.91	100.00	100.00	100.00	May-97	99.93	100.00	100.00	100.00
Jan-93	98.81	99.78	99.93	99.85	Jun-97	99.75	99.91	100.00	99.92
Feb-93	99.72	99.95	99.61	95.59	Jul-97	100.00	99.99	100.00	100.00
Mar-93	99.82	99.97	99.64	97.85	Aug-97	100.00	99.99	100.00	100.00
Apr-93	99.60	100.00	99.99	100.00	Sep-97	100.00	99.99	100.00	100.00
May-93	98.85	99.99	100.00	100.00	Oct-97	100.00	99.99	100.00	100.00
Jun-93	96.83	99.83	100.00	100.00	Nov-97	100.00	100.00	99.99	100.00
Jul-93	97.03	99.71	100.00	100.00	Dec-97	100.00	100.00	99.90	100.00
Aug-93	97.82	99.72	100.00	100.00	Jan-98	100.00	100.00	99.96	100.00
Sep-93	98.86	99.99	100.00	100.00	Feb-98	100.00	100.00	99.97	100.00
Oct-93	99.19	100.00	100.00	100.00	Mar-98	100.00	100.00	99.99	100.00
Nov-93	99.64	99.99	100.00	100.00	Apr-98	100.00	100.00	100.00	100.00
Dec-93	99.95	99.99	99.99	99.40	May-98	100.00	100.00	100.00	100.00
Jan-94	99.30	99.48	99.76	86.82	Jun-98	100.00	100.00	100.00	100.00
Feb-94					Jul-98	100.00	99.62	100.00	99.80
Mar-94					Aug-98	100.00	99.13	100.00	99.55
Apr-94					Sep-98	100.00	99.72	100.00	99.90
May-94	97.27	99.60	100.00	100.00	Oct-98	100.00	100.00	100.00	100.00
Jun-94	98.86	99.86	100.00	100.00	Nov-98	100.00	100.00	100.00	100.00
Jul-94	99.73	98.88	100.00	99.84	Dec-98	100.00	100.00	99.97	100.00
Aug-94	100.00	98.23	100.00	99.23	Jan-99	98.26	97.63	99.09	92.70
Sep-94	100.00	98.25	100.00	99.01	Feb-99	99.43	99.52	100.00	99.59
Oct-94	100.00	98.77	100.00	99.30	Mar-99	99.86	99.88	100.00	99.90
Nov-94	100.00	99.91	100.00	99.99	Apr-99	100.00	100.00	100.00	100.00
Dec-94	100.00	100.00	100.00	100.00	May-99	100.00	100.00	100.00	100.00
Jan-95	99.83	99.69	100.00	98.19	Jun-99	99.98	99.61	100.00	99.68
Feb-95	99.90	99.79	99.81	94.87	Jul-99	99.93	98.30	100.00	98.42
Mar-95	100.00	100.00	100.00	100.00	Aug-99	99.96	98.34	100.00	98.36
Apr-95	100.00	100.00	100.00	100.00	Sep-99	99.96	99.32	100.00	99.27
May-95	100.00	100.00	100.00	100.00	Oct-99	100.00	99.97	100.00	99.96
Jun-95	100.00	98.99	100.00	99.54	Nov-99	100.00	100.00	100.00	100.00
Jul-95	100.00	98.18	100.00	98.23	Dec-99	100.00	100.00	100.00	100.00
Aug-95	100.00	98.04	100.00	97.69	Jan-00				
Sep-95	100.00	99.55	99.96	99.58	Feb-00				
Oct-95	100.00	100.00	99.96	100.00	Mar-00				
Nov-95	100.00	100.00	99.90	100.00	Apr-00	100.00	100.00	99.99	100.00
Dec-95	99.82	99.76	99.90	98.35	May-00	99.68	99.67	99.99	99.79
Jan-96	99.85	99.80	98.73	92.17	Jun-00	99.97	99.42	100.00	99.77
Feb-96	100.00	99.99	96.41	91.37	Jul-00	99.97	99.26	100.00	99.41
Mar-96	99.99	99.98	99.92	99.94	Aug-00	99.98	99.17	100.00	99.11
Apr-96	100.00	100.00	100.00	100.00	Sep-00	100.00	99.45	100.00	99.35
May-96	99.85	100.00	100.00	100.00	Oct-00	99.98	99.93	100.00	99.92
Jun-96	99.96	99.69	100.00	100.00	Nov-00	100.00	100.00	100.00	100.00
Jul-96	100.00	98.95	100.00	99.99	Dec-00	99.68	99.49	99.99	95.95
Aug-96	100.00	99.05	100.00	99.99	Jan-01	99.34	99.03	97.33	92.47
Sep-96	100.00	99.69	100.00	99.97	Feb-01	99.59	99.56	99.96	99.07
Oct-96	100.00	100.00	100.00	100.00	Mar-01	99.72	99.81	99.99	99.75

Table C27 Seasonal Degree of Saturation ADAMS Co.

Season	Sr1	Sr2	Sr3	Sr4
SP95*	99.92		99.08	100.00
SU95	99.04		96.86	99.85
F95	98.79		98.66	99.79
W95	98.49		98.46	99.08
SP96*	99.17		99.50	99.75
SU96*				
F96*	99.52		98.95	97.16
W96	98.40		97.69	95.53
SP97	98.99		97.71	92.28
SU97	99.79		97.22	
F97	100.00		97.74	
W97	100.00		96.23	
SP98	100.00		96.73	
SU98	99.93		96.64	
F98	99.83		97.97	
W98	99.63		99.77	
SP99	99.60		99.93	
SU99	99.88		96.65	
F99	99.97			
W99*	99.68			
SP00*	99.08			
SU00	98.18			
F00	99.13			
W00	97.61			

* Incomplete Data

Table C28 Seasonal Degree of Saturation ATHENS Co.

Season	Sr1	Sr2	Sr3	Sr4
W91	98.43	98.91	99.25	99.43
SP92	98.78	99.09	99.32	99.37
SU92	99.35	99.03	99.39	98.31
F92	99.09	98.72	100.00	99.81
W92	98.91	98.54	99.90	98.64
SP93	98.70	98.03	99.97	99.65
SU93	96.52	95.50	99.91	99.72
F93	98.19	97.84	99.99	99.89
W93*	98.95	98.81	99.81	99.24
SP94*	97.58	97.06	98.74	
SU94	97.99	97.18	99.77	
F94	99.50	99.14	100.00	
W94	99.94	99.89	99.81	
SP95	98.92	99.93	100.00	
SU95	98.87	99.53	100.00	
F95	99.97	99.79	99.96	
W95	99.19	99.23	95.72	
SP96	99.89	99.93	99.51	
SU96*	100.00	100.00	100.00	
F96				
W96*	96.44	99.80	96.04	
SP97				
SU97*		97.29		
F97		97.81		
W97		98.65		
SP98		97.93		
SU98		97.81		
F98		98.24		
W98		97.69		
SP99		93.25		
SU99*		93.08		
F99				
W99				
SP00*		95.77		
SU00		96.52		
F00		97.70		
W00		97.62		

* Incomplete Data

Table C29 Seasonal Degree of Saturation COLUMBIANA Co.

Season	Sr1	Sr2	Sr3	Sr4
F94*	99.94	99.84	98.54	98.19
W94	97.34	96.73	96.72	95.59
SP95	99.90	99.47	99.89	99.98
SU95*	99.99	99.22	99.79	100.00
F95	99.62	99.08	98.09	98.72
W95*	94.59	94.09	91.77	94.07

* Incomplete Data

Table C30 Seasonal Degree of Saturation CRAWFORD Co.

Season	Sr1	Sr2	Sr3	Sr4
SP92*	97.77	96.91	99.64	94.43
SU92	98.80	98.47	99.85	95.80
F92	99.34	99.05	99.98	98.91
W92	98.83	98.51	99.42	98.64
SP93	98.96	98.55	99.46	98.35
SU93	99.32	99.65	99.81	96.60
F93	98.60	99.18	99.61	97.21
W93	97.45	97.74	92.17	91.75
SP94	97.88	98.76	98.68	97.18
SU94	99.65	99.96	98.48	98.79
F94	99.93	100.00	99.84	99.84
W94	98.95	99.71	98.66	96.92
SP95	99.83	99.97	99.77	99.58
SU95	100.00	100.00	100.00	99.87
F95	99.77	99.91	99.84	99.67
W95	97.19	99.10	95.02	95.89
SP96	99.79	99.98	99.13	99.78
SU96*	100.00	100.00	100.00	100.00
F96*	99.70	99.85	99.63	99.79
W96	98.67	99.51	98.62	98.23
SP97	99.68	99.97	99.99	100.00
SU97	100.00	100.00	100.00	100.00
F97	99.89	99.94	99.89	99.95
W97	99.34	99.75	99.50	99.83
SP98	99.99	100.00	100.00	100.00
SU98	99.82	100.00	100.00	100.00
F98	99.82	99.99	100.00	100.00
W98	98.94	99.55	99.11	98.14
SP99	98.62	100.00	100.00	100.00
SU99	99.43	99.81	100.00	100.00
F99	99.79	99.83	100.00	100.00
W99*	99.90	99.82	100.00	99.96
SP00*	98.33	99.87	99.99	99.99

* Incomplete Data

Table C31 Seasonal Degree of Saturation KNOX Co.

Season	Sr1	Sr2	Sr3	Sr4
F91*	100.00	100.00	100.00	100.00
W91	100.00	100.00	100.00	100.00
SP92*	96.90	96.90	96.36	96.90
SU92	99.57	99.57	99.90	99.86
F92	100.00	100.00	100.00	99.79
W92	99.98	99.98	99.99	99.85
SP93	100.00	99.98	100.00	99.99
SU93	100.00	99.98	99.90	99.57
F93	100.00	99.83	99.97	100.00
W93	99.04	98.77	99.35	96.44
SP94	99.41	99.61	100.00	99.99
SU94	98.37	99.81	100.00	99.92
F94	99.17	99.82	100.00	100.00
W94	99.00	99.32	99.77	98.29
SP95	97.79	98.88	100.00	100.00
SU95*	98.58	99.04	98.69	99.73
F95				
W95				
SP96	97.76	98.47	100.00	98.71
SU96	99.61	99.88	100.00	99.27
F96	99.54	99.85	99.49	97.90

* Incomplete Data

Table C32 Seasonal Degree of Saturation LICKING Co.

Season	Sr1	Sr2	Sr3	Sr4
F91*	98.41	100.00	100.00	100.00
W91	99.72	100.00	100.00	99.78
SP92	100.00	100.00	100.00	100.00
SU92	100.00	99.99	100.00	100.00
F92	99.99	99.99	99.99	99.99
W92	99.55	99.62	99.60	99.45
SP93	99.91	99.95	99.96	99.96
SU93	100.00	99.98	100.00	100.00
F93	99.96	99.96	100.00	100.00
W93	98.89	99.10	98.60	97.42
SP94	100.00	100.00	99.99	99.16
SU94	100.00	100.00	100.00	100.00
F94	100.00	100.00	100.00	100.00
W94	99.45	99.86	99.14	97.52
SP95	99.98	99.99	99.38	95.57
SU95	99.97	100.00	100.00	100.00
F95	99.98	99.99	99.96	98.45
W95	99.54	99.70	99.36	96.52
SP96	99.99	100.00	99.99	94.63
SU96	100.00	100.00	100.00	94.49
F96	100.00	99.99	99.99	97.34
W96	99.82	99.83	98.99	96.94
SP97*	99.97	99.97	99.64	98.47

* Incomplete Data

Table C33 Seasonal Degree of Saturation WOOD2 Co.

Season	Sr1	Sr2	Sr3	Sr4
SP92*	99.28	98.99	99.56	99.24
SU92	99.85	99.79	99.83	99.70
F92	100.00	100.00	99.97	99.99
W92	99.88	99.85	98.18	98.36
SP93	99.73	99.60	99.80	100.00
SU93	99.97	99.83	99.07	99.95
F93	99.86	99.73	99.94	99.85
W93	99.72	98.08	94.01	88.02
SP94*	99.71	99.29	97.62	100.00
SU94	99.43	99.20	98.23	100.00
F94	99.89	99.79	99.98	100.00
W94	99.78	99.79	99.97	99.68
SP95	97.87	97.63	99.93	98.82

* Incomplete Data

Table C34 Seasonal Degree of Saturation WOOD8 Co.

Season	Sr1	Sr2	Sr3	Sr4
SP92*	92.99	94.48	86.38	92.74
SU92*	90.71	92.16	88.47	91.39
F92*	93.54	95.71	93.08	94.81
W92*	99.33	99.88	99.74	97.74
SP93	98.84	99.99	100.00	100.00
SU93	97.60	99.75	100.00	100.00
F93	99.47	99.99	100.00	100.00
W93*	99.64	99.76	99.87	92.95
SP94*	97.96	99.79	100.00	100.00
SU94	99.83	98.62	100.00	99.51
F94	100.00	99.34	100.00	99.61
W94	99.91	99.83	99.94	97.78
SP95	100.00	99.85	100.00	99.98
SU95	100.00	98.40	100.00	98.36
F95	100.00	100.00	99.92	99.87
W95	99.88	99.84	98.36	94.08
SP96	99.94	99.98	100.00	100.00
SU96	100.00	99.14	100.00	99.98
F96	100.00	100.00	100.00	100.00
W96	99.31	99.30	99.74	97.66
SP97	99.91	100.00	100.00	100.00
SU97	99.98	99.94	100.00	99.97
F97	100.00	100.00	99.98	100.00
W97	100.00	100.00	99.96	100.00
SP98	100.00	100.00	100.00	100.00
SU98	100.00	99.49	100.00	99.75
F98	100.00	100.00	99.99	100.00
W98	99.18	98.99	99.68	97.32
SP99	100.00	99.97	100.00	99.97
SU99	99.95	98.56	100.00	98.62
F99	100.00	99.98	100.00	99.97
W99*	100.00	100.00	100.00	100.00
SP00*	99.86	99.72	99.99	99.86
SU00	99.98	99.24	100.00	99.27
F00	99.99	99.96	100.00	99.95
W00	99.44	99.29	99.06	95.64

* Incomplete Data

Appendix D

**BACK CALCULATION OF RESILIENT MODULUS OF SUBGRADE SOILS
FROM FWD DEFLECTIONS**

Table D1 DATA to BACKCALCULATE RESILIENT MODULUS
AT THE BREAK POINT FROM FWD TESTING (Adams Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Time/Tem (FWD)	*	*	*	*
	Air Temp (Logger)				
1992	Time/Tem (FWD)	*	*	*	*
	Air Temp (Logger)				
1993	Time/Tem (FWD)	*	*	*	12/8/93 9:21 31F
	Air Temp (Logger)				FWD -0.5C -
1994	Time/Tem (FWD)	*	6/23/94 11:01 75F	9/20/94 9:22 58F	11/29/94 9:19 32F
	Air Temp (Logger)		LOG 29.3C	FWD 14.4C -	FWD 0C -
1995	Time/Tem (FWD)	3/21/95 9:42 50F	6/6/95 9:15 67F	11/7/95 9:56 45F	*
	Air Temp (Logger)	FWD 10.0C -	FWD 19.4C -	LOG 9.2C	*
1996	Time/Tem (FWD)	4/30/96 9:54 49F	7/8/96 8:45 79F	9/17/96 9:03 64F	*
	Air Temp (Logger)	LOG 5.2C	FWD 26.5C -	FWD 17.8C -	*
1997	Time/Tem (FWD)	4/1/97 9:24 35F	7/15/97 9:24 82F	*	*
	Air Temp (Logger)	LOG 6.9C	FWD 69F LOG 26.0C	*	*
1998	Time/Tem (FWD)	3/10/98 10:20 31F	6/23/98 9:09 75F	*	*
	Air Temp (Logger)	FWD 28F LOG -4.1C	FWD 69F LOG 22.2C		
1999	Time/Tem (FWD)	4/20/99 8:38 52F		9/21/99 8:45 64F	
	Air Temp (Logger)	LOG 9.2C		- LOG 13.4C	
2000	Time/Tem (FWD)	3/27/00 9:31 57F		9/20/00 8:47 67F	
	Air Temp (Logger)	- -		- LOG 20.4C	
2001	Time/Tem (FWD)	4/17/01 8:51 43F			
	Air Temp (Logger)	- LOG 1.2C			

* No FWD Files

Table D2 DATA to BACKCALCULATE RESILIENT MODULUS
AT THE BREAK POINT FROM FWD TESTING (Athens Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Time/Tem (FWD)	*	*	11/14/91 10:35 39F	*
	Air Temp (Logger)			FWD 3.9C	
1992	Time/Tem (FWD)	3/19/92 9:01 31F	6/10/92 8:44 55F	9/24/92 9:21 45F	11/23/92 9:25 43F
	Air Temp (Logger)	LOG 4.2C	LOG 16.3	LOG 9.8C	LOG 9.6C
1993	Time/Tem (FWD)	3/24/93 9:56 55F	6/30/93 9:32 70F	9/20/93 8:43 51F	12/6/93 8:45 39F
	Air Temp (Logger)	LOG 13.0C	LOG 21.8C	LOG 16.3	LOG 6.5C
1994	Time/Tem (FWD)	*	6/16/94 9:28 75F	9/21/94 8:59 60F	12/01/94 9:32 24F
	Air Temp (Logger)		LOG 26.5C	LOG 19.6C	LOG -1.6C
1995	Time/Tem (FWD)	3/23/95 9:14 41F	6/8/95 10:54 75F	11/15/95 9:58 30F	*
	Air Temp (Logger)	LOG 4.9C	LOG 28.1C	LOG 1.3C	
1996	Time/Tem (FWD)	4/25/96 9:47 62F	6/26/96 8:57 70F	9/19/96 9:31 49F	*
	Air Temp (Logger)	LOG 18.0C	LOG 20.2C	FWD 9.4C	
1997	Time/Tem (FWD)	4/3/97 8:37 44F	7/17/97 8:22 83F		*
	Air Temp (Logger)	LOG 8.2C	FWD 23.3C		
1998	Time/Tem (FWD)	3/12/98 9:16 19F	Bad Load Cell	9/30/98 10:03 80F	*
	Air Temp (Logger)	FWD 15F LOG -5.5C		FWD 65F LOG 24.8C	
1999	Time/Tem (FWD)	4/22/99 8:34 61F		10/14/99 9:02 57F	
	Air Temp (Logger)	FWD 56F LOG 22.0C		- -	
2000	Time/Tem (FWD)	3/30/00 8:16 45F		9/21/00 8:30 61F	
	Air Temp (Logger)	- -		- LOG 14.5C	
2001	Time/Tem (FWD)	4/18/01 8:23 42.1F			
	Air Temp (Logger)	- LOG 4.78C			

* No FWD Files

Table D3 DATA to BACKCALCULATE RESILIENT MODULUS
AT THE BREAK POINT FROM FWD TESTING (Crawford Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Time/Tem (FWD)	*	*	11/7/91 9:56 26F	*
	Air Temp (Logger)			FWD -3.3C	
1992	Time/Tem (FWD)	3/18/92 9:44 28F	6/9/92 8:55 65F	9/23/92 9:18 43	11/25/92 8:52 41F
	Air Temp (Logger)	FWD -2.2C	LOG 17.1C	LOG 7.4C	LOG 5.9C
1993	Time/Tem (FWD)	3/23/93 8:52 42F	6/29/93 10:08 67F	9/23/93 8:53 64F	12/2/93 9:04 39F
	Air Temp (Logger)	LOG 7.8C	LOG 20.9C	LOG 18.0C	LOG 4.8C
1994	Time/Tem (FWD)	Incomplete FWD File	Incomplete FWD File	Incomplete FWD File	Incomplete FWD File
	Air Temp (Logger)				
1995	Time/Tem (FWD)	3/27/95 8:32 45F	6/12/95 9:11 58F	11/8/95 9:56 35F	*
	Air Temp (Logger)	LOG 3.2C	LOG 19.8C	LOG -0.4C	
1996	Time/Tem (FWD)	5/1/96 9:29 47F	6/27/96 9:21 76F	9/20/96 8:53 54F	*
	Air Temp (Logger)	LOG 8.1C	LOG 21.2C	FWD 12.2C	
1997	Time/Tem (FWD)	4/4/97 8:57 50F	7/28/97 9:11 85F	*	*
	Air Temp (Logger)	LOG 16.2C	FWD 74F LOG 24.5C		
1998	Time/Tem (FWD)	3/17/98 9:22 42F	Bad Load Cell	10/01/98 9:11 57F	*
	Air Temp (Logger)	FWD 41F LOG 2.5C		FWD 57F LOG 12.1C	
1999	Time/Tem (FWD)	4/26/99 8:55 48F		9/22/99 9:02 46F	
	Air Temp (Logger)	FWD 44F LOG 13.0C		- LOG 11.8C	
2000	Time/Tem (FWD)	3/29/00 9:26 44F		9/22/00 8:27 53F	
	Air Temp (Logger)	- -		- LOG 12.9C	
2001	Time/Tem (FWD)	4/19/01 8:57 43F			
	Air Temp (Logger)	- -			

* No FWD Files

Table D4 DATA to BACKCALCULATE RESILIENT MODULUS
AT THE BREAK POINT FROM FWD TESTING (Knox Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Time/Tem (FWD)	*	*	11/12/91 10:59 33F	*
	Air Temp (Logger)			FWD 0.6C	
1992	Time/Tem (FWD)	3/18/92 12:22 34F	6/9/92 11:47 71F	9/23/92 12:59 58F	11/25/92 10:48 41F
	Air Temp (Logger)	LOG 7.3C	FWD 21.7C	LOG 11.8C	LOG 7.3C
1993	Time/Tem (FWD)	3/23/93 10:37 44F	6/30/93 2:07 74F	9/23/93 10:49 65F	12/2/93 10:54 44F
	Air Temp (Logger)	LOG 8.4C	LOG 14.1C	LOG 18.6C	LOG 8.3C
1994	Time/Tem (FWD)	*	6/17/94 12:05 84F	9/23/94 1130 65F	12/02/94 11:45 39F
	Air Temp (Logger)		LOG 30.9C	LOG 16.9C	LOG 10.5C
1995	Time/Tem (FWD)	3/27/95 10:19 44F	6/12/95 11:07 58F	11/8/95 11:51 36F	*
	Air Temp (Logger)	LOG 6.1C	LOG 18.6C	FWD 2.2C	
1996	Time/Tem (FWD)	5/1/96 11:52 46F	6/27/96 10:58 81F	9/20/96 11:18 80F	*
	Air Temp (Logger)	LOG 8.8C	LOG 23.4C	LOG 20.6C	
1997	Time/Tem (FWD)	4/4/97 12:26 73	7/28/97 11:03 80F	*	*
	Air Temp (Logger)	LOG 22.9C	FWD 75F LOG 24C		
1998	Time/Tem (FWD)	3/17/98 11:11 42F	Bad Load Cell	10/01/98 11:07 73F	*
	Air Temp (Logger)	FWD 38F LOG 2.7C		FWD 59F LOG 14.0C	
1999	Time/Tem (FWD)	4/26/99 11:01 76F		9/22/99 10:45 65F	
	Air Temp (Logger)	FWD 61F LOG 16.6C		- LOG 13.4C	
2000	Time/Tem (FWD)	3/29/00 11:10 48F		*	
	Air Temp (Logger)	- -			
2001	Time/Tem (FWD)	4/19/01 11:08 69.1F			
	Air Temp (Logger)	- LOG 11.7C			

* No FWD Files

Table D5 DATA to BACKCALCULATE RESILIENT MODULUS
AT THE BREAK POINT FROM FWD TESTING (Licking Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Time/Tem (FWD)	*	*	11/13/91 11:07 36F	*
	Air Temp (Logger)			FWD 2.2C	
1992	Time/Tem (FWD)	3/19/92 12:57 34F	6/10/92 12:28 73F	9/24/92 12:32 59F	11/23/92 12:00 45F
	Air Temp (Logger)	LOG 0.0C	LOG 21.9C	LOG 15.3C	LOG 7.8C
1993	Time/Tem (FWD)	3/24/93 12:35 58F	6/30/93 11:35 70F	9/20/93 11:36 62F	12/6/93 12:56 38F
	Air Temp (Logger)	LOG 9.7C	LOG 22.3C	LOG 17.0F	LOG 4.0C
1994	Time/Tem (FWD)	*	6/16/94 13:19 91F	9/21/94 11:31 71F	12/01/94 12:51 34F
	Air Temp (Logger)		LOG 28.8C	LOG 23.2C	LOG 4.0C
1995	Time/Tem (FWD)	3/23/95 11:39 46F	6/8/95 13:03 76F	11/15/95 12:58 33F	
	Air Temp (Logger)	LOG 5.0C	LOG 23.6C	LOG 1.3C	
1996	Time/Tem (FWD)	4/25/96 12:32 64F	6/26/96 12:46 98F	9/19/96 11:59 83F	*
	Air Temp (Logger)	LOG 19.2C	FWD 75F LOG 24.5C	LOG 21.2C	
1997	Time/Tem (FWD)	4/3/97 12:07 55F	7/17/97 11:25 106F	*	*
	Air Temp (Logger)	LOG 18.1C	FWD 29.4C		
1998	Time/Tem (FWD)	3/12/98 12:44 27F	*	9/30/98 13:18 92F	*
	Air Temp (Logger)	FWD 26F LOG -4.4C		FWD 78F LOG 24.9C	
1999	Time/Tem (FWD)	4/22/99 11:16 81F		*	
	Air Temp (Logger)	FWD 18.3C -			
2000	Time/Tem (FWD)	3/30/00 10:53 61F		9/21/00 11:04 73F	
	Air Temp (Logger)	-		-	
2001	Time/Tem (FWD)	4/18/01 11:47 63.0F			
	Air Temp (Logger)	-			

* No FWD Files

Table D6 DATA to BACKCALCULATE RESILIENT MODULUS
AT THE BREAK POINT FROM FWD TESTING (Wood 8 Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Time/Tem (FWD)	*	*	10/20/91 9:45 60F	11/5/91 9:08 19F
	Air Temp (Logger)			FWD 15.6C	FWD -7.2C
1992	Time/Tem (FWD)	3/14/92 9:38 37F	6/8/92 8:44 60F	9/28/92 9:01 49F	11/24/92 8:51 40F
	Air Temp (Logger)	FWD 2.8C	LOG 16.5C	LOG 11.4C	FWD 4.4C
1993	Time/Tem (FWD)	3/22/93 9:14 32F	6/28/93 8:51 66F	9/21/93 9:07 50F	12/1/93 9:13 27F
	Air Temp (Logger)	LOG 1.5C	LOG 19.5C	LOG 15.9C	LOG -1.7C
1994	Time/Tem (FWD)	*	6/21/94 9:24 71F	9/22/94 8:53 57F	11/30/94 9:41 29F
	Air Temp (Logger)		LOG 28.6C	LOG 20.4C	LOG -0.4C
1995	Time/Tem (FWD)	3/22/95 9:04 35F	6/7/95 8:52 63F	11/20/95 9:40 39F	*
	Air Temp (Logger)	LOG 4.7C	LOG 25.2C	LOG 4.0C	
1996	Time/Tem (FWD)	4/24/96 8:37 40F	6/25/96 9:07 74F	9/18/96 8:36 59F	*
	Air Temp (Logger)	LOG 6.2C	FWD 61F LOG 18.7C	LOG 16.3C	
1997	Time/Tem (FWD)	4/2/97 9:15 35F	7/16/97 9:26 85F	*	*
	Air Temp (Logger)	LOG 10.2C	FWD 71F LOG 26.8C		
1998	Time/Tem (FWD)	3/11/98 9:10 19F	Bad Load Cell	9/29/98 8:46 61F	*
	Air Temp (Logger)	FWD 18F LOG -7.8C		FWD 62F LOG 15.8C	
1999	Time/Tem (FWD)	4/21/99 8:50 51F		9/20/99 8:54 70F	
	Air Temp (Logger)	FWD 50F LOG 9.5C		- LOG 17.4C	
2000	Time/Tem (FWD)	3/28/00 8:54 48F		9/19/00 8:46 64F	
	Air Temp (Logger)	- -		- LOG 19.6C	
2001	Time/Tem (FWD)	4/16/01 9:09 45F			
	Air Temp (Logger)	LOG 6.0C			

* No FWD Files

Table D7 BACK CALCULATED RESILIENT MODULUS AT THE BREAK POINT
FROM FWD TESTING (MPa)
(Adams Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Average				
	at Ref. Pt.				
1992	Average				
	at Ref. Pt.				
1993	Average				28.13
	at Ref. Pt.				67.42
1994	Average		- X	- X	9.86
	at Ref. Pt.		20.27	35.44	45.71
1995	Average	30.20	37.85	94.31	
	at Ref. Pt.	59.50	75.49	129.12	
1996	Average	- X	- X	33.37	
	at Ref. Pt.	5.93	27.16	49.77	
1997	Average	34.19	1.24		
	at Ref. Pt.	70.18	28.75		
1998	Average	- X	18.27		
	at Ref. Pt.	32.75	49.09		
1999	Average	36.95		8.82	
	at Ref. Pt.	70.39		5.38	
2000	Average	34.40		31.71	
	at Ref. Pt.	64.67		48.67	
2001	Average	- X			
	at Ref. Pt.	- X			

X High FWD Deflections

Table D8 BACK CALCULATED RESILIENT MODULUS AT THE BREAK POINT
FROM FWD TESTING (MPa)
(Athens Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Average			129.06	
	at Ref. Pt.			138.29	
1992	Average	143.53	141.74	138.36	157.25
	at Ref. Pt.	160.70	159.04	154.29	173.25
1993	Average	177.52	163.94	192.83	155.25
	at Ref. Pt.	203.79	179.18	201.72	176.14
1994	Average		148.84	167.32	116.44
	at Ref. Pt.		152.01	166.63	124.37
1995	Average	136.02	187.86	185.03	
	at Ref. Pt.	142.64	194.76	191.17	
1996	Average	167.39	138.16	115.96	
	at Ref. Pt.	181.86	139.19	120.99	
1997	Average	133.61	138.64		
	at Ref. Pt.	151.39	147.95		
1998	Average	104.58		175.80	
	at Ref. Pt.	120.30		185.79	
1999	Average	200.20		157.11	
	at Ref. Pt.	215.99		164.77	
2000	Average	120.71		138.29	
	at Ref. Pt.	- X		149.88	
2001	Average	120.30			
	at Ref. Pt.	126.23			

X High FWD Deflections

Table D9 BACK CALCULATED RESILIENT MODULUS AT THE BREAK POINT
FROM FWD TESTING (MPa)
(Crawford Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Average			18.82	
	at Ref. Pt.			30.40	
1992	Average	- X	34.75	21.30	45.71
	at Ref. Pt.	8.82 X	38.40	28.82	55.84
1993	Average	33.78	37.99	60.46	43.29
	at Ref. Pt.	51.43	41.71	63.70	52.19
1994	Average				
	at Ref. Pt.				
1995	Average	17.92	66.60	60.87	
	at Ref. Pt.	30.20	75.77	67.35	
1996	Average	15.44	14.06	24.34	
	at Ref. Pt.	23.16	20.20	27.16	
1997	Average	55.77	26.47		
	at Ref. Pt.	65.49	35.16		
1998	Average	- X		19.10	
	at Ref. Pt.	12.68		25.99	
1999	Average	34.95		17.86	
	at Ref. Pt.	34.06		19.10	
2000	Average	- X		2.14	
	at Ref. Pt.	4.48		6.20	
2001	Average	- X			
	at Ref. Pt.	- X			

X High FWD Deflections

Table D10 BACK CALCULATED RESILIENT MODULUS AT THE BREAK POINT
FROM FWD TESTING (MPa)
(Knox Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Average			70.04	
	at Ref. Pt.			53.50	
1992	Average	67.15	84.52	66.25	79.14
	at Ref. Pt.	52.53	71.42	55.70	77.49
1993	Average	54.60	54.95	121.82	89.83
	at Ref. Pt.	31.57	30.06	95.48	68.39
1994	Average		85.62	74.94	77.14
	at Ref. Pt.		45.64	45.36	51.71
1995	Average	48.46	96.72	85.49	
	at Ref. Pt.	20.13	56.60	50.74	
1996	Average	20.27	72.52	79.01	
	at Ref. Pt.	- X	58.32	49.91	
1997	Average	69.28	65.84		
	at Ref. Pt.	47.91	36.33		
1998	Average	25.51		56.39	
	at Ref. Pt.	28.13		41.43	
1999	Average	48.67		58.53	
	at Ref. Pt.	11.17		21.37	
2000	Average	8.13			
	at Ref. Pt.	- X			
2001	Average	35.30			
	at Ref. Pt.	20.54			

X High FWD Deflections

Table D11 BACK CALCULATED RESILIENT MODULUS AT THE BREAK POINT
FROM FWD TESTING (MPa)
(Licking Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Average			219.71	
	at Ref. Pt.			188.83	
1992	Average	203.03	242.12	255.84	245.08
	at Ref. Pt.	170.28	195.17	221.57	211.99
1993	Average	250.53	268.31	281.41	235.91
	at Ref. Pt.	205.37	236.46	232.12	193.58
1994	Average		205.92	266.94	218.82
	at Ref. Pt.		138.29	209.65	158.91
1995	Average	224.81	269.49	265.90	
	at Ref. Pt.	150.15	195.79	217.44	
1996	Average	256.18	237.36	245.43	
	at Ref. Pt.	170.07	169.04	166.49	
1997	Average	249.56	231.43		
	at Ref. Pt.	197.93	186.00		
1998	Average	182.07		241.84	
	at Ref. Pt.	134.02		198.06	
1999	Average	235.64			
	at Ref. Pt.	154.84			
2000	Average	238.19		242.53	
	at Ref. Pt.	131.61		137.60	
2001	Average	145.88			
	at Ref. Pt.	-X			

X High FWD Deflections

Table D12 BACK CALCULATED RESILIENT MODULUS AT THE BREAK POINT
FROM FWD TESTING (MPa)
(Wood 8 Co.)

YEAR	Eri	SPRING	SUMMER	FALL	WINTER
1991	Average			71.28	18.89
	at Ref. Pt.			78.18	24.68
1992	Average	42.74	56.94	60.39	63.22
	at Ref. Pt.	44.40	56.32	64.60	64.11
1993	Average	61.77	62.67	62.39	73.15
	at Ref. Pt.	62.25	67.42	75.01	78.38
1994	Average		69.15	88.93	69.56
	at Ref. Pt.		67.42	87.55	76.25
1995	Average	74.52	99.41	124.23	
	at Ref. Pt.	66.32	98.65	130.02	
1996	Average	71.42	57.63	89.90	
	at Ref. Pt.	75.01	58.19	102.38	
1997	Average	84.38	61.70		
	at Ref. Pt.	86.24	54.88		
1998	Average	48.40		81.07	
	at Ref. Pt.	56.67		84.11	
1999	Average	70.39		77.70	
	at Ref. Pt.	82.73		85.00	
2000	Average	65.29		84.31	
	at Ref. Pt.	72.32		91.97	
2001	Average	54.60			
	at Ref. Pt.	65.08			

X High FWD Deflections

THIS PAGE LEFT INTENTIONALLY BLANK

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25

